

PROCEDURE TO REPLACE POWER SOFA CABLE

Picture 1--- (driver side worm gear) make sure the length (A) of this worm gear is equal to the length of the passenger side worm gear. To do this, hit the extend or retract on the 7 inch touch screen until the lengths of both worm gears are even. (this is with the defective cable end "not" attached to the motor)

Picture 2--- THIS PICTURE IS ON THE P/S BUT USE THIS AS REFERENCE IF REMOVING CABLE ON D/S MOTOR. Once the length of the worm gears are even, proceed replacing the cable. Loosen the 4 nuts on the motor so the motor can be moved enough for you to remove the end of the cable (B) that's connected to the motor. If you notice the bottom nuts are secured while the top nuts there's an opening on the metal bracket so that you can move/rotate the motor for you to pull out the cable connection (B).

Picture 3--- THIS PICTURE IS ON THE P/S BUT USE THIS AS REFERENCE IF REMOVING CABLE ON D/S WORM GEAR. Replace the old cable with a new one. Loosen hex nut to remove old cable. Install new cable---make sure the **inside square cable** is fully inserted or engage to the inside mechanism of the worm gear then tighten the hex nut. For the cable end that is attached to the motor, make sure the **inside square cable** is fully inserted or engage to the inside mechanism of the motor.

Picture 2--- Move/rotate back the motor with the attached cable back to the bracket that holds the motor and tighten the four nuts. Then test sofa by extending and retracting it.

Note: In the future, when using the power sofa, make sure no one is sitting on the power sofa when you are trying to retract or extend the power sofa.

