



Technical Service Bulletin

SUBJECT:		No: TSB-20-00-008	
TECHNICAL SPECIFICATIONS - 2021 MIRAGE		DATE: December 2020	
		MODEL: 2021 Mirage	
CIRCULATE TO:	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER

2021 MIRAGE TECHNICAL AND MECHANICAL FEATURES				
Feature Description	ES	LE	Carbonite Edition (CE)	SE
Engine				
Type	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder
Engine Code	3A92	3A92	3A92	3A92
Materials	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block
Bore x Stroke	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm
Compression Ratio	10.5:1	10.5:1	10.5:1	10.5:1
Displacement	1.2L / 1193 cc	1.2L / 1193 cc	1.2L / 1193 cc	1.2L / 1193 cc
Horsepower	78PS,76hp@6000	78PS,76hp@6000	78PS,76hp@6000	78PS,76hp@6000
Torque	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm
Emissions	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70
Fuel System	ECI-MULTI	ECI-MULTI	ECI-MULTI	ECI-MULTI
Transmission				
5 Speed Manual Transmission	STD	-	-	-
1st	3.545	-	-	-
2nd	1.913	-	-	-
3rd	1.31	-	-	-
4th	0.973	-	-	-
5th	0.804	-	-	-
Reverse	3.214	-	-	-
Final Drive	4.055	-	-	-
INVECS-III CVT	OPT	STD	STD	STD
CVT Automatic Ratios	4.007 - 0.550	4.007 - 0.550	4.007 - 0.550	4.007 - 0.550
Reverse	3.771	3.771	3.771	3.771
Final Drive	3.757	3.757	3.757	3.757
Suspension				
Front	MacPherson type strut	MacPherson type strut	MacPherson type strut	MacPherson type strut
Rear	Torsion Beam	Torsion Beam	Torsion Beam	Torsion Beam
Steering				
Type	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist
Turn Circle - Curb to Curb (ft)	30.2 ft.	30.2 ft.	30.2 ft.	30.2 ft.
Turn Circle - Wall to Wall (ft)	32.1 ft.	32.1 ft.	32.1 ft.	32.1 ft.
Brakes/ Tires/ Wheels				
Front	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc
Rear	Drum Brake	Drum Brake	Drum Brake	Drum Brake
Anti-Lock Brakes	STD	STD	STD	STD
Wheels	14-inch steel wheels with wheel covers	14-inch alloy wheels	14-inch alloy wheels	15-inch two-tone alloy wheels
Tires	165/65R14	165/65R14	165/65R14	175/55R15
Spare Tire (Temporary Tire)	STD	STD	STD	STD
Exterior Dimensions				
Wheelbase (inches)	96.5	96.5	96.5	96.5
Length (inches)	151.4	151.4	151.4	151.4
Width (inches)	65.6	65.6	65.6	65.6
Height (inches)	59.4	59.4	59.4	59.4
Track, Front (inches)	56.3	56.3	56.3	56.3
Track, Rear (inches)	55.7	55.7	55.7	55.7
Min. Ground Clearance (inches)	6.3	6.3	6.3	6.3
Interior Dimensions				
Head Room				
Front Head Room (inches)	39.0	39.0	39.0	39.0
Rear Head Room (inches)	37.2	37.2	37.2	37.2
Leg room				
Front Leg Room (inches)	41.7	41.7	41.7	41.7
Rear Leg Room (inches)	34.2	34.2	34.2	34.2
Shoulder room				
Front Shoulder Room (inches)	51.7	51.7	51.7	51.7
Rear Shoulder Room (inches)	51.0	51.0	51.0	51.0
Hip room				
Front Hip Room (inches)	48.8	48.8	48.8	48.8
Rear Hip Room (inches)	46.4	46.4	46.4	46.4

Copyright 2020 Mitsubishi Motors North America, Inc.

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com).

(5009)

Page 2 of 2
TSB-20-00-008

Feature Description Continued	ES	LE	Carbonite Edition (CE)	SE
SAE volume				
Interior Volume (cu. ft.)	103.3	103.3	103.3	103.3
Passenger Volume (cu. ft.)	86.2	86.2	86.2	86.2
Cargo volume (rear seats up) (cu. ft.)	17.1	17.1	17.1	17.1
Cargo volume (rear seats down) (cu. ft.)	47.0	47.0	47.0	47.0
Capacities				
Passenger Seating Capacity	5	5	5	5
Fuel Tank Capacity	9.2 gal	9.2 gal	9.2 gal	9.2 gal
Weights				
GWR CVT [5MT]	3020 (2910)	3020	3020	3020
Curb Weight CVT [5MT]	2095(2040)	2095	2095	2117
Fuel Economy				
City (MT)	36 (33)	36	36	36
Highway (MT)	43 (41)	43	43	43
Combined (MT)	39 (36)	39	39	39
Electrical				
Battery	55D23L	55D23L	55D23L	55D23L
Alternator (Amps)	85 Amps	85 Amps	85 Amps	85 Amps
Warranties				
Basic	5 years or 60,000 miles	5 years or 60,000 miles	5 years or 60,000 miles	5 years or 60,000 miles
Powertrain	10 years or 100,000 miles	10 years or 100,000 miles	10 years or 100,000 miles	10 years or 100,000 miles
Anti-corrosion	7 years or 100,000 miles	7 years or 100,000 miles	7 years or 100,000 miles	7 years or 100,000 miles
Roadside Assistance	STD	STD	STD	STD