
ATTENTION:

GENERAL MANAGER PARTS MANAGER **CLAIMS PERSONNEL** SERVICE MANAGER

IMPORTANT - All Service Personnel Should Read and Initial in the boxes provided, right.





SUBARU

QUALITY DRIVEN® SERVICE

SERVICE BULLETIN

APPLICABILITY: 2000MY to Current, All Models **SUBJECT:** Replacement Key and Immobilizer

Information

NUMBER: 01-168-09R DATE: 06/17/09

Revised: 01/04/21

INTRODUCTION

The purpose of this bulletin is to provide replacement key and immobilizer information along with an overview of the Subaru Lock Information web-site.

OVERVIEW OF THE RETAILER-ONLY SUBARU LOCK INFORMATION SITE

The Subaru Lock Information Site (SLIS) is located at http://lockinfo.subaru.com, and provides information on how to obtain immobilizer codes and key cut codes for Subaru vehicles from the 2000MY to present. This bulletin identifies the equipment required to initialize (reset) the immobilizer code and cut the key blanks, for both immobilizer and non-immobilizer type keys. Subaru of America began using immobilizer systems in some 2005MY vehicles (please refer to Immobilizer Chart for more detailed information).

KEY BLANK TYPES

Subaru vehicles are equipped with either standard edge cut keys or high security laser cut keys. All high security keys are equipped with an immobilizer device installed. Some standard edge cut keys may or may not be equipped with an immobilizer device. Key blanks can be purchased through normal parts channels. The following page are examples of the Subaru key blank styles:

There are many different styles of key cuts. Be sure to order the correct blank for your particular application and verify your key cutting equipment is compatible. Master keys are shown below.

> 2005-2007 Legacy & Outback edge cut key w/immobilizer (also available without immobilizer)



2008-2011 Impreza, WRX, & STI and 2012-2014 WRX & STI high security laser cut key w/immobilizer



continued...


CAUTION: VEHICLE SERVICING PERFORMED BY UNTRAINED PERSONS COULD RESULT IN SERIOUS INJURY TO THOSE PERSONS OR TO OTHERS.

Subaru Service Bulletins are intended for use by professional technicians ONLY. They are written to inform those technicians of conditions that may occur in some vehicles, or to provide information that could assist in the proper servicing of the vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do the job correctly and safely. If a condition is described, DO NOT assume that this Service Bulletin applies to your vehicle, or that your vehicle will have that condition.

SUBARU OF AMERICA, INC. IS **ISO 14001 COMPLIANT**

ISO 14001 is the international standard for excellence Environmental in Management Systems. Please recycle or dispose of automotive products in a manner that is friendly to our environment and in accordance with all local, state and federal laws and regulations.

2008 Legacy, Outback, and Tribeca edge cut key w/immobilizer and keyless entry







2009 Legacy & Outback and 2009-2014 edge cut key w/immobilizer and keyless entry


2010-2014 Legacy & Outback high security standard laser cut key w/immobilizer and keyless entry





2012+ Impreza, 2013+ Crosstrek and 2014+ Forester, 2015+ Legacy & Outback, and 2015+ WRX & STI edge cut key w/immobilizer and keyless entry

2013+ BRZ edge cut key w/immobilizer and keyless entry





2013-2014 BRZ keyless access with pushbutton start system access key with inside cut high security laser cut emergency key, immobilizer, and keyless entry 2013-2014 Legacy & Outback keyless access with push-button start system access key with high security laser cut emergency key, immobilizer, and keyless entry





2014-2015 Forester, 2014 Crosstrek Hybrid, and 2015 WRX & STI keyless access with push-button start system access key with inside cut high security laser cut emergency key, immobilizer, and keyless entry. (Different part number and key cutting code from 2013 BRZ.)

2015+ BRZ, 2015+ Legacy, Outback, Impreza, Crosstrek and 2016+ WRX, WRX STI and Forester keyless access with push button start system access key with single-sided inside cut high security laser cut emergency key, immobilizer, and keyless entry.





SUBARU VEHICLES EQUIPPED WITH ENGINE IMMOBILIZER SYSTEM

| | Baja | Forester | Impreza | Legacy | Outback | Tribeca | BRZ | Crosstrek |
|---------------|------|----------|----------|--------|-------------|---------|-----|-----------|
| 2005 | n/a | 2.5XT | STi | 2.5GT | 2.5XT, 3.0R | | | |
| 2006 | n/a | 2.5XT | WRX, STi | All | All | All | | |
| 2007 | | 2.5XT | WRX, STi | All | All | All | | |
| 2008 | | 2.5XT | All | All | All | All | | |
| ≥ 2009 | | All | All | All | All | All | All | All |

WEB SITE ACCESS: AUTOMOTIVE SECURITY PROFESSIONALS

The public-facing locksmith site (linked off of STIS, via the "Immobilizer Key Access" button), is a pay site for lock professionals.

WEB SITE ACCESS: AUTHORIZED SUBARU RETAILERS

Authorized Subaru Retailers can access SLIS through Subarunet (under the Service tab, or by directly following the URL http://lockinfo.subaru.com. Access to the immobilizer information is restricted to Subaru Dealership Service Managers and Parts Managers. Access will be granted by using the managers' SKILS user name. Subaru Parts Managers (PM) and Service Managers (SM) who are registered in the Dealer Employee Maintenance Database as such are designated as the only persons at a retailer authorized to access the Subaru Lock Information System (SLIS). Sharing of access information with other retailer employees is not allowed.

Access to and use of the SLIS system is provided strictly for internal retailer use. Use of this system is restricted to Subaru vehicles owned or being repaired by the SM/PM's respective retailer as documented by a properly executed and signed repair order with a complaint requesting a repair requiring the information provided by SLIS.

Use of the SLIS system for any other purpose is strictly forbidden. Anyone found to be providing lock code or immobilizer information to any entity (outside their respective retailer for authorized purposes) will have their (and their retailer's) access immediately terminated and may be referred to law enforcement officials for prosecution if the VIN accessed is subsequently reported to the National Insurance Crime Bureau (NICB) as a stolen vehicle.

Note: It is the retailers' responsibility to perform due diligence by entering or deleting employees in the SKILS Dealer Employee Maintenance Database. This is especially true of Service Manager and Parts Manager position changes.

Step by Step Process To Access the Site

- Once on the SLIS home page, the Service Manager or Parts Manager will be asked for their SKILS user name. At that time, if this is the first time he/she has logged on to the web site, the password "Welcome" should be used. He/she will then be prompted to create a new password (this will not change your current SKILS password).
- The Service Manager or Parts Manager will then be prompted to read the disclaimer and answer "accept" or "not accept". If they answer "not accept", the system will not let them access the immobilizer information.

- A page will then be displayed, allowing for entry of the full 17 character VIN of the vehicle in question.
- Provided the VIN is found in the database, the immobilizer Security ID along with the key/cutting code will appear.
- A charge of \$2.80 will be incurred for each immobilizer request.

Note: Costs are \$9.95 per transaction.

SOA Warranty will only reimburse an approved warranty claim with an Immobilizer Code access cost of \$2.80 per transaction, as a sublet cost. The public-facing (professional locksmith) web site's public access fee of \$9.95 will be reduced to \$2.80 per transaction, if those fees are submitted as a part of a warranty claim.

NASTF SECURE DATA RELEASE MODEL (SDRM)

Positive Identification Policy

NASTF SDRM Subaru Parts and Service Managers who are registered in the Dealer Employee Maintenance Database and are designated as Registry Vehicle Security Professionals (VSPs) shall comply with the following **Positive Identification Policy** when servicing orders for keys, immobilizer reset, or other anti-theft services for vehicles:

- 1. **Inform the Customer** At the time of initial request, ask the customer whether he or she has identification and authority for the service. Inform them of the requirements of this Positive Identification Policy.
- 2. Complete the Form Upon arrival at the job site or when the customer comes in, the VSP shall complete an *Authorization for Automotive Key Generation and/or Immobilizer System / Anti-Theft Services* form (aka *Form D-1*, page 15) that asks for the name, address, phone number, driver's license, vehicle make, model and year, vehicle license plate number, Vehicle Identification Number (VIN), odometer reading, and disclaimer and signature. An invoice or work order that contains all identifying information, when stapled to a duly signed *Form D-1*, is acceptable for collection of this customer information. Subarunet.com user name should be used in place of LSID.
- 3. **Verify I.D.** Verify the customer's valid photo ID and compare to the information provided by the customer on the authorization form. The customer must present a valid state issued driver's license as proof of identity to qualify for use of Registry services.
- 4. **Verify Authority** Ask the customer to present proof of entitlement, which shall include at least one of the following: a valid registration certificate, a valid insurance ID card, a valid insurance policy, vehicle title or a certificate of ownership for the vehicle. The name and address on the proof of entitlement document must match the information on the driver's license to qualify for use of Registry services. In the event that necessary documentation is locked within the vehicle, the vehicle may be entered to verify the authority of the requestor. If upon entry to the vehicle, you are unable to verify the authority of the requestor, the vehicle shall be shut and locked. Do not produce a replacement key, do not provide any key related information to the requestor and destroy all information acquired from the automaker during the transaction.
- 5. **Ask for Signature** Require the customer to read and sign *Form D-1*(page 15). The customer is attesting to:

- a. the information given by the customer being correct and truthful,
- b. the customer having the authority to obtain keys or immobilizer services for the vehicle and,
- c. the customer agreeing to indemnify and hold harmless the service provider and related parties against liability.
- 6. **File the Form** Keep the completed *Form D-1* on file for two (2) years, or longer as required by law.
- 7. **Compliance with Applicable Laws.** The VSP will take all other actions required by applicable laws. In the event of a conflict between the steps set forth herein and the applicable laws, the VSP should comply with applicable laws.
- 8. **Sublet work** A mobile VSP doing work for a body shop, garage, or dealership may accept a legible photocopy of the picture I.D. in order to match it to the registration/title documents. This cannot be a faxed copy. The shop owner or manager must verify the customer's I.D. in person and attest they have done so by signing the bottom of the *Form D-1*

EQUIPMENT

The Subaru Diagnostic System (SDS) is required to reprogram Subaru immobilizer codes. See the Subaru Technical Information System (STIS) (http://techinfo.subaru.com) for more information. Instructions for Immobilizer re-initialization for keys, etc., can be found in the applicable Immobilizer Manual on STIS.

TEACHING OPERATION CODES

A Teaching Operation Code may be needed. The following are the necessary Teaching Codes:

| VEHICLE LINE | MODEL YEAR | TEACHING CODE |
|--------------|------------|---------------|
| Legacy | 2005-2014 | 3781 |
| Impreza | 2005~07 | 3178 |
| | 2008-2011 | 3781 |
| Forester | 2005~08 | 3178 |
| | 2009-2013 | 3781 |
| Tribeca | 2006-2014 | 3781 |

KEY CUTTING MACHINERY RECOMMENDATIONS

Subaru of America recommends the use of the Class C Solutions Group "BD Laser Max" key cutting machine for standard edge cut and high security laser cut keys. Consult http://subaru.service-solutions.com for key machine purchases.

BD Laser Max



RETAILER CENTRALIZED KEY CUTTING SERVICE

The Subaru of America Parts Department offers a key cutting service for retailers who have not purchased the key cutting machine. The service program details can be found on Subarunet.com, in the Parts Operations area, using the "Key Request" link. Forms, details, and costs are found in this area of Subarunet.com.

Key Cutting Tips For Using a BD Laser Max

Every Subaru vehicle has a key code that can be found on the original key ring tag and on Subarunet. This code is known as an indirect (obfuscated) code. To cut a key, the indirect code must be translated to the direct code which is the actual key cutting depth information.

Behind the scenes there is a database for each key type which converts the indirect key codes into the respective direct depth codes required to cut a key. In the past Subaru provided third party companies with this database so they could program their key cutting machines for indirect code cutting. The indirect key code could be typed into the key machine and the key machine would automatically convert the indirect code into the direct depth code and cut the key.

For security reasons Subaru is no longer providing this database. The keys for newer Subaru models must be cut using the direct method. The direct code cut depth information for a given key must be obtained through Subaru Lock Information Service (SLIS).

The following information will guide you through both indirect and direct depth key cutting methods.

Prior to Using Machine

- 1. Locate model and model year in the Key Type & Cutting Information chart found on the following pages to find the vehicle specific cutting information
- 2. Note Cut By, Jaw, Cutter Size and Adapter requirement
- 3. If the Cut By is listed as Code, obtain the key code for the vehicle through Subaru.net or through the SLIS service (listed as Key No in SLIS)
- 4. If the Cut By is listed as Depth, obtain the Depth Code through the SLIS service (listed as Key Code in SLIS)

Machine Tips

- 1. To limit the selection to US market vehicles, from the Main menu go to Cars and change region to North America
- 2. Maintain up-to-date software. Software releases prior to March 2016 will not cut all of the keys listed in this bulletin. Refer to attached BD Laser Max instructions for updating software and sign up for software update alerts at https://blueclassc.mscdirect.com/acton/form/1684/0039:d-0001/0/index.htm
- 3. When inserting a key blank into the jaw, make sure that the jaw is clear of debris
- 4. Press down on the blank as you tighten the jaw to ensure that the blank is fully seated

Cutting a Subaru Key

- 1. From the main menu, select CARS
- 2. Select Subaru
- 3. Select Subaru model
- 4. Select the row with the year range and key type
- 5. If cut by code, select CODES and input the key code
- 6. If cut by depth, select DIRECT and input the depth code per the input sequence chart
- 7. Follow the machine prompts to set up the required cutter size and jaw type
- 8. Follow the machine prompts to set up the tip stop or adapter (if required). For assistance in setting up the tip stop and adapter refer to following pages for more information
- 9. If application calls for F/G jaw, either a F or G jaw can be used
- 10. If an original key is available, check that the image of the key cut matches the original key and proceed with cutting the key

KEY TYPE & CUTTING INFORMATION (Legend for charts on Pages 8-11):


Multiple part numbers = Refer to Electronic Parts Catalog for the correct VIN specific part number **Sub Master** = Master Key without remote keyless entry functions


Valet = Door and ignition only. No remote keyless entry functions. Will not unlock glovebox on Forester and Outback, trunk and glovebox on Legacy and 2008-2011 Impreza, and trunk on BRZ

Push-Button Start Emergency = Emergency Key for Keyless Access with Push-Button Start **Pre-cut available** = A pre-cut replacement key can be ordered through the TRMI service

Tip Stop Setup for A and C Jaws

A and C jaws use an integrated tip stop that slides into place when required






Tip Stop Integrated Into Jaw

Tip Stop Setup for F/G Jaw

F/G jaws use a magnetic tip stop that is placed into the required grooved track



Tip Stop In G1 Position








Adapter (AD03) Setup

4IT 4+4 thin type emergency keys require use of the AD03 adapter that is placed into the jaw as shown prior to inserting the key blank









| Ney Type & Cutting Information Master | 2008MY 57497AG070 | 2009MY 57497AG070 | 2010MY 57497FG080 | 2011MY 57497FG160 | 2012MY 57497FJ021 | 2013MY 57497FJ021 | 2014MY 57497FJ021 | 2015MY 57497FJ230 | 2016MY 57497FJ230 | 2017MY 57497FL00A |
|---------------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| Sub Master | | | | | 57497FJ090 | 57497FJ090 | 57497FJ090 / 57497FJ250 | 57497FJ250 | 57497FJ250 | 57497FL08A |
| Valet | 57497FG010 | 57497FG010 | 57497FG090 | 57497FG170 | - | · | | | · | |
| Pre-cut available | Yes | Yes | Yes | Yes | _{Se} | Yes | Yes | Yes | Yes | Yes |
| Cut Type | Laser | Laser | Laser | Laser | Edge | Edge | Edge | Edge | Edge | Edge |
| Key Type | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 10 | 10 | 10 | 10 | 10 | 10 |
| Key Code Series | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 |
| Cut By | Code | Code | Code | Code | Depth | Depth | Depth | Depth | Depth | Depth |
| Jaw | A | A | A | A | E/G | F/G | F/G | F/G | F/G | F/G |
| Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 1.5 mm |
| Adapter Required | No |
| Push Button Start Emergency | , | , | - | | - | • | • | 57497AL020 | 57497AL020 | 57497AL02A |
| Pre-cut available | 1 | - | - | - | - | - | - | Yes | Yes | Yes |
| Cut Type | | | - | | - | | | Laser | Laser | Laser |
| Key Type | | | - | | - | | | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin |
| Key Code Series | 1 | - | - | - | - | 1 | | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 |
| Cut By | | - | - | - | - | | | Depth | Depth | Depth |
| Jaw | 1 | - | | - | - | 1 | | C | C | C |
| Cutter Size | - | - | - | - | - | 1 | - | 2.5 mm | 2.5 mm | 2.5 mm |
| Adapter Required | - | - | - | - | - | | - | Yes | Yes | Yes |
| Key Type & Cutting Information | 2018MY | 2019MY | 2020MY | 2021MY | | | | | | |
| Master | 57497FL00A | 57497XC01A | 57497XC01A | 57497XC01B | | | | | | |
| Sub Master | 57497FL08A | 57497FL08A | 57497FL08A | 57497FL08B | | | | | | |
| Valet | - | - | - | = | | | | | | |
| Pre-cut available | Yes | Yes | Aes | Yes | | | | | | |
| Cut Type | Edge | Edge | Edge | Edge | | | | | | |
| Key Type | 10 | 10 | 10 | 10 | | | | | | |
| Key Code Series | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | | | | | | |
| BD Laser Setup Cut By | Depth | Depth | Depth | Depth | | | | | | |
| Jaw | F/G | F/G | E/G | F/G | | | | | | |
| Cutter Size | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | | | | | | |
| Adapter Required | No | No | oN | No | | | | | | |
| Push Button Start Emergency | 57497AL02A | 57497AL02A | 57497AL02A | 57497AL02A | | | | | | |
| Pre-cut available | Yes | Yes | Yes | Yes | | | | | | |
| Cut Type | Laser | Laser | Laser | Laser | | | | | | |
| Key Type | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | | | | | | |
| Key Code Series | 90000 - 94999 | 0006 | 90000 - 94999 | 90000 - 94999 | | | | | | |
| BD Laser Setup Cut By | Depth | Depth | Depth | Depth | | | | | | |
| Jaw | C | C | C | Ö | | | | | | |
| Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | | | | | | |
| | | | | | | | | | | |

| Model Key Type | Key Type & Cutting Information | 2008MY | 2009MY | 2010MY | 2011MY | 2012MY | 2013MY | 2014MY | 2015MY | 2016MY | 2017MY |
|------------------|--|---------------|---------------|---------------|------------|------------|------------|------------|---------------|---------------|---------------|
| | Master | 57497AG070 | 57497AG070 | 57497FG080 | 57497FG160 | 57497FG160 | 57497FG160 | 57497FG160 | 57497FJ021 | 57497FJ230 | 57497FJ230 |
| | Sub Master | - | - | | | | | • | 57497FJ090 | 57497FJ250 | 57497FJ250 |
| | Valet | 57497FG010 | 57497FG010 | 57497FG090 | 57497FG170 | 57497FG170 | 57497FG170 | 57497FG170 | - | - | - |
| | Pre-cut available | Yes | SəA | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Cut Type | Laser | Laser | Laser | Laser | Laser | Laser | Laser | Edge | Edge | Edge |
| | Key Type | T0001-3000 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 10 | 10 | 10 |
| | Key Code Series | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 |
| BD Laser | BD Laser Setup Cut By | Code | Code | Code | Code | Code | Code | Code | Depth | Depth | Depth |
| | Jaw | A | A | A | A | A | A | A | F/G | F/G | F/G |
| | Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 1.5 mm | 1.5 mm | 1.5 mm |
| | Adapter Required | No | No | No | No | No | No | No | No | No | No |
| Push E | Push Button Start Emergency | | | | | - | - | T0001-3000 | 57497FJ060 | 57497AL020 | 57497AL020 |
| | Pre-cut available | | | | | , | - | | Yes | Yes | Yes |
| | Cut Type | | | | | | | | Laser | Laser | Laser |
| | Key Type | | , | | | , | , | , | 4IT 5+4 | 4IT 4+4 thin | 4IT 4+4 thin |
| | Key Code Series | | | 1 | | ٠ | - | | 77000 - 78569 | 90000 - 94999 | 90000 - 94999 |
| BD Laser | BD Laser Setup Cut By | | | | | | | | Depth | Depth | Depth |
| | Jaw | | | | 1 | 1 | - | | А | C | C |
| | Cutter Size | - | 1 | | - | - | - | | 2.5 mm | 2.5 mm | 2.5 mm |
| | Adapter Required | | | | | - | 1 | | No | Yes | Yes |
| I Key Type | WRX / STI Key Type & Cutting Information | 2018MY | 2019MY | 2020MY | | | | | | | |
| | Master | 57497FJ230 | 57497FJ230 | 5749VA330 | | | | | | | |
| | Sub Master | 57497FJ250 | 57497FJ250 | 57497FJ250 | | | | | | | |
| | Valet | | | 1 | | | | | | | |
| | Pre-cut available | Yes | Yes | Yes | | | | | | | |
| | Cut Type | Edge | Edge | Edge | | | | | | | |
| | Key Type | 10 | 10 | 10 | | | | | | | |
| | Key Code Series | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | | | | | | | |
| BD Laser | BD Laser Setup Cut By | Depth | Depth | Depth | | | | | | | |
| | Jaw | F/G | E/G | F/G | | | | | | | |
| | Cutter Size | 1.5 mm | 1.5 mm | 1.5 mm | | | | | | | |
| | Adapter Required | No | No | No | | | | | | | |
| Push E | Push Button Start Emergency | 57497AL020 | 57497AL020 | 57497AL020 | | | | | | | |
| | Pre-cut available | Yes | Yes | Yes | | | | | | | |
| | Cut Type | Laser | Laser | Laser | | | | | | | |
| | Key Type | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | | | | | | | |
| | Key Code Series | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 | | | | | | | |
| BD Laser | BD Laser Setup Cut By | Depth | Depth | Depth | | | | | | | |
| | Jaw | C | C | C | | | | | | | |
| | Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | | | | | | | |
| | | 11 | Vec | Ves | | | | | | | |

Page 11 of 20

| Model | Key Type & Cutting Information | 2008MY | 2009MY | 2010MY | 2011MY | 2012MY | 2013MY | 2014MY | 2015MY | 2016MY | 2017MY | 2018MY |
|----------|--------------------------------|--------------|--------------|--------------|----------------|------------|------------|---------------|---------------|---------------|---------------|---------------|
| | Master | 57497FC000 | S | 57497SC010 | 57497AJ070 | 57497AJ070 | 57497AJ070 | 57497FJ021 | 57497FJ021 | 57497FJ230 | 57497FJ230 | 57497FJ230 |
| | Sub Master | 1 | - | , | | , | , | | | | | 1 |
| | Valet | 57497FC030 | 57497SC020 | 57497SC020 | 57497AJ010 | 57497AJ010 | 57497AJ010 | 57497SG000 | 57497SG000 | 57497SG000 | 57497SG000 | 57497SG000 |
| | Pre-cut available | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Cut Type | Edge | Laser | Laser | Laser | Laser | Laser | egb∃ | Edge | $_{ m Edge}$ | Edge | Edge |
| | Key Type | 10 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 10 | 10 | 10 | 10 | 10 |
| | Key Code Series | 30001-37850 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 |
| | BD Laser Setup Cut By | Code | Code | Code | Code | Code | Code | Depth | Depth | Depth | Depth | Depth |
| | Jaw | F/G | A | A | A | A | A | F/G | F/G | F/G | F/G | F/G |
| | Cutter Size | 1.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm |
| | Adapter Required | No | No | No | No | No | No | No | No | No | No | No |
| | Push Button Start Emergency | - | - | - | - | ı | - | 57497FJ060 | 57497FJ060 | 57497AL020 | 57497AL020 | 57497AL020 |
| | Pre-cut available | - | - | - | - | 1 | - | SeX | səX | SəA | səX | Yes |
| | Cut Type | 1 | - | - | | ı | | Laser | Laser | Laser | Laser | Laser |
| | Key Type | 1 | - | , | - | 1 | | 4IT 5+4 | 4IT 5+4 | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin |
| | Key Code Series | | - | - | - | 1 | | 77000 - 78569 | 77000 - 78569 | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 |
| | BD Laser Setup Cut By | - | - | - | - | - | - | Depth | Depth | Depth | Depth | Depth |
| | Jaw | - | - | - | - | - | = | A | Э | Э | Э | С |
| | Cutter Size | - | - | - | - | - | - | 2.5 mm |
| | Adapter Required | | - | | - | 1 | | No | No | Yes | Yes | Yes |
| | Key Type & Cutting Information | 2018MY | 2019MY | 2020MY | 2021MY | | | | | | | |
| Forester | Master | 57497FJ230 | 57497SJ050 | 57497SJ050 | 57497SJ051 | | | | | | | |
| | Sub Master | - | 57497SJ000 | 57497SJ000 | 57497SJ001 | | | | | | | |
| | Valet | 57497SG000 | - | - | - | | | | | | | |
| | Pre-cut available | Yes | Yes | Yes | Yes | | | | | | | |
| | Cut Type | Edge | Edge | Edge | Edge | | | | | | | |
| | Key Type | 10 | 10 | 10 | 10 | | | | | | | |
| | Key Code Series | 32000 - | 32000 - | 32000 - | 32000 - | | | | | | | |
| | | Dant | De:::4 | 7,7,7,7 | Cont | | | | | | | |
| | DD Laser Setup | Depui | E/G | Depui | E/G | | | | | | | |
| | Cutter Size | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | | | | | | | |
| | Adapter Required | å | S. | oZ. | N _o | | | | | | | |
| | Push Button Start Emergency | 57497AL020 | 5749 | 57497AL020 | 57497AL020 | | | | | | | |
| | Pre-cut available | Yes | Yes | Yes | Yes | | | | | | | |
| | Cut Type | Laser | Laser | Laser | Laser | | | | | | | |
| | Key Type | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | | | | | | | |
| | Key Code Series | - 00006 | - 00006 | - 00006 | - 00006 | | | | | | | |
| | | 94999 | 94999 | 94999 | 94999 | | | | | | | |
| | BD Laser Setup Cut By | Depth | Depth | Depth | Depth | | | | | | | |
| | Jaw | C | C | С | C | | | | | | | |
| | Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | | | | | | | |
| | Adapter Required | Yes | Yes | Yes | Yes | | | | | | | |
| | | | | | | | | | | | | |

| Model Rey Type & Cu | Key Type & Cutting Information | 2008MY | 2009MY | 2010MY | 2011MY | 2012MY | 2013MY | 2014MY | 2015MY | 2016MY | 2017MY |
|-----------------------|--------------------------------|------------------|------------------|------------------|------------------|--------|---------------|----------------------------|---------------|--------------------|---------------|
| M | Master | - | - | - | - | - | 57497FJ021 | 57497FJ021 | 57497FJ230 | 57497FJ230 | 57497FJ230 |
| Sub | Sub Master | - | - | - | | - | 57497FJ090 | 57497FJ090 / 57497FJ250 | 57497FJ250 | <i>57</i> 497FJ250 | 57497FJ250 |
| | Valet | | 1 | | - | 1 | 1 | | 1 | | |
| Pre-cut | Pre-cut available | - | | - | - | ı | Yes | Yes | Yes | Yes | Yes |
| Cut | Cut Type | - | - | - | - | - | Edge | Edge | Edge | Edge | Edge |
| Key | Key Type | - | - | - | - | - | 10 | 10 | 10 | 10 | 10 |
| Key Co | Key Code Series | - | | - | - | ı | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 |
| BD Laser Setup | Cut By | - | | - | - | ı | Depth | Depth | Depth | Depth | Depth |
| | Jaw | | 1 | | - | 1 | F/G | F/G | F/G | F/G | E/G |
| | Cutter Size | | | | - | | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm |
| | Adapter Required | - | - | | | 1 | No | No | No | No | No |
| Push Button S | Push Button Start Emergency | - | - | 1 | - | 1 | 1 | 57497FJ060 | 57497AL020 | 57497AL020 | 57497AL020 |
| Pre-cut | Pre-cut available | | | | - | 1 | ı | Yes | Yes | Yes | Yes |
| Cut | Cut Type | | | | - | | | Laser | Laser | Laser | Laser |
| Key | Key Type | | 1 | 1 | | , | | 4IT 5+4 | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin |
| Key Cc | Key Code Series | | - | | - | 1 | 1 | 77000 - 78569 | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 |
| BD Laser Setup Cut By | Cut By | | 1 | | - | | | Depth | Depth | Depth | Depth |
| | Jaw | - | 1 | - | 1 | 1 | | А | C | С | C |
| | Cutter Size | | 1 | - | | | | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm |
| | Adapter Required | | 1 | - | | | | No | Yes | Yes | Yes |
| | Key Type & Cutting Information | 2018MY | 2019MY | 2020MY | 2021MY | | | | | | |
| Crosstrek | Master | 57497FL000 | 57497SJ051 | 57497SJ051 | 57497SJ051 | | | | | | |
| qnS | Sub Master | 57497FL080 | 57497FL081 | 57497FL081 | 57497FL081 | | | | | | |
| Λ | Valet | - | - | - | - | | | | | | |
| Pre-cut | Pre-cut available | Yes | Yes | Yes | Yes | | | | | | |
| Cut | Cut Type | Edge | Edge | Edge | Edge | | | | | | |
| Key | Key Type | 10 | 10 | 10 | 10 | | | | | | |
| Key Cc | Key Code Series | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 | | | | | | |
| BD Laser Setup | Cut By | Depth | Depth | Depth | Depth | | | | | | |
| | Jaw | F/G | F/G | F/G | F/G | | | | | | |
| | Cutter Size | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | | | | | | |
| | Adapter Required | No | No | No | No | | | | | | |
| Push Button S | Push Button Start Emergency | 57497AL020 | 57497AL020 | 57497AL020 | 57497AL020 | | | | | | |
| Pre-cut | Pre-cut available | Yes | Yes | Yes | Yes | | | | | | |
| Cut | Cut Type | Laser | Laser | Laser | Laser | | | | | | |
| Key | Key Type | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | | | | | | |
| Key Cc | Key Code Series | - 00006 | - 00006 | - 00006 | - 00006 | | | | | | |
| | £. | 94999 | 94999 | 94999 | 94999 | | | | | | |
| BD Laser Setup | Cut By | Depth | Depth | Depth | Depth | | | | | | |
| | Jaw | С | C | С | Э | | | | | | |
| | Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | | | | | | |
| | | 1/ | Voc | Vac | 1/2 | | | | | | |

| mation mey mation mey mation mey | 57497AG35A 57497AG12A No Edge 10 30001-37850 Code F/G | 57497AG48A | 57497 A 100A | | | | | | | |
|--|--|---------------|---------------|---------------|------------|------------|------------|---------------|---------------|---------------|
| Sub Master Valet Pre-cut available Cut Type Key Type Key Code Series BD Laser Setup Key Type Cut Type Cut Type Key Type Cut Type Adapter Required Adapter Setup Daw Master Sub Type Key Type | No Edge | | ********** | 57497AJ10A | 57497AJ10A | 57497AJ10A | 57497AJ10A | 57497AL00A | 57497AL00A | 57497AL00A |
| Pre-cut available Cut Type Key Type Key Type Key Type Adapter Required Push Button Start Emergency Pre-cut available Cut Type Key Type Key Type Key Type Key Type Cut By Jaw Duaser Setup Adapter Required Adapter Required Adapter Second Adapter Second Adapter Required Adapter Second Adapter Required Adapter Second Cut Type Cut Type Key Type Key Type Key Type Key Type Cut By Jaw Cut By Jaw Cut By Jaw Cut By Adapter Required Pre-cut available Cut Type Key Type Key Type Adapter Required Push Button Start Emergency Pre-cut available Cut Type Adapter Required Push Button Start Emergency Pre-cut available Cut Type Adapter Second Adapter Required Adapter Second Adapter Required Adapter Second Adapter Second Adapter Second Adapter Required Adapter Second Adapter Required Adapter Second Adapter Second Adapter Second Cut Type Cut Type Cut Type Cut Type Adapter Required Adapter Second Adapter Second Adapter Required Adapter Second A | 57497AG12A No Edge 10 30001-37850 Code | _ | - | - | - | - | - | - | - | - |
| Pre-cut available Cut Type Key Type Key Code Series BD Laser Setup Cut By Adapter Required Cut Type Adapter Required Adapter Required Adapter Required Adapter Required Cut Type Cut Type Key Type Key Type Key Type Cut Type Key Type Key Type Key Type Cut Type Cut Type Adapter Required Push Button Start Emergency Pre-cut available Cut Type | No Edge 10 30001-37850 Code F/G | 57497AG12A | 57497AJ01A | 57497AJ01A | 57497AJ01A | 57497AJ01A | 57497AJ01A | 57497AL01A | 57497AL01A | 57497AL01A |
| Cut Type Key Type Key Type Cutter Size Cutter Size Cut Type Cut Type Key Type Cut By Jaw Cut Type Key Type Key Type Key Type Key Type Adapter Required Cut Type Cut Type Key Type Cut By Jaw Cut By Jaw Cut By Jaw Cut By Adapter Required Push Button Start Emergency Pre-cut available Cut Type Key Type Key Type Cut Type Adapter Required Push Button Start Emergency Pre-cut available Cut Type Adapter Required Adapter Required Adapter Series BD Laser Setup Adapter Required Adapter Required Adapter Required Adapter Series BD Laser Setup Cut By Aw Cut By Aw Cut Type Key Type | Edge 10 30001-37850 Code F/G | No | Yes | Yes | Yes | Yes | SeX | Yes | Yes | Yes |
| Key Type Cut By Daser Setup Cut By Daser Setup Cut By Daser Setup Cut By Daser Setup Cut Type Cut Type Cut Type Cut By Daser Setup | 10 30001-37850 Code F/G | Edge | Laser | Laser | Laser | Laser | Laser | Edge | Edge | Edge |
| Rey Code Series | 30001-37850 Code F/G | 10 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 10 | 10 | 10 |
| BD Laser Setup Cut By Jaw | Code F/G | 30001-37850 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 |
| Jaw | F/G | Code | Code | Code | Code | Code | Code | Depth | Depth | Depth |
| Cutter Size Adapter Required | | F/G | A | A | A | A | A | F/G | F/G | F/G |
| Adapter Required Push Button Start Emergency | 1.5 mm | 1.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 1.5 mm | 1.5 mm | 1.5 mm |
| Push Button Start Emergency Pre-cut available Cut Type Key Type Key Type Adapter Required Adapter Required Naster Sub Master Cut Type Cut Type Key Type Key Type Key Type Key Type Key Type Cut Type Adapter Required Adapter Required Cut Type Cut Type Key Type Key Type Key Type Key Type Cut Type Cut Type Cut Type Cut Type Adapter Required Dush Button Start Emergency Pre-cut available Cut Type Adapter Required Adapter Required Dush Button Start Emergency Pre-cut available Cut Type Cut Typ | No | No | No | No | No | No | No | No | No | No |
| Pre-cut available Cut Type Key Type Key Type Cut By Adapter Required Adapter Required Valet Pre-cut available Cut Type Key Code Series BD Laser Setup Cut By Adapter Required Adapter Required Cut Type Key Code Series BD Laser Setup Adapter Required Adapter Required Cut Type Cut Type Adapter Required Adapter Required Dush Button Start Emergency Pre-cut available Cut Type Adapter Required Adapter Setup Cut Type Cut Type Cut Type Adapter Required Adapter Required Dush Button Start Emergency Rey Type Cut Type | - | - | - | - | - | 57497AJ11A | 57497AJ11A | 57497AL02A | 57497AL02A | 57497AL02A |
| Cut Type Key Type Key Code Series BD Laser Setup Cut By Jaw Cutter Size Adapter Required Adapter Required Naster Sub Master Valet Pre-cut available Cut Type Key Type Key Code Series BD Laser Setup Adapter Required Adapter Required Adapter Required Adapter Required Cut Type Key Code Series BD Laser Setup Cut By Law Cut Type Cut Type Cut Type Key Type Adapter Required Adapter Required Dre-cut available Cut Type Key Type Key Type Adapter Required Draser Setup Adapter Required Adapter Required Adapter Required Draser Setup Adapter Required | - | - | - | - | - | Yes | Yes | Yes | Yes | Yes |
| Key Type | - | - | - | - | - | Laser | Laser | Laser | Laser | Laser |
| Key Code Series | - | - | - | - | - | 4ET 5+5 | 4ET 5+5 | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin |
| BD Laser Setup Cut By Jaw Duter Size Cutter Size Adapter Required Adapter Required Master Sub Master Valet Pre-cut available Cut Type Key Code Series BD Laser Setup Cut By Jaw Dush Button Start Emergency Pre-cut available Cut Type Cut Type Cut Exp Cut Exp Dush Button Start Emergency Pre-cut available Cut Type Key Code Series Rey Code Series BD Laser Setup Cut By Dush Button Start Emergency Pre-cut available Cut Type Key Code Series BD Laser Setup Cut By Jaw Jaw Jaw Jaw Dush Button Start Emergency Exp Code Series BD Laser Setup Cut By Jaw Ja | - | - | - | - | - | T0001-3000 | T0001-3000 | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 |
| Jaw Cutter Size Adapter Required Adapter Required Master Sub Master Valet Pre-cut available Cut Type Key Type Key Code Series BD Laser Setup Cut By Jaw Dush Button Start Emergency Pre-cut available Cut Type Adapter Required Push Button Start Emergency Fre-cut available Cut Type Key Type Key Code Series Rey Code Series BD Laser Setup Cut By Adapter Required Adapter Setup Adapter Required Adapter Setup | - | - | - | - | - | Code | Code | Depth | Depth | Depth |
| Cutter Size Adapter Required Master Sub Master Valet Pre-cut available Cut Type Key Type Key Code Series BD Laser Setup Adapter Required Adapter Required Push Button Start Emergency Pre-cut available Cut Type Key Type Adapter Required Adapter Required Adapter Size Cutt Type Key Type Key Type Cut Type Adapter Required Dush Button Start Emergency Pre-cut available Cut Type Key Type Key Type Adapter Required Dush Button Start Emergency Adapter Required | _ | - | - | - | - | A | A | С | С | С |
| Adapter Required Master Sub Master Sub Master Valet Pre-cut available Cut Type Key Code Series BD Laser Setup Cut By Jaw Cutter Size Adapter Required Push Button Start Emergency Pre-cut available Cut Type Key Code Series Rey Type Key Code Series Rey Code Series Rey Code Series Adapter Required Dush Button Start Emergency Pre-cut available Cut Type Key Type Key Code Series Adapter Setup Adapter Required Adapter Requir | - | - | - | - | - | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm |
| Master Sub Master | - | - | - | - | - | No | No | Yes | Yes | Yes |
| le size ergency le le ses | 2018MY | 2019MY | 2020MY | 2021MY | | | | | | |
| le size crgency le le ses | 57497AL27A | 57497AL37A | 57497AN00A | 57497AN00B | | | | | | |
| le ss size ergency le le ss | - | - | 1 | _ | | | | | | |
| es size r Required ergency le | 57497AL02A | 57497AL01A | 57497XC00A | 57497XC00B | | | | | | |
| ss Size r Required ergency le | Yes | Yes | Yes | Yes | | | | | | |
| ss Size ergency le | Edge | Edge | Edge | Edge | | | | | | |
| ss Size r Required ergency le | 10 | 10 | 10 | 10 | | | | | | |
| Size r Required ergency le | 32000 - 39999 | 32000 - 39999 | 32000-39999 | 32000-39999 | | | | | | |
| Jaw Cutter Size Adapter Required Start Emergency available Type y Type ode Series Cut By Jaw | Depth | Depth | Depth | Depth | | | | | | |
| Cutter Size Adapter Required Start Emergency available Type y Type ode Series Cut By Jaw | F/G | F/G | F/G | F/G | | | | | | |
| Adapter Required Start Emergency available Type y Type ode Series Cut By Jaw | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | | | | | | |
| Start Emergency available Type 7 Type ode Series Cut By Jaw | No | No | No | No | | | | | | |
| available Type y Type ode Series Cut By Jaw | 57497AL02A | 57497AL02A | 57497AL02A | 57497AL02A | | | | | | |
| v Type v Type ode Series Cut By Jaw | Yes | Yes | Yes | Yes | | | | | | |
| y Type ode Series Cut By Jaw | Laser | Laser | Laser | Laser | | | | | | |
| ode Series Cut By Jaw | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | | | | | | |
| Cut By Jaw | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 | | | | | | |
| | Depth | Depth | Depth | Depth | | | | | | |
| | С | С | С | C | | | | | | |
| | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | | | | | | |
| Adapter Required Y | Yes | Yes | Yes | Yes | | | | | | |

| 51497AG38A 57497AG38A 57497AG38A 57497AG38A 57497AG10A 57497AJ10A 57497AJ | Model | Key Type & Cutting Information | 2008MY | 2009MY | 2010MY | 2011MY | 2012MY | 2013MY | 2014MY | 2015MY | 2016MY | 2017MY |
|--|---------|--------------------------------|---------------|---------------|---------------|---------------|------------|------------|------------|---------------|---------------|---------------|
| Sub Master Sub | | Master | 57497AG35A | 57497AG48A | 57497AJ00A | 57497AJ10A | 57497AJ10A | 57497AJ10A | 57497AJ10A | 57497AL00A | 57497AL00A | 57497AL00A |
| Paris | | Sub Master | | - | - | - | - | | - | | - | |
| Pre-cut available No No No Nes | | Valet | 57497AG12A | 57497AG12A | 57497AJ01A | 57497AJ01A | 57497AJ01A | 57497AJ01A | 57497AJ01A | 57497AL01A | 57497AL01A | 57497AL01A |
| Elege Ele | | Pre-cut available | No | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Rey Type Cuttor Start Cuttor S | | Cut Type | Edge | Edge | Laser | Laser | Laser | Laser | Laser | Edge | эāрЭ | Edge |
| Protect Series | | Key Type | 10 | 10 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 4ET 5+5 | 10 | 10 | 10 |
| Pib Laser Stein Ctrl By Code | | Key Code Series | 30001-37850 | 30001-37850 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | T0001-3000 | 32000 - 39999 | 32000 - 39999 | 32000 - 39999 |
| Cuter Size Fig Fig Fig A A A A A A A A A | | BD Laser Setup Cut By | Code | Code | Code | Code | Code | Code | Code | Depth | Depth | Depth |
| Cutter Size 1.5 mm 1.5 mm 2.5 mm 2.5 mm 2.5 mm 1.5 m | | Jaw | F/G | F/G | A | A | A | A | A | F/G | F/G | F/G |
| Adjuster Required No No No No No No No N | | Cutter Size | 1.5 mm | 1.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 1.5 mm | 1.5 mm | 1.5 mm |
| Pash Buton Start Envergency | | Adapter Required | No | No | No | No | No | No | oN | No | oN | No |
| Pre-cut available | | Push Button Start Emergency | - | - | - | - | - | 57497AJ11A | S7497AJ11A | 57497AL02A | S7497AL02A | 57497AL02A |
| Cut Type | | Pre-cut available | - | - | - | - | - | Yes | SeA | Yes | Sey | Yes |
| Rey Type | | Cut Type | - | - | , | - | - | Laser | Laser | Laser | Laser | Laser |
| Rey Code Series | | Key Type | - | - | - | - | - | 4ET 5+5 | 4ET 5+5 | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin |
| BD Laser Setup Cut By - - - - A A Code Depth Cutter Size - - - - - A A C Cutter Size - - - - - - A C Cutter Size - - - - - - A C Master 57497AL27A 57497AL20A 57497AC0A | | Key Code Series | - | - | - | - | - | T0001-3000 | T0001-3000 | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 |
| Jany | | BD Laser Setup Cut By | - | - | - | - | - | Code | Code | Depth | Depth | Depth |
| Cutter Size - - - 2.5 mm 2.5 | | Jaw | - | - | - | - | - | A | Y | С | Э | С |
| Key Type & Cutting Information 2018NY 2020NY 2021NY | | Cutter Size | - | - | - | - | - | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm |
| Key Type & Cutting Information 2018MY 2019MY 2020MY Sub Master 57497AL27A 57497AL37A 57497AN00A Sub Master - - - Sub Master - - - Valet 75497AL02A 57497AL01A 57497AN00A Pre-cut available Yes Yes Yes Key Type 10 10 10 Key Type 10 10 10 Key Code Series 32000 - 39999 32000 - 39999 32000 - 39999 BD Laser Setup Cut By Depth Depth Depth Adapter Required No No No No Pre-cut available Yes Yes Yes Cut Type Laser Laser Laser Laser Key Type 4IT 4+4 thin 4IT 4+4 thin Aft 4+4 thin Key Type C C C Cutter Size 2.5 mm 2.5 mm Adapter Required Yes Yes | | Adapter Required | | | - | 1 | - | No | No | Yes | Yes | Yes |
| 57497AL27A 57497AL27A 57497AN00A | Outback | Key Type & Cutting Information | Z018MY | 2019MY | 2020MY | 2021MY | | | | | | |
| le Yes Yes Yes Yes Yes Edge Edge Edge Edge 10 10 10 10 10 10 10 10 10 10 10 10 10 | | Master | 57497AL27A | 57497AL37A | 57497AN00A | 57497AN00B | | | | | | |
| le Yes Yes Yes Yes Edge Edge Edge Edge Edge 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 15 10 10 10 15 11 15 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 | | Sub Master | - | - | - | | | | | | | |
| le Yes Yes Yes Edge Edge Edge Edge 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 1.5 mm 1.5 mm 1.5 mm 1.5 mm 1.5 mm 1.5 mm No No No No No No No No 1 Laser Laser Laser 1 Laser Laser Laser 1 Depth 00000 - 94999 90000 - 94999 1 C C C 1 C C C 1 C C C 1 C <th></th> <th>Valet</th> <th>57497AL02A</th> <th>57497AL01A</th> <th>57497XC00A</th> <th>57497XC00B</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> | | Valet | 57497AL02A | 57497AL01A | 57497XC00A | 57497XC00B | | | | | | |
| Edge IO | | Pre-cut available | Yes | Yes | Yes | Yes | | | | | | |
| 10 10 10 10 10 | | Cut Type | Edge | Edge | Edge | Edge | | | | | | |
| ss 32000 - 39999 32000 - 39999 32000 - 39999 Depth Depth Depth Depth F/G F/G F/G F/G size 1.5 mm 1.5 mm 1.5 mm r Required No No No ergency 57497AL02A 57497AL02A 57497AL02A fe Yes Yes Yes Laser Laser Laser Laser 4IT 4+4 thin 4IT 4+4 thin 4IT 4+4 thin ss 90000 - 94999 90000 - 94999 90000 - 94999 c C C C c C C C size 2.5 mm 2.5 mm Yes r Required Yes Yes | | Key Type | 10 | 10 | 10 | 10 | | | | | | |
| Size F/G F/G F/G size 1.5 mm 1.5 mm 1.5 mm r Required No No No ergency 57497AL02A 57497AL02A 57497AL02A le Yes Yes Yes Laser Laser Laser Laser 4IT 4+4 thin 4IT 4+4 thin 4IT 4+4 thin ss 90000 - 9499 90000 - 9499 Depth Depth Depth C C C size 2.5 mm 2.5 mm r Required Yes Yes | | Key Code Series | 32000 - 39999 | 32000 - 39999 | 32000-39999 | 32000-39999 | | | | | | |
| F/G F/G F/G F/G size 1.5 mm 1.5 mm 1.5 mm r Required No No No ergency 57497AL02A 57497AL02A 57497AL02A le Yes Yes Yes Laser Laser Laser Laser 4TT 4+4 thin 4TT 4+4 thin 4TT 4+4 thin ss 90000 - 94999 90000 - 94999 90000 - 94999 c C C C c C C C c C C C size 2.5 mm 2.5 mm Yes | | | Depth | Depth | Depth | Depth | | | | | | |
| size 1.5 mm 1.5 mm 1.5 mm r Required No No No ergency 57497AL02A 57497AL02A 57497AL02A le Yes Yes Yes Laser Laser Laser Laser 4IT 4+4 thin 4IT 4+4 thin 4IT 4+4 thin ss 90000 - 9499 90000 - 9499 Depth Depth Depth C C C c C C c C C c C C c C C c C C c Yes Yes | | Jaw | F/G | F/G | F/G | F/G | | | | | | |
| Required No No No ergency 57497AL02A 57497AL02A 57497AL02A le Yes Yes Yes Laser Laser Laser Laser 4IT 4+4 thin 4IT 4+4 thin 4IT 4+4 thin es 90000 - 9499 90000 - 9499 pepth Depth Depth C C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C | | Cutter Size | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | | | | | | |
| ergency 57497AL02A 57497AL02A 57497AL02A 57497AL02A le Yes Yes Yes Laser Laser Laser Laser \$4T7 4+4 thin 4T7 4+4 thin 4T7 4+4 thin \$5s 90000 - 94999 90000 - 94999 90000 - 94999 \$1 C C C \$1 C C C \$2.5 mm 2.5 mm 2.5 mm \$1 Yes Yes | | Adapter Required | No | No | No | No | | | | | | |
| Fe | | Push Button Start Emergency | 57497AL02A | 57497AL02A | 57497AL02A | 57497AL02A | | | | | | |
| Laser Laser Laser Laser 4IT 4+4 thin 4IT 4+4 thin 4IT 4+4 thin 5s 90000 - 94999 90000 - 94999 Depth Depth Depth C C C c C C c C C c C C c C C c C C c C C c C C c C C c C C c C C | | Pre-cut available | Yes | Yes | Yes | Yes | | | | | | |
| ss 4TT 4+4 thin 4TT 4+4 thin 4TT 4+4 thin ss 90000 - 94999 90000 - 94999 90000 - 94999 Depth Depth Depth Depth C C C C size 2.5 mm 2.5 mm Yes | | Cut Type | Laser | Laser | Laser | Laser | | | | | | |
| cs 90000 - 94999 90000 - 94999 90000 - 94999 Depth Depth Depth Depth C C C C size 2.5 mm 2.5 mm 2.5 mm r Required Yes Yes | | Key Type | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | | | | | | |
| Depth Depth Depth Depth C C C C size 2.5 mm 2.5 mm Yes | | Key Code Series | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 | | | | | | |
| C C C C 2.5 mm 2.5 mm 2.5 mm Yes Yes Yes | | BD Laser Setup Cut By | Depth | Depth | Depth | Depth | | | | | | |
| 2.5 mm 2.5 mm 2.5 mm Yes Yes Yes | | Jaw | C | C | С | C | | | | | | |
| Yes Yes Yes | | Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | | | | | | |
| | | Adapter Required | Yes | Yes | Yes | Yes | | | | | | |

| Model | Key Type & C | Key Type & Cutting Information | 2008MY | 2009MY | Z010MY | ZOTIMIX | Z012MY | 2013MY | 2014MY | Z015MY | 2016MY | X1M/107 |
|-------|-----------------|--------------------------------|------------------|-------------------------------|---------------|---------|--------|---------------|---------------|---------------|----------------|---------------|
| | _ | Master | - | 1 | | - | _ | 57497CA110 | 57497CA110 | 57497CA310 | 57497CA310 | 57497CA310 |
| | Suk | Sub Master | | , | 1 | , | | , | , | 1 | | |
| | | Valet | - | - | | - | - | 57497CA250 | 57497CA250 | 57497CA250 | 57497CA250 | 57497CA250 |
| | Pre-cı | Pre-cut available | - | - | - | - | - | Yes | Yes | Yes | Yes | Yes |
| | CL | Cut Type | - | - | - | - | - | Edge | Edge | Edge | Edge | Edge |
| | Ke | Key Type | - | - | - | - | - | 10 | 10 | 10 | 10 | 10 |
| | Key C | Key Code Series | - | - | - | - | - | 90000 - 00005 | 96669 - 00005 | 90000 - 00005 | 66669 - 000005 | 90000 - 00005 |
| | BD Laser Setup | Cut By | | | | | - | Code | Code | Code | Code | Code |
| | | Jaw | - | - | , | - | - | F/G | F/G | F/G | F/G | F/G |
| | | Cutter Size | | | | | - | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm | 1.5 mm |
| | | Adapter Required | - | - | - | - | - | No | No | No | No | No |
| | Push Button | Push Button Start Emergency | - | - | 1 | - | - | 57497CA200 | 57497CA200 | 57497AL020 | 57497AL020 | 57497AL020 |
| | Pre-cı | Pre-cut available | - | - | - | - | - | Yes | Yes | Yes | Yes | Yes |
| | C | Cut Type | - | - | - | - | - | Laser | Laser | Laser | Laser | Laser |
| | Ke | Key Type | 1 | - | 1 | - | - | 4IT 5+5 | 4IT 5+5 | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin |
| | Key C | Key Code Series | - | - | - | - | - | 40000 - 49999 | 40000 - 49999 | 90000 - 94999 | 90000 - 94999 | 90000 - 94999 |
| | BD Laser Setup | Cut By | | | 1 | | - | Depth | Depth | Depth | Depth | Depth |
| | | Jaw | - | - | - | - | - | С | С | С | С | С |
| | | Cutter Size | | | 1 | | 1 | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm | 2.5 mm |
| | | Adapter Required | - | | 1 | , | 1 | No | No | Yes | Yes | Yes |
| | Key Type & C | Key Type & Cutting Information | 2018MY | 2019MY | 2020MY | | | | | | | |
| BRZ | V | Master | 57497CA310 | 57497CA310 | - | | | | | | | |
| | Suk | Sub Master | - | 1 | 1 | | | | | | | |
| | | Valet | 57497CA250 | 57497CA250 | 1 | | | | | | | |
| | Pre-cı | Pre-cut available | Yes | Yes | - | | | | | | | |
| | Cr | Cut Type | Edge | Edge | - | | | | | | | |
| | Ke | Key Type | 10 | 10 | 1 | | | | | | | |
| | Key C | Key Code Series | - 0000 <i>\$</i> | 90000 - 00005 | 1 | | | | | | | |
| | | Cut By | Code | Code | 1 | | | | | | | |
| | DD I geen Catum | Jaw | F/G | F/G | - | | | | | | | |
| | DD Laser Setup | Cutter Size | 1.5 mm | 1.5 mm | - | | | | | | | |
| | | Adapter Required | No | No | - | | | | | | | |
| | Push Button | Push Button Start Emergency | 57497AL020 | 57497AL020 | 57497AL020 | | | | | | | |
| | Pre-cı | Pre-cut available | Yes | Yes | Yes | | | | | | | |
| | ŭ | Cut Type | Laser | Laser | Laser | | | | | | | |
| | Ke | Key Type | 4IT 4+4 thin | 4IT 4+4 thin | 4IT 4+4 thin | | | | | | | |
| | Key C | Key Code Series | 90000 - 94999 | 90000 - 94999 90000 - 94999 | 90000 - 94999 | | | | | | | |
| | | Cut By | Depth | Depth | Depth | | | | | | | |
| | DD I agas Cotus | Jaw | C | С | C | | | | | | | |
| | DD Laser Setup | Cutter Size | 2.5 mm | 2.5 mm | 2.5 mm | | | | | | | |
| | | A donter Degined | Ves | Ves | Ves | _ | _ | _ | _ | | | |


| 2021MY | 57497XC01A | - | 57497XC00A | Yes | Edge | 10 | 32000 - 39999 | Depth | F/G | 1.5 mm | No | 57497AL02A | Yes | Laser | 4IT 4+4 thin | 90000 - 94999 | Depth | С | 2.5 mm | Yes |
|--|------------|------------|------------|-------------------|----------|----------|-----------------|-----------------------|-----|-------------|------------------|-----------------------------|-------------------|----------|--------------|-------------------------------|-----------------------|-----|-------------|------------------|
| 2020MY | 57497XC01A | 1 | 57497XC00A | Yes | Edge | 10 | 32000 - 39999 | Depth | F/G | 1.5 mm | No | 57497AL02A | Yes | Laser | 4IT 4+4 thin | 90000 - 94999 90000 - 94999 | Depth | С | 2.5 mm | Yes |
| 2019MY | 57497XC01A | - | 57497XC00A | Yes | Edge | 10 | 32000 - 39999 | Depth | F/G | 1.5 mm | No | 57497AL02A | Yes | Laser | 4IT 4+4 thin | 90000 - 94999 | Depth | C | 2.5 mm | Yes |
| Model Key Type & Cutting Information | Master | Sub Master | Valet | Pre-cut available | Cut Type | Key Type | Key Code Series | BD Laser Setup Cut By | Jaw | Cutter Size | Adapter Required | Push Button Start Emergency | Pre-cut available | Cut Type | Key Type | Key Code Series | BD Laser Setup Cut By | Jaw | Cutter Size | Adapter Required |
| Model | | | | | | | | | | ****** | Ascell | | | | | | | | | |

| Model | Model Rey type & Cutting Information 2008/01x 2009/01x 2010/01x | ting information | Z 1/1/2/1/Z | Z10/2/07 | ZUIUIVI X | ZUIIMIZ | Z012M1 | ZINCI07 | Z014INLX |
|--------|---|-----------------------------|-------------|-------------|-------------|-------------|---|--|-------------|
| | Ma | Master | 57497AG35A | 57497AG48A | 57497XA12A | 57497XA20A | 57497XA20A | 57497AG35A 57497AG48A 57497XA12A 57497XA20A 57497XA20A 57497XA20A 57497XA20A | 57497XA20A |
| | N duS | Sub Master | - | - | - | - | - | - | - |
| | Va | Valet | 57497AG12A | 57497AG12A | 57497XA13A | 57497XA13A | 57497XA13A | 57497AG12A 57497AG12A 57497XA13A 57497XA13A 57497XA13A 57497XA13A 57497XA13A | 57497XA13A |
| | Pre-cut | Pre-cut available | No | oN | No | No | No | oN | No |
| | Cut | Cut Type | Edge | Edge | Edge | Edge | Edge | $_{ m Edge}$ | Edge |
| Tuiboo | Key | Key Type | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Lineca | Key Coc | Key Code Series | 30001-37850 | 30001-37850 | 30001-37850 | 30001-37850 | 30001-37850 30001-37850 30001-37850 30001-37850 | 30001-37850 | 30001-37850 |
| | | Cut By | Code | Code | Code | Code | Code | Code | Code |
| | DD I com Catura | Jaw | F/G | E/G | F/G | F/G | F/G | E/G | F/G |
| | DD Laser Setup | Cutter Size | 1.5 mm | 1.5 mm | 1.5 mm |
| | | Adapter Required | No | No | No | No | No | No | No |
| | Push Button St | Push Button Start Emergency | - | - | - | - | - | - | - |
| | | | | | | | | | |

Depth Code Input Sequence


Edge cut key depth code input sequence 2012MY+ Impreza, 2015MY+ WRX/STI 2013MY+ Crosstrek, 2014MY+ Forester, 2015MY+ Legacy, 2015MY+ Outback

The machine will automatically populate the second row Depth Code: 1-2-3-4-5-6-7-8-9-10




Emergency key depth code input sequence (4IT 4+4 key) 2015MY+ Impreza, 2016MY+ WRX/STI 2015MY+ Crosstrek, 2016MY+ Forester, 2015MY+ Legacy, 2015MY+ Outback, 2015MY+ BRZ

Enter code in reverse order from sequence provided Depth Code: 1-2-3-4-5-6-7-8




Emergency key depth code input sequence (4IT 5+5 key) 2013-14MY BRZ

Enter code in reverse order from sequence provided Depth Code: 1-2-3-4-5-6-7-8-9-10



Emergency key depth code input sequence (4IT 5+4 key) 2015MY WRX/STI, 2014MY Crosstrek, 2014-15MY Forester

Enter code in reverse order from sequence provided
Depth Code: 1-2-3-4-5-*-7-8-9-10







BD Laser Max Keyonline Via PC (USB Memory Stick) Update Instruction

USB Memory stick requirements: 2-4 GB flash/thumb drive. Drive must be free of information prior to performing the update.

- 1. From the main menu select:
 - a. Setup
 - b. Updates
 - c. Keyonline via pc
 - i. Do you want to update the software?
 - 1. Select "Yes".
 - ii. Please insert the USB memory stick in to the console and press "OK".
 - 1. The BD Laser Max will then transfer a ".csk" file to the USB memory stick.
 - iii. Once the file transfer is complete the machine will display "Please remove the USB memory stick, download the update from Keyonline website on your personal computer and save it on the USB memory stick"
 - 1. Select "OK" and remove the USB memory stick from the console.
- 2. Insert USB memory stick in to desktop/laptop.
- 3. Visit http://bdlaser.mscdirect.com/
- 4. Double click "choose file".
- 5. Search and select the ".csk" file downloaded from the BD Laser Max and select "open".
- 6. Click "request update"
 - a. A dialogue box with the message "This action may require some time. Please wait" will appear. Select "OK".
- 7. The update package will then be created.
 - a. Once the package creation is completed select
 - i. For Windows users: Select "SAVE" and then "SAVE AS" under the drive that is associated with your USB drive.
 - ii. For Chrome users: Select the "Show in folder" option, then pull to transfer the file to the USB drive.
- 8. Once the download/transfer is complete, safely eject the USB memory stick from the desktop/laptop.
- 9. Return to the BD Laser Max which displays the message "Please insert the USB memory stick containing the update".
 - a. Insert the USB memory stick and select "OK".
- 10. The BD Laser Max will then display the message "Do you want to update the software?"
 - a. Select "yes".
 - b. Please note: The update process may take some time.
- 11. Once the update file transfer is complete the machine will display "Software update successfully installed". Select "OK" then remove the USB memory stick and save for future use.

1301 E. 9th Street Suite, #700 · Cleveland, OH 44114 Email: keymachines@MSCDirect.com · Phone: 866-438-6767 Confidential – Property of Class C Solutions Group, a business of MSC Industrial Supply Co.

Form D1

AUTHORIZATION FOR AUTOMOTIVE KEY GENERATION and/or IMMOBILIZER SYSTEM/ANTI-THEFT SERVICES

(The LSID Holder must fill out this form, after personally looking at the photo I.D., the registration and the VIN plate on the Vehicle. These forms are to be kept for 2 years in a secured location as per the NASTF positive I.D. Policy. The NASTF Director of Operations will randomly audit these forms to ensure compliance with positive I.D policy. Failure to produce D-1 Forms when requested will result in LSID registry suspension and possible termination.)

I hereby certify that I have the authority to order keys and immobilizer system reset services for the vehicle indicated below. I agree that the information I am providing is true and correct. Further, to the maximum extent permitted by applicable law, I agree to indemnify and hold harmless the service provider listed below and related parties providing security information from any and all liability or claims that may arise from the performance of this service. I further agree to indemnify the automaker and their affiliates, successors, assignees, and nominees from any and all claims, losses, or costs (including reasonable attorney's fees) arising from any acts or omissions of the service provider, the service provider's employees, subcontractors, or agents.

| Vehicle Owner/Customer | Name: | | | |
|--|-------------------------|---------------------|-----------------------|---------------------|
| Address: | | | | |
| City / State / Zip Code: | | | | |
| Telephone: | | | | |
| | | | | |
| Vehicle O | wner/Customer Signature | | | Date |
| Driver's License Number ¹ | | State | | Expiration Date |
| Other Form of ID (specify typ | e and number): | | | |
| | | 1 | | |
| Vehicle Year | Make | | Model | Color: |
| License Plate Number | | | _State of Vehicle Reg | istration |
| Vehicle ID Number (VIN) (17 | characters) | | | |
| | | | | |
| Odometer Reading (mileage) |): | | (or) Not Availabl | e: □ |
| For Dealership/Auctions: | PO / Stock # | | 1 | |
| Service Performed: | ☐ Key cut from code | ☐ Immobilizer reset | ☐ Other (describe b | elow) : |
| | | | | |
| VSP/Service Provider Busine | ess Name | | | |
| | | | | |
| Phone: | | | | |
| Address: | | | | |
| City / State / Zip Code: | | | | |
| VSP/Technician Name | | | | Subaru.net Username |
| VOI / Technician i vaine | | | | I / / |
| VSP/Technician Signature | | | | 1 1 |
| Ocatacation Obs. C. 184 | o Oi ma a trong | | | |
| Contracting Shop Owner/Manage (Item 8 of the Positive ID Policy) | er Signature | | | Date |

1 IMPORTANT: Mobile Service Providers - If the VSP is not present at the time vehicle is received for service by a contracting service facility, the contracting service facility must make a photocopy of the vehicle owner's driver's license and attach to this form. Additionally, a valid registration must be left with the vehicle so that the VSP can verify that the driver's license matches the ownership documentation.