

Tire Positioning Before New Vehicle Delivery

Service Category General

Section Pre-Delivery Service

Market USA

Toyota Supports
ASE Certification 

Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION
2022	ES250, ES300H, ES350, GX460, IS300, IS350, LC500, LC500C, LC500H, LS500, LS500H, NX250, NX350, NX350H, NX450H+, RC F, RC300, RC350, RX350, RX450H, UX200, UX250H	

Introduction

During the manufacturing process, tires are mounted on the vehicle as matched sets to help reduce conditions such as pulling or drifting. If the wheels are replaced or refinished before vehicle delivery, it is important that the tires remain on the vehicle in the same location and in the same direction of rotation.

Follow the Tire Positioning Procedure in this bulletin to ensure that the original tires stay in the same location on the vehicle.

Warranty Information

OP CODE	DESCRIPTION	TIME	OFP	T1	T2
N/A	Not Applicable to Warranty	–	–	–	–

Tire Positioning Procedure

1. Mark the tire installation position on the inward facing tire sidewall.
Example: Front Right = FR, Front Left = FL, Rear Right = RR, Rear Left = RL
2. Install the original tires on the NEW or refinished wheels with the marked side facing inward.
3. Balance the tire/wheel assemblies.
4. Place the tire/wheel assemblies on the vehicle in the marked positions.

NOTE

Torque the wheel fasteners in sequence to the proper torque value.