



# Technical Service Bulletin

## 17 UV leak additive for finding oil leaks

17 22 17 2060750/3 March 3, 2022. Supersedes Technical Service Bulletin Group 17 number 21-12 dated February 2, 2021 for reasons listed below.

Model(s)	Year	VIN Range	Vehicle-Specific Equipment
All	2001 - 2023	All	Not Applicable

## Condition

REVISION HISTORY		
Revision	Date	Purpose
3	-	Updated Vehicle Data (Added MY22/23)
2	02/08/2021	Revised <i>Service</i> (Updated Step 1)
1	10/05/2020	Initial publication

### Customer states:

One or more of the following statements:

- There may be a smell in the engine compartment.
- An oil leak is present in the front end of the car or in the area of the engine compartment.
- Oil marks may be found under the car.
- There is engine oil loss.

### Workshop findings:

- An oil leak can be found in the engine area.

## Technical Background

This pigment supports the search for oil leaks from engines. The pigment of the fluorescent yellow leak search additive makes leaks visible and is therefore ideal for finding oil leaks. The UV pigment mixes with the engine oil and glows fluorescent yellow when the UV lamp shines onto the point of the leak. Depending on the intensity of the leak, the engine oil may even be leaking at idle speed; very small leaks, on the other hand, can also require a test drive. The additive can remain in the engine and is suitable for gas and diesel engines; an oil change is not required.



**Tip:** Engine cleaning before following the instructions below is not necessary.



# Technical Service Bulletin

---



## Note:

It can be used for all combustion engines. **Do not use** for locating transmission leaks.

## Production Solution

Not applicable.

## Service

1. Add one bottle of search additive G 052 940 A1 to the engine via the oil filler neck. One bottle is sufficient for up to 5 quarts of engine oil. For larger oil quantities, use double the amount. There is no danger of damaging the engine if extra additive is put in.
2. Run the engine and locate the leak using UV lamp VAS 231005 or equivalent (Figure 1).




**Figure 1.** Example of finding a leak using the additive and UV lamp.

## Warranty

This TSB is informational only and not applicable to any Audi Warranty.

## Required Parts and Tools

Always check with your Parts Department and/or ETKA for the latest information and parts bulletins.



# Technical Service Bulletin

---

Part Number	Part Description	Quantity
See ETKA	Fasteners, Bolts, Nuts, and Screws as needed per the Repair Manual	See ETKA/ELSA
G 052940A1	Leak search additive	Shop Supply

Tool Number	Tool Description
VAS231005 (WVA-074) or equivalent	UV lamp

## Additional Information

All parts and service references provided in this TSB (2060750) are subject to change and/or removal.

©2022 Audi of America, Inc. All rights reserved. The information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites without the prior expressed written permission of the publisher.