

Xentry Battery Tester results disagree with workshop assessment

Topic number	LI54.10-P-071499
Version	2
Function group	54.10 - Battery, power supply, voltage converter
Date	3/31/22
Validity	118, 177, 247, 167, 205, 213, 217, 222, 238, 253, 257, 206, 223, 232, 243, 247, 295, 297, 463 except code U98 (LITHIUM-IONEN-STARTERBATTERIE (LISB))
Reason for change	updating model validity

Complaint

The result from the XENTRY battery test does not match the current state of the battery.

Cause

The XENTRY battery tester uses the stored on-board electrical system data in the SAM module to access the health of the 12 volt battery. The XENTRY battery test may not take into account a single discharge event because the SAM cannot record the data if the battery is discharged.

Note: A discharged battery does not necessarily need to be replaced. A discharged battery may be recovered with no permanent damage.

Remedy

1) If the battery is discharged, charge battery. Review WS54.00-P-0037B for minimum charger specifications.

Note the amperage difference between trickle (maintainer) chargers of at least 16A and quick chargers of at least 30A.

Review AP54.10-P-5449U. Note when battery is sufficiently charged the charger current is less 5A.

2) While charging the battery analyze the vehicle data to determine root cause of discharge using the following data points:

A) Review FSAM on-board electrical data conspicuous records

NOTE: For guidance on use of the on-board electrical data please review the AKUBIS video titled "New on-board electrical system diagnosis shown on BR 166". The video can be accessed through WIS by following the path WSM--> content by model series --> passenger cars --> ML-Class --> Model 166 --> group 54 --> New on-board electrical system diagnosis.

B) Customer description

C) Midtronics test

Determine if root cause is due:

XENTRY TIPS

- vehicle technical issue?
- customer behavior?

3) If battery still does not accept charge, create a PTSS case.

Must include with case:

- A) Amperage setting of charger and time battery was on charger
- B) Xentry Battery Tester results
- C) Voltage of battery taken with multimeter: Do not connect charger while taking measurements
- D) SAM control unit log
- E) Midtronics tester results
- F) Workshop analysis of conspicuous SAM data
- G) Root cause analysis for battery discharge based on the above documents (technical, customer, etc.)

NOTE: For expedited results when creating a case write customer complaint as "Xentry Battery Tester implausible".

Symptoms				
Overall vehicle > Power supply > Battery/On-board electrical system > Battery function > Battery discharges				
Operation numbers/damage codes				
Op. no.	Operation text	Time	Damage code	Note