



Back Office Mack Chassis - Secondary Gauge Set Up - Model Year 2018 and Newer



> Internal Content

Refer to the tables below for the correct SIA and Variant settings for Secondary Gauge Clusters.

SIA Setting	Description
0	U2GAUGE (none)
1	2GP-ETPB (Engine Oil Temperature, Transmission Oil Temperature, Pyrometer, Boost Pressure)
2	2GP-ETPA (Engine Oil Temperature, Transmission Oil Temperature, Pyrometer, Brake Application Pressure)
3	2GP-BTPA (Boost Pressure, Transmission Oil Temperature, Pyrometer, Brake Application Pressure)

Variant	Description	Setting Option
RJI	BOOST PSI	0=NO / 1=YES
RJP	ENG OIL TEMP	0=OFF / 1=ON
RJH	BRAKE APP GAUGE	0=NO / 1=YES THIS WILL ALSO NEED SENSOR # 22443498 & OVERLAY HARNESS # 20877267

Parameter	Description	Setting Option
ED	Transmission oil temperature	1
RKI	Transmission Oil Temperature Digital Gauge Source	2
RQQ	Transmission Oil Temperature Fault Log, Enable	1
SCV	Trans Oil Temp Broadcast J1939 TRF1, Enable	1



Tags

[k64044455](#)

[mack](#)

Related links and attachments

No links or attachments available



Feedback

[Give feedback](#)

to help improve the content of this article