



# Service Bulletin

Bulletin No.: 22-NA-039

Date: February, 2022

## INFORMATION

**Subject:** Information on Front License Plate Adapter Bracket Installation During PDI

Brand:	Model:	Model Year:		VIN:		Engine:	Transmission:
		from	to	from	to		
GMC	HUMMER EV	2022	2022			All	All

Involved Region or Country	United States
Additional Options (RPOs)	
Condition	Installation of front license plate adapter bracket during PDI.
Correction	Follow the appropriate installations if a front license plate is or is not required.

### Service Procedure

**Note:** In the dealer PDI trunk kit from the factory, you will find the silver front license plate adapter and a set of 4 retainers and screws.

#### Procedure Without Front License Plate



5990749

**Note:** When not equipped with a front license plate, the silver license plate bracket is to be secured to the front bumper assembly.

1. Remove the black bolt/screws (1) from the lower portion of the fascia.

2. Align the bottom of the license plate bracket to the black T- shaped retainers (2).
3. Push the bracket into place while aligning and securing the 4 tabs across the top into the fascia. Push gently to fully seat the bracket assembly.
4. Secure the black bolt/screws (1) into the lower portion of the fascia.

#### Tighten

Tighten the bolt/screws to 2,5 Nm (22 lb in).



5990750

### Procedure With Front License Plate



5990751

**Note:** This installation procedure should only be completed when the front license plate is ready to be installed.

1. Drill four 4.5 mm (3/16") holes into the license plate bracket. There are 4 small dimples on the back of the bracket that must be drilled out.



5990752

**Note:** If the retainers are already installed, give any extra retainers to the customer.

2. In the dealer PDI trunk kit, there are 4 white retainer and 4 license plate screws. Insert the white retainers into the front bumper.



5990749

3. Install the pre-drilled license plate bracket onto the front bumper. Refer to Steps #1-4 from the above procedure.



5990753

**Caution:** To avoid damaging the license plate, do NOT over torque the screws.

4. Install the customer's license plate over the top side of the silver painted bracket and secure with the 4 license plate screws.

### Warranty Information

The labor time for installing the front license plate adapter is included in the PDI time.

Version	1
Modified	Released February 18, 2022

GM bulletins are intended for use by professional technicians, NOT a "do-it-yourselfer". They are written to inform these technicians of conditions that may occur on some vehicles, or to provide information that could assist in the proper service of a vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do a job properly and safely. If a condition is described, DO NOT assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See your GM dealer for information on whether your vehicle may benefit from the information.



WE SUPPORT VOLUNTARY  
TECHNICIAN  
CERTIFICATION