

TIGER 900 BOND EDITION SHIPPING WITH ADDITIONAL TIRES



Notice Information

Ref	21595
Posted Date:	
Posted To:	General Manager / Business Owner, Technician, Parts / Accessories Coordinator, Sales Executive, Clothing Sales, Sales Manager, Aftersales Manager, Service Leader / Advisor, Accounts / Admin, Marketing Executive
Subject:	Service/Technical

TOL NOTICE (USCA) - May 26, 2022

TOL Ref. #21595-SVC

TIGER 900 BOND EDITION SHIPPING WITH ADDITIONAL TIRES

A pair of Michelin Anakee Wild tires will be included in the delivery crate for the Tiger 900 Bond Edition motorcycles. These approved tires are offered as part of the complete motorcycle and are not to be removed or sold separately from the motorcycle.

Should the customer wish, these tires can be fitted at PDI. The removed OE tires will remain the property of the customer.

Dealers should charge the customer their standard labor rate for installation.

If the customer opts for the Michelin Anakee Wild tires to be fitted from new, dealers must inform the customer at the motorcycle handover that these tires will affect the motorcycle's handling performance. A warning decal is placed on the tank as a permanent reminder - see below.



Dealers must inform customers as follows:

1. Triumph recommends that the motorcycle is not driven in excess of 60mph when fitted with the Michelin Anakee Wild tires.
2. Triumph warns that cornering lean angles will be reduced.
3. Triumph warns that additional care should be taken when riding on wet roads.

4. When operating the motorcycle for the first time, the customer should exercise extreme caution and care until accustomed with the bike's handling characteristics when fitted with these tires.
5. The approved dual-purpose tire is fitted with standard tire wear indicators and once this is worn down to 2mm, the tire must be replaced.
6. Triumph warns that tires must be inflated to 34 Fr /42 Rr psi for use on the highway.

Refer to the table below for tire specifications.

TIGER 900 BOND EDITION	STANDARD	MICHELIN ANAKEE WILD™
TIRE SIZES:		
Front	90/90-21 M/C 54V	90/90-21 54R M+S
Rear	150/70 R17 M/C 69V	150/70R17 69R M+S
TIRE PRESSURES (COLD):		
Front	2.34 bar (34 lb/in²)	2.34 bar (34 lb/in²)
Rear	2.89 bar (42 lb/in²)	2.89 bar (42 lb/in²)

If you have any additional questions, please contact Triumph Customer Support at (888) 284-6288.