

Manufacturer's Certificate

Taycan (Y1A)

22/22 ENU 4400

4

Approved: Wheels and Tires (22/22)

Revision: This bulletin replaces bulletin Group 4 15/22, dated May 3 , 2022.

Model Year: As of 2020

Vehicle Type: **Taycan (Sedan + CUV): Taycan / Taycan Sport Turismo / 4S / 4S Sport Turismo / Turbo / Turbo Sport Turismo / Turbo S / Turbo S Sport Turismo / GTS / GTS Sport Turismo**

Information: Start of new model year 28/2022

Sizes: **Permissible tire and wheel sizes**  
(RO = rim offset in mm, FA = Front axle, RA = Rear axle)

Tires	Tire sizes	Wheel sizes	Snow chains
<b>Taycan / Taycan Sport Turismo / 4S / 4S Sport Turismo / Turbo / Turbo Sport Turismo / Turbo S / Turbo S Sport Turismo / GTS / GTS Sport Turismo (Sedan + CUV)</b>			
Summer	19" FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL  Not for Turbo and Turbo S.  Not for GTS and GTS Sport Turismo  *)	FA: 8J x 19, RO 50 RA: 10J x 19, RO 47	No
	20" FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL  Not for Turbo S vehicles	FA: 9J x 20, RO 54 RA: 11J x 20, RO 60	
	20' FA: 255/40 ZR 20 101 ZR Y XL RA: 295/35 ZR 20 105 ZR Y XL  Only for Turbo S CUV.		
	21-inch FA: 265/35 ZR 21 101 ZR Y XL RA: 305/30 ZR 21 104 ZR Y XL	FA: 9.5J x 21, RO 60	

Tires	Tire sizes	Wheel sizes	Snow chains
	For Turbo vehicles: not standard for USA	RA: 11.5J x 21, RO 66	
All Season- **)	19" FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL  Not for Turbo and Turbo S. Not for GTS and GTS Sport Turismo Not for China *)	FA: 8J x 19, RO 50 RA: 10J x 19, RO 47	
	20" FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL  Not for China	FA: 9J x 20, RO 54 RA: 11J x 20, RO 60	
	21-inch FA: 265/35 R 21 101H XL RA: 305/30 R 21 104H XL	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
Winter	19" FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL  Not for Turbo and Turbo S. Not for GTS and GTS Sport Turismo *)	FA: 8J x 19, RO 50 RA: 10J x 19, RO 47	RA only
	20" FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	FA: 9J x 20, RO 54 RA: 11J x 20, RO 60	

\*) Not with Porsche Ceramic Composite Brake (PCCB) or Porsche Surface Coated Brake (PSCB).

Wheels:

**Overview of Porsche wheels**

Identification on inside of wheel:

Wheel size, rim offset (RO) in mm, part number (without color code FFF) and Porsche logo

**19"-inch Taycan S Aero wheel, 19-inch Taycan Aero wheel**

FA: 8J x 19, RO 50

Part No. 9J1.601.025.B\_FFF

RA: 10J x 19, RO 47

Part No. 9J1.601.025.C\_FFF



*Taycan S Aero wheel, Taycan Aero wheel*

**20" inch Taycan Turbo Aero wheel**

FA: 9J x 20, RO 54

Part No. 9J1.601.025.J\_FFF

RA: 11J x 20, RO 60

Part No. 9J1.601.025.K\_FFF



*Taycan Turbo Aero wheel*

**20" inch Taycan Sport Aero wheel**

FA: 9J x 20, RO 54

Part No. 9J1.601.025.E\_FFF

RA: 11J x 20, RO 60

Part No. 9J1.601.025.F\_FFF



*Taycan Sport Aero wheel*

**20" inch Taycan TEQ Design wheel**

FA: 9J x 20, RO 54 (summer)  
Part No. 9J1.601.025.L\_FFF

RA: 11J x 20, RO 60  
Part No. 9J1.601.025.M\_FFF



*Taycan TEQ Design wheel*

**20" inch Turbo wheel**

FA: 9J x 20, RO 54  
Part No. 9J1.601.025.AJ\_FFF

RA: 11J x 20, RO 60  
Part No. 9J1.601.025.AK\_FFF



*Taycan Turbo wheel*

**20 inch off-road wheel**

FA: 9J x 20, RO 54  
Part No. 9J1.601.025.AS\_FFF

RA: 11J x 20, RO 60  
Part No. 9J1.601.025.AT\_FFF



*Taycan off-road wheel*

**20" inch Taycan Turbo S Aero Design**

FA: 9J x 20, RO 54  
Part No. 9J1.601.025.AG\_FFF

RA: 11J x 20, RO 60  
Part No. 9J1.601.025.AH\_FFF



*Taycan Turbo S Aero Design*

**21-inch Mission E Design wheel**

Only with PCCB or PSCB.

FA: 9.5J x 21, RO 60  
Part No. 9J1.601.025.AA\_FFF

RA: 11.5J x 21, RO 66  
Part No. 9J1.601.025.AB\_FFF



*Mission E Design wheel*

**21-inch Exclusive Design wheel**

FA: 9.5J x 21, RO 60

Part No. left: 9J1.601.025.Q\_FFF

Part No. right: 9J1.601.025.AC\_FFF

RA: 11.5J x 21, RO 66

Part No. left: 9J1.601.025.R\_FFF

Part No. right: 9J1.601.025.AD\_FFF

*Exclusive Design wheel***21-inch Exclusive Design wheels with carbon-fiber aeroblades**

FA: 9.5J x 21, RO 60

Part No. left: 9J1.601.025.S\_FFF

Part No. right: 9J1.601.025.AE\_FFF

RA: 11.5J x 21, RO 66

Part No. left: 9J1.601.025.T\_FFF

Part No. right: 9J1.601.025.AF\_FFF

*Exclusive Design wheels with carbon-fiber aeroblades*

**21-inch Cross Turismo Design wheel**

FA: 9.5J x 21, RO 60

Part No. :9J1.601.025.AL\_FFF

RA: 11.5J x 21, RO 66

Part No.: 9J1.601.025.AM\_FFF



*Cross Turismo Design wheel*

**21-inch RS Spyder Design wheel**

FA: 9.5J x 21, RO 60

Part No. 9J1.601.025.BC\_FFF

RA: 11.5J x 21, RO 66

Part No. 9J1.601.025.BD\_FFF



*RS Spyder Design Wheel*



**Information**

Improper handling can damage the wheel surface.

Carry out tire removal and mounting using a bead holding-down device only.

Use a leather pad on the rim flange to support the valve insertion tool.

Only use the Porsche centering clamping set for balancing.

Do not use brushes to clean the wheels because brushes can cause deep scratches that cannot be removed by polishing.

Never use solvents or other chemical substances on tires.

**Information**

Only install wheels with identical part number on each axle.

Exception: 21-inch Exclusive Design wheel and 21-inch Exclusive Design wheels with carbon-fiber aeroblades

Wheel  
mounting:

using wheel bolts:

**Tightening torque 160 Nm (118 ftlb.)**

Summer Tires:

Model	Tire size	Tire make and type / Label value (Link to EU database)
Taycan version / Sport Turismo Taycan / 4S / 4S Sport Turismo / Turbo / Turbo Sport Turismo / Turbo S / Turbo S Sport Turismo GTS / GTS Sport Turismo (Sedan + CUV)	FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL  Not for Turbo and Turbo S.  Not for GTS and GTS Sport Turismo	Continental Premium Contact 6 NFO FA: <a href="https://eprel.ec.europa.eu/qr/483380">https://eprel.ec.europa.eu/qr/483380</a> RA: <a href="https://eprel.ec.europa.eu/qr/482780">https://eprel.ec.europa.eu/qr/482780</a>
		Hankook ventus S1 evo NFO FA: <a href="https://eprel.ec.europa.eu/qr/463553">https://eprel.ec.europa.eu/qr/463553</a> RA: <a href="https://eprel.ec.europa.eu/qr/463560">https://eprel.ec.europa.eu/qr/463560</a>
		Michelin Pilot Sport 4 NFO FA: <a href="https://eprel.ec.europa.eu/qr/412377">https://eprel.ec.europa.eu/qr/412377</a> RA: <a href="https://eprel.ec.europa.eu/qr/410806">https://eprel.ec.europa.eu/qr/410806</a>
	FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL  Not for Turbo S vehicles	Michelin Pilot Sport 4 NFO FA: <a href="https://eprel.ec.europa.eu/qr/409571">https://eprel.ec.europa.eu/qr/409571</a> RA: <a href="https://eprel.ec.europa.eu/qr/409604">https://eprel.ec.europa.eu/qr/409604</a>
		Pirelli CintuRato P7 Blue NFO FA: <a href="https://eprel.ec.europa.eu/qr/595725">https://eprel.ec.europa.eu/qr/595725</a> RA: <a href="https://eprel.ec.europa.eu/qr/595726">https://eprel.ec.europa.eu/qr/595726</a>
	FA: 255/40 ZR 20 101Y XL RA: 295/35 ZR 20 105Y XL  Only for Turbo S CUV.	Goodyear Eagle F1 Supersport NFO FA: <a href="https://eprel.ec.europa.eu/qr/531033">https://eprel.ec.europa.eu/qr/531033</a> RA: <a href="https://eprel.ec.europa.eu/qr/531034">https://eprel.ec.europa.eu/qr/531034</a>
		Pirelli PZero NFO FA: <a href="https://eprel.ec.europa.eu/qr/595740">https://eprel.ec.europa.eu/qr/595740</a> RA: <a href="https://eprel.ec.europa.eu/qr/595741">https://eprel.ec.europa.eu/qr/595741</a>
	FA: 265/35 ZR 21 101Y XL RA: 305/30 ZR 21 104Y XL  For Turbo vehicles: not	Goodyear Eagle F1 Asymmetric3 NFO FA: <a href="https://eprel.ec.europa.eu/qr/529729">https://eprel.ec.europa.eu/qr/529729</a> RA: <a href="https://eprel.ec.europa.eu/qr/529726">https://eprel.ec.europa.eu/qr/529726</a>



Model	Tire size	Tire make and type / Label value (Link to EU database)
	standard for USA	Pirelli P-ZERO NFO FA: <a href="https://eprel.ec.europa.eu/qr/595738">https://eprel.ec.europa.eu/qr/595738</a> RA: <a href="https://eprel.ec.europa.eu/qr/595739">https://eprel.ec.europa.eu/qr/595739</a>

All-Season Tires:

Model	Tire size	Tire make and type / Label value (Link to EU database)
Taycan version / Sport Turismo Taycan / 4S / 4S Sport Turismo / Turbo / Turbo Sport Turismo / Turbo S / Turbo S Sport Turismo GTS / GTS Sport Turismo (Sedan + CUV)	FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL  Not for Turbo and Turbo S.	Continental ProContact RX NFO FA: <a href="https://eprel.ec.europa.eu/qr/483273">https://eprel.ec.europa.eu/qr/483273</a> RA: <a href="https://eprel.ec.europa.eu/qr/482743">https://eprel.ec.europa.eu/qr/482743</a>
	Not for GTS and GTS Sport Turismo	Goodyear Eagle Touring NFO FA: <a href="https://eprel.ec.europa.eu/qr/529738">https://eprel.ec.europa.eu/qr/529738</a> RA: <a href="https://eprel.ec.europa.eu/qr/529739">https://eprel.ec.europa.eu/qr/529739</a>
	FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL	Continental ProContact RX NFO FA: <a href="https://eprel.ec.europa.eu/qr/483338">https://eprel.ec.europa.eu/qr/483338</a> RA: <a href="https://eprel.ec.europa.eu/qr/481297">https://eprel.ec.europa.eu/qr/481297</a>
		Pirelli Cinturato P7 A/S NFO Turbo Sedan: not for USA. FA: <a href="https://eprel.ec.europa.eu/qr/595727">https://eprel.ec.europa.eu/qr/595727</a> RA: <a href="https://eprel.ec.europa.eu/qr/595728">https://eprel.ec.europa.eu/qr/595728</a>
	FA: 265/35 R 21 101 H XL RA: 305/30 R 21 104 H XL	Continental ProContact RX NFO FA: <a href="https://eprel.ec.europa.eu/qr/482746">https://eprel.ec.europa.eu/qr/482746</a> RA: <a href="https://eprel.ec.europa.eu/qr/481299">https://eprel.ec.europa.eu/qr/481299</a>
		Goodyear Eagle F1 Touring NFO Not for China FA: <a href="https://eprel.ec.europa.eu/qr/531035">https://eprel.ec.europa.eu/qr/531035</a> RA: <a href="https://eprel.ec.europa.eu/qr/531036">https://eprel.ec.europa.eu/qr/531036</a>

Winter Tires:

Model	Tire size	Tire make and type / Label value (Link to EU database)
Taycan version / Sport Turismo Taycan / 4S / 4S Sport Turismo / Turbo / Turbo Sport Turismo /	FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL  Not for Turbo and Turbo S.	Continental TS 860 S NFO FA: <a href="https://eprel.ec.europa.eu/qr/479702">https://eprel.ec.europa.eu/qr/479702</a> RA: <a href="https://eprel.ec.europa.eu/qr/620844">https://eprel.ec.europa.eu/qr/620844</a>
	Not for GTS and GTS Sport Turismo	Pirelli P-Zero Winter NFO FA: <a href="https://eprel.ec.europa.eu/qr/595723">https://eprel.ec.europa.eu/qr/595723</a> RA: <a href="https://eprel.ec.europa.eu/qr/595724">https://eprel.ec.europa.eu/qr/595724</a>
	FA: 245/45 R 20 103V XL	Goodyear UltraGrip Performance Gen1 NFO

Model	Tire size	Tire make and type / Label value (Link to EU database)
Turbo S / Turbo S Sport Turismo GTS / GTS Sport Turismo (Sedan + CUV)	RA: 285/40 R 20 108V XL	FA: <a href="https://eprel.ec.europa.eu/qr/529740">https://eprel.ec.europa.eu/qr/529740</a> RA: <a href="https://eprel.ec.europa.eu/qr/529741">https://eprel.ec.europa.eu/qr/529741</a>  Pirelli P-Zero Winter NFO FA: <a href="https://eprel.ec.europa.eu/qr/595729">https://eprel.ec.europa.eu/qr/595729</a> RA: <a href="https://eprel.ec.europa.eu/qr/595730">https://eprel.ec.europa.eu/qr/595730</a>

Arrow with inscription "Rotation"

= directional mounting

"Inside/Outside" inscription

= mounting on specified side only

Arrow with both inscriptions "Rotation" and  
"Inside/Outside"

= directional mounting on specified side only.



#### Information

"N..." = Specification code of the tire, e.g. "NFO", "NF1", "NF2" ... The complete "N ..." code of the relevant tire makes must be shown on the tire sidewall near the type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.



#### Information

If a tire is damaged and it is not possible to determine with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally and/or mechanically overloaded due to a loss of pressure or other prior damage, replace the tire in question for safety reasons.

Repairs to "V", "W", "Y" and "ZR" tires are not permissible, as well as the use of inner tubes in tubeless tires. Please inform your customers accordingly. It is advisable to mount winter tires at temperatures below **45° F/7°C**, because the driving characteristics of summer tires are reduced at low temperatures. Extremely low temperatures can cause permanent damage to summer tires.



#### WARNING

##### Incorrect tire pressure

- Uncontrollable vehicle handling

⇒ Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.

⇒ Check age of tires. Replace tires that are more than 6 years old.

⇒ Perform visual inspections.

⇒ Use only tires recommended by Porsche.



**WARNING**

Driving with different tires (mixed tires)

- Uncontrollable vehicle handling

⇒ Only use tires of the same make and type, with the same speed index and the same specification code (NFO, NF1, NF2, etc.) on a vehicle.



**Information**

The tire pressure applies only to the tire makes and types approved by Porsche, and is specified for cold tires (approx. **68° F/20°C**). The tire pressures must never be lower than the specified values.

**Standard spare wheel tire pressure**

**Standard tire pressure for summer tires + UHP, MY 2022 + 2023**

Wheel size	Taycan (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.4 bar 240 kPa 35 psi	–	2.4 bar 240 kPa 35 psi	–	2.4 bar 240 kPa 35 psi	–	2.4 bar 240 kPa 35 psi	–
	–	2.3 bar (33 psi) 230 kPa 33 psi	–	2.5 bar 250 kPa 36 psi	–	2.3 bar (33 psi) 230 kPa 33 psi	–	2.5 bar 250 kPa 36 psi
20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	–	2.4 bar 240 kPa 35 psi	–	2.4 bar 240 kPa 35 psi	–	2.4 bar 240 kPa 35 psi	–
	–	2.3 bar (33 psi) 230 kPa 33 psi	–	2.6 bar 260 kPa 37 psi	–	2.3 bar (33 psi) 230 kPa 33 psi	–	2.6 bar 260 kPa 37 psi

21-inch wheels	2.3 bar (33 psi) 230 kPa 33 psi	–	2.5 bar 250 kPa 36 psi	–	2.3 bar (33 psi) 230 kPa 33 psi	–	2.5 bar 250 kPa 36 psi	–
	–	2.4 bar 240 kPa 35 psi	–	2.9 bar 290 kPa 42 psi	–	2.5 bar 250 kPa 36 psi	–	2.9 bar 290 kPa 42 psi

Wheel size	Taycan 4S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.7 bar 270 kPa 39 psi	–	2.7 bar 270 kPa 39 psi	–	2.7 bar 270 kPa 39 psi	–	2.7 bar 270 kPa 39 psi	–
	–	2.4 bar 240 kPa 35 psi	–	2.6 bar 260 kPa 37 psi	–	2.4 bar 240 kPa 35 psi	–	2.6 bar 260 kPa 37 psi
20-inch wheels (245/45R20 & 285/40R20)	2.7 bar 270 kPa 39 psi	–	2.7 bar 270 kPa 39 psi	–	2.7 bar 270 kPa 39 psi	–	2.7 bar 270 kPa 39 psi	–
	–	2.4 bar 240 kPa 35 psi	–	2.7 bar 270 kPa 39 psi	–	2.4 bar 240 kPa 35 psi	–	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	–	2.8 bar (41 psi) 280 kPa 41 psi	–	2.7 bar 270 kPa 39 psi	–	2.8 bar (41 psi) 280 kPa 41 psi	–
	–	2.5 bar 250 kPa 36 psi	–	3.0 bar (44 psi) 300 kPa 44 psi	–	2.7 bar 270 kPa 39 psi	–	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan Turbo (Sedan)/Turbo S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA

20-inch wheels (245/45R20 & 285/40R20)	2.7 bar 270 kPa 39 psi	-	2.7 bar 270 kPa 39 psi	-	2.7 bar 270 kPa 39 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.6 bar 260 kPa 37 psi	-	3.1 bar 310 kPa 45 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi
20-inch wheels (245/45R20 & 285/40R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi
21-inch wheels	2.4 bar 240 kPa 35 psi	-	2.5 bar 250 kPa 36 psi	-	2.4 bar 240 kPa 35 psi	-	2.5 bar 250 kPa 36 psi	-
	-	2.5 bar 250 kPa 36 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.5 bar 250 kPa 36 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan (CUV), Taycan 4S (CUV), Taycan 4S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi
20-inch wheels (245/4 5R20 & 285/40 R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/4 5R20 & 285/40 R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi

21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Turbo (CUV), Taycan Turbo S (CUV)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/4 5R20 & 285/40 R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
20-inch wheels (255/4 0R20 & 295/35 R20)  <b>only Taycan Turbo S (CUV)</b>	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Turbo Sport Turismo, Taycan Turbo S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.5 bar 250 kPa 36 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.5 bar 250 kPa 36 psi	-	2.8 bar (41 psi) 280 kPa 41 psi
21-inch wheels	2.7 bar 270 kPa 39 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.7 bar 270 kPa 39 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.2 bar 320 kPa 46 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.2 bar 320 kPa 46 psi



Standard tire pressure for summer tires + UHP, MY 2020 + 2021

Wheel size	Taycan (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.2 bar (32 psi) 220 kPa 32 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.2 bar (32 psi) 220 kPa 32 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-
	-	2.1 bar (30 psi) 210 kPa 30 psi	-	2.5 bar 250 kPa 36 psi	-	2.2 bar (32 psi) 220 kPa 32 psi	-	2.5 bar 250 kPa 36 psi
20-inch wheels (245/45R20 & 285/40R20)	2.2 bar (32 psi) 220 kPa 32 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.2 bar (32 psi) 220 kPa 32 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-
	-	2.1 bar (30 psi) 210 kPa 30 psi	-	2.6 bar 260 kPa 37 psi	-	2.2 bar (32 psi) 220 kPa 32 psi	-	2.6 bar 260 kPa 37 psi
21-inch wheels	2.3 bar (33 psi) 230 kPa 33 psi	-	2.5 bar 250 kPa 36 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.5 bar 250 kPa 36 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.9 bar 290 kPa 42 psi	-	2.5 bar 250 kPa 36 psi	-	2.9 bar 290 kPa 42 psi

Wheel size	Taycan 4S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.2 bar (32 psi) 220 kPa 32 psi	-	2.6 bar 260 kPa 37 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi

20-inch wheels (245/45R20 & 285/40R20)	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.2 bar (32 psi) 220 kPa 32 psi	-	2.7 bar 270 kPa 39 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.7 bar 270 kPa 39 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.5 bar 250 kPa 36 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan Turbo (Sedan)/Turbo S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.6 bar 260 kPa 37 psi	-	3.1 bar 310 kPa 45 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi
20-inch wheels (245/45R20 & 285/40R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi
21-inch wheels	2.4 bar 240 kPa 35 psi	-	2.5 bar 250 kPa 36 psi	-	2.4 bar 240 kPa 35 psi	-	2.5 bar 250 kPa 36 psi	-
	-	2.5 bar 250 kPa 36 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.5 bar 250 kPa 36 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan (CUV), Taycan 4S (CUV), Taycan 4S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi

20-inch wheels (245/4 5R20 & 285/40 R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/4 5R20 & 285/40 R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Turbo (CUV), Taycan Turbo S (CUV)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA

20-inch wheels (245/45R20 & 285/40R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
20-inch wheels (255/45R20 & 295/35R20) <b>only Taycan Turbo S (CUV)</b>	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi

21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Turbo Sport Turismo, Taycan Turbo S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.5 bar 250 kPa 36 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.5 bar 250 kPa 36 psi	-	2.8 bar (41 psi) 280 kPa 41 psi
21-inch wheels	2.7 bar 270 kPa 39 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.7 bar 270 kPa 39 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.2 bar 320 kPa 46 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.2 bar 320 kPa 46 psi

## Standard tire pressure for all-season vehicles, MY 2020 to 2023

Wheel size	Taycan (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA

19-inch wheels	2.3 bar (33 psi) 230 kPa 33 psi	-	2.5 bar 250 kPa 36 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.5 bar 250 kPa 36 psi	-
	-	2.2 bar (32 psi) 220 kPa 31 psi	-	2.7 bar 270 kPa 39 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi
20-inch wheels (245/4 5R20 & 285/40 R20)	2.3 bar (33 psi) 230 kPa 33 psi	-	2.5 bar 250 kPa 36 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.5 bar 250 kPa 36 psi	-
	-	2.2 bar (32 psi) 220 kPa 31 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.5 bar 250 kPa 36 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.5 bar 250 kPa 36 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan 4S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.2 bar (32 psi) 220 kPa 31 psi	-	2.6 bar 260 kPa 37 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.6 bar 260 kPa 37 psi

20-inch wheels (245/45R20 & 285/40R20)	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.2 bar (32 psi) 220 kPa 31 psi	-	2.7 bar 270 kPa 39 psi	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.7 bar 270 kPa 39 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.5 bar 250 kPa 36 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan Turbo/Turbo S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.5 bar 250 kPa 36 psi	-	2.6 bar 260 kPa 37 psi	-	2.5 bar 250 kPa 36 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.7 bar 270 kPa 39 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.6 bar 260 kPa 37 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi



Wheel size	Taycan Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
20-inch wheels (245/4 5R20 & 285/40 R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan (CUV), Taycan 4S (CUV), Taycan 4S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi

20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Turbo (CUV), Taycan Turbo S (CUV)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA

20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.6 bar 260 kPa 37 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan Turbo Sport Turismo, Taycan Turbo S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA

20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-	2.4 bar 240 kPa 35 psi	-	2.6 bar 260 kPa 37 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi
21-inch wheels	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-	2.6 bar 260 kPa 37 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.1 bar 310 kPa 45 psi

## Standard tire pressure for winter, MY 2020 to 2023

Wheel size	Taycan (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.3 bar (33 psi) 230 kPa 33 psi	-	2.9 bar 290 kPa 42 psi	-	2.5 bar 250 kPa 36 psi	-	2.9 bar 290 kPa 42 psi
20-inch wheels (245/45R20 & 285/40R20)	2.4 bar 240 kPa 35 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.9 bar 290 kPa 42 psi	-	2.5 bar 250 kPa 36 psi	-	2.9 bar 290 kPa 42 psi

Wheel size	Taycan 4S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA

19-inch wheels	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-
	-	2.4 bar 240 kPa 35 psi	-	2.9 bar 290 kPa 42 psi	-	2.6 bar 260 kPa 37 psi	-	2.9 bar 290 kPa 42 psi
20-inch wheels (245/4 5R20 & 285/40 R20)	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-
	-	2.4 bar 240 kPa 35 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.6 bar 260 kPa 37 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan Turbo/Turbo S (Sedan)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/4 5R20 & 285/40 R20)	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.8 bar (41 psi) 280 kPa 41 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.5 bar 250 kPa 36 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.5 bar 250 kPa 36 psi	-	2.9 bar 290 kPa 42 psi	-	2.5 bar 250 kPa 36 psi	-	2.9 bar 290 kPa 42 psi

20-inch wheels (245/45R20 & 285/40R20)	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-	2.5 bar 250 kPa 36 psi	-	2.7 bar 270 kPa 39 psi	-
	-	2.5 bar 250 kPa 36 psi	-	2.9 bar 290 kPa 42 psi	-	2.5 bar 250 kPa 36 psi	-	2.9 bar 290 kPa 42 psi

Wheel size	Taycan (CUV), Taycan 4S (CUV), Taycan 4S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
19-inch wheels	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.6 bar 260 kPa 37 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.6 bar 260 kPa 37 psi	-	3.0 bar (44 psi) 300 kPa 44 psi
20-inch wheels (245/45R20 & 285/40R20)	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.6 bar 260 kPa 37 psi	-	3.1 bar 310 kPa 45 psi	-	2.6 bar 260 kPa 37 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.6 bar 260 kPa 37 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.6 bar 260 kPa 37 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan Turbo (CUV), Taycan Turbo S (CUV)							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi

Wheel size	Taycan GTS Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi	-	2.7 bar 270 kPa 39 psi	-	3.0 bar (44 psi) 300 kPa 44 psi

Wheel size	Taycan Turbo Sport Turismo, Taycan Turbo S Sport Turismo							
	4 seater				5 seater			
	Part load		Full load		Part load		Full load	
	FA	RA	FA	RA	FA	RA	FA	RA
20-inch wheels (245/45R20 & 285/40R20)	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-	2.7 bar 270 kPa 39 psi	-	2.9 bar 290 kPa 42 psi	-
	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi	-	2.7 bar 270 kPa 39 psi	-	3.1 bar 310 kPa 45 psi



**WARNING**

Incorrectly installed snow chains

- Uncontrollable vehicle handling

- ⇒ Do not exceed the maximum speed of Speed 30 mph/50 km/h.
- ⇒ Observe installation instructions from the chain manufacturer.

Porsche offers the following snow chains as accessories:

Tire size	Porsche Part No.	Type of snow chain
275/45 R 19 M+S	9J1.073.690	Quick fit
285/40 R 20 M+S	9J1.073.690	Quick fit

- Wheel Storage:
- Tires must be stored in a cool, dry and dark room with adequate ventilation.
  - Tires must never come into contact with fuel, oil, grease or chemicals.
  - Do not store summer tires in storage areas with ambient temperatures of less than 5° F (-15° C).
  - Complete wheel & tire assemblies can be stacked for storage; we recommend that you increase the tire pressure by approximately 6 psi (0.4 bar).
  - Optimum conditions for storage of the complete wheels are provided by the Original Porsche storage trolley, Part No. 000.044.000.38.
  - If the tires are not mounted on wheels, it is best to store them in a vertical position.
  - We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots.
  - Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.

- General Information:
- Always use new valves when changing tires.
  - Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on.
  - Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily.
  - In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.
  - In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

**Matching (uncontrolled and controlled) is explained below: Uncontrolled matching:**

- Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

**Controlled matching:**

- With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching.
- Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm - ideally approx. 0.5 mm - are desirable.



- The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

### **New Tires (Replacements):**

- If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, type and with the same specification code must always be used on each of the two axles.
- If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling.
- This is especially the case if new tires are mounted on the rear axle.
- This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire on the same axle by more than 30 %.

Refer to WM 449503 for specific details of the vehicle you are working on.

- >The 2mm specification will be given here.
- > If there is none listed then the default is 30%.

### **Repairs to Tires:**

- If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.
- Repairs to "V", "W", "Y", and "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires.

### **Tire Aging:**

- Tires age due to chemical and physical processes, which can impair their function.
- Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use.
- Hairline aging cracks can occur on older tires.
- On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.
- Therefore, attention should be paid not only to the tread depth but also to the age of the tire.
- Tires should not be older than 6 years.
- The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201 = 22nd week of 2001.

**Important Notice:** Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2022 Porsche Cars North America, Inc.