

**NUMBER:** 18-078-22

**GROUP:** 18 - Vehicle Performance

DATE: April 8, 2022

This bulletin is supplied as technical information only and is not an authorization for repair. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without written permission of FCA US LLC.

### SUBJECT:

Flash: Powertrain Control Module (PCM) Updates

## **OVERVIEW**:

This bulletin involves reprogramming the PCM with the latest available software.

#### MODELS:

2021 (KL) Jeep Cherokee

- NOTE: This bulletin applies to vehicles within the following markets/countries: North America, APAC, EMEA and LATAM.
- NOTE: This bulletin applies to vehicles equipped with a 2.4L I4 Zero-Evap Multiair Engine W/ESS (Sales Code EDE) or a 2.4L I4 Multiair Engine W/ESS (Sales Code EDD).

#### SYMPTOM/CONDITION:

Customers may experience a Malfunction Indicator Lamp (MIL) illumination. Upon further investigation the technician may find the following Diagnostic Trouble Code (DTC):

• U0418 - Implausible Data Received From Brake System Control Module.

### NOTE: DTC U0418 can be set erroneously due to a low battery (below 10 volts).

### DIAGNOSIS:

If the customer describes the symptom/condition listed above or if the technician finds the DTC, perform the Repair Procedure.

## **REPAIR PROCEDURE:**

NOTE: Install a battery charger to ensure battery voltage does not drop below 13.2 volts. Do not allow the charging voltage to climb above 13.5 volts during the flash process.

# NOTE: If this flash process is interrupted/aborted, the flash should be restarted.

- 1. Reprogram the PCM with the latest software. Detailed instructions for flashing control modules using the wiTECH Diagnostic Application are available by selecting the application's "HELP" tab.
- 2. Clear any DTCs that may have been set in any module due to reprogramming. The wiTECH application will automatically present all DTCs after the flash and allow them to be cleared.
- 3. Place the ignition in the off position for a minimum of 30 seconds to complete the flash.

## POLICY:

Reimbursable within the provisions of the warranty.

## TIME ALLOWANCE:

Labor Operation No:	Description	Skill Cat- egory	Amount
18-19-06-9Q	Module, Powertrain Control (PCM) - Reprogram (0 - Introduction)	1 - Engine Repair and Performance	0.3 Hrs.

NOTE: The expected completion time for the flash download portion of this procedure is approximately 7 minutes. Actual flash download times may be affected by vehicle connection and network capabilities.

# FAILURE CODE:

# The dealer must use failure code CC with this Technical Service Bulletin.

- If the customer's concern matches the SYMPTOM/CONDITION identified in the Technical Service Bulletin, failure code CC is to be used.
- When utilizing this failure code, the 3C's (customer's concern, cause and correction) must be provided for processing Technical Service Bulletin flash/reprogramming conditions.

CC	Customer Concern
----	------------------