

VOLUNTARY SERVICE CAMPAIGN

AT23-003

NTB23-056

June 21, 2023

VOLUNTARY SERVICE CAMPAIGN 2022-2023 FRONTIER AND 2023 TITAN/TITAN XD; AUTOMATIC PARK FUNCTION

CAMPAIGN ID #: APPLIED VEHICLES: PC982 2022-2023 Frontier (D41) 2023 Titan/Titan XD (A61)

Check Service COMM or Dealer Business Systems (DBS) National Service History to confirm campaign eligibility.

INTRODUCTION

Nissan is conducting this voluntary service campaign, on certain specific model year 2022-2023 Frontier and 2023 Titan/Titan XD vehicles, to configure the Automatic Park function. This service will be performed at no charge to the customer for parts or labor.

IDENTIFICATION NUMBER

Nissan has assigned identification number PC982 to this campaign. This number must appear on all communication and documentation of any nature dealing with this campaign.

DEALER RESPONSIBILITY

Dealers are to repair vehicles falling within range of this campaign that enter the service department. This includes vehicles purchased from private parties, vehicles presented by transient (tourists) owners, and vehicles in a dealer's inventory.

Bulletins are intended for use by qualified technicians, not 'do-it-yourselfers'. Qualified technicians are properly trained individuals who have the equipment, tools, safety instruction, and know-how to do a job properly and safely. **NOTE:** If you believe that a described condition may apply to a particular vehicle, DO NOT assume that it does. See your Nissan dealer to determine if this applies to your vehicle.

SERVICE PROCEDURE

- 1. Start the engine.
- 2. With the transmission in the PARK position, inspect the **P** in the gear indicator on the combination meter.
 - If the **P** indicator is flashing, continue to step 3 to configure the Automatic Park function.
 - If the **P** indicator is not flashing, no further action is required. Skip to the **CLAIMS INFORMATION** on the last page.



Figure 1

3. Turn the ignition OFF.

IMPORTANT: Before starting, make sure:

- All CONSULT-III software updates (if any) have been installed.
- 4. Confirm that the CONSULT PC is connected to Wi-Fi.
- 5. Turn the ignition ON, engine OFF.
- 6. Connect the VI to the vehicle.
- 7. Start C-III plus.
- 8. If prompted, select **USA/CANADA Dealers** from the drop down menu, and then select **OK.**

9. Login using your NNAnet credentials.

IMPORTANT: If not prompted to enter your username and password, the CONSULT PC may not be connected to Wi-Fi. Close C-III plus, confirm the CONSULT PC is connected to Wi-Fi, and then reopen C-III plus.

- 10. Wait for the VI to be recognized.
 - The serial number will display when the VI is recognized (Figure 2).

11. Select Diagnosis (All Systems)

	Back Home	Print Screen Screen Capture Mode	Recorded Data
	Connection Stat	us	Diagnosis Menu
	Serial No	. Status	Diagnosis (One System)
VI is recognized	230072	7 Normal Mode/Wireless connection	Diagnosis (All Systems)
	MI -		
		No connection	Re/programming, Configuration
	Select V	I/MI	Immobilizer
	Application Settin	g	Maintenance
	VDR		

Figure 2

12. Select TRANSMISSION under the All DTC tab.

Diagnosis (All Systems) Diagnosis (All Systems) Diagnosis (All Systems)								
All DTC	O CAN Diag	0	CAN DIAG SUPPORT MNTR	DTC ONetwo	ork DTC)		
Result		Detailed Infor	Detailed Information					
TRANSMISSION	CRNT	TRANSMIS	SION	CRNT	ОТС]			
ENGINE	NO DTC	FIGAG	CANCEL	CRN1 -	Expla			
ABS	NO DTC							
METER/M&A	NO DTC							
ВСМ	NO DTC					Print		
AIR BAG	NO DTC					Print		
ICC/ADAS	NO DTC					Save		
1/4				1/1]	ERASE		

Figure 3

13. Select Work support.

e Back	Home	Print Scree	n Screen Capture	Measurement Mode	Recorded Data	P Help	ERT	12.4V	Yil vi	× MI		
Dia Sys	agnosis (Al stems)		Select Vehicle	Confi	rm Vehicle	Diagn Sys	osis (All tems)		ENGIN	E		
Self D Result	iagnostic t	Data	Monitor	्र ्रि Work s			st	€	CU dentifica	ation	$\langle $	·
P18	8A5	AUTO PA CANCEL	RK FUNC			CRNT		- [DT Exp	C ola		
1												
											Print	4
										•	Save	
								1/1			ERASE	
					Figure	94						

14. Select CANCEL AUTOMATIC PARK FUNCTION, and then select Start.



- 15. Select **Off**, and then select **End**.
 - Verify **Current status** shows "Off".

HINT: DTC P18A5-00 will automatically clear after changing the **CANCEL AUTOMATIC PARK FUNCTION** to **Off**.



- 16. Close C-III plus and disconnect the VI.
- 17. Start the engine.
- 18. With the transmission in the PARK position, inspect and verify that the **P** in the gear indicator on the combination meter is no longer flashing.



Figure 7

CLAIMS INFORMATION

CAMPAIGN ("CM") ID	DESCRIPTION	OP CODE	FRT
DC092	Inspect Gear Position Indicator (OK Condition)	PC9820	0.2
PC982	Inspect Gear Position Indicator and Configure the Automatic Park Function	PC9821	0.3

Submit a "CM" line claim using the following claims coding:

AMENDMENT HISTORY

PUBLISHED DATE	REFERENCE	DESCRIPTION
June 21, 2023	NTB23-056	Original bulletin published