



Service Bulletin

Bulletin No.: 01-06-01-011O

Date: October, 2023

INFORMATION

Subject: Information on Engine Oil Consumption Guidelines

Models: 2024 and Prior GM Passenger Cars and Gasoline-Powered Light Duty Trucks Under 8500 LB GVW

Attention: This bulletin also applies to any of the above models that may be Exported to or sold in: North America, Europe, Uzbekistan, Russia, Middle East, Iraq, Israel, Palestine, Argentina, Brazil, Bolivia, Chile, Colombia, Ecuador, Paraguay, Peru, Uruguay, Venezuela, Japan, Cadillac Korea (South Korea), GM Korea Company, China, Taiwan, Thailand, Singapore, Philippines, Australia/New Zealand, Egypt, Other Africa, South Africa

This bulletin has been revised to add Engine Hours and Equivalent Odometer Value to the Table. Please discard Corporate Bulletin Number 01-06-01-011N.

All engines require oil to lubricate and protect the load bearing and internal moving parts from wear including cylinder walls, pistons and piston rings. When a piston moves down its cylinder, a thin film of oil is left on the cylinder wall. During the power stroke, part of this oil layer is consumed in the combustion process. As a result, varying rates of oil consumption are accepted as normal in all engines.

Important: Service agents must comply with all International, Federal, State, Provincial, and/or Local laws applicable to the activities it performs under this bulletin, including but not limited to handling, deploying, preparing, classifying, packaging, marking, labeling, and shipping dangerous goods. In the event of a conflict between the procedures set forth in this bulletin and the laws that apply to your dealership, you must follow those applicable laws.

Oil Consumption

The accepted rate of oil consumption for engines used in the vehicles referenced is 0.946 liter (1 qt) in 3200 km (2000 mi).

Important: This rate only applies to personal use vehicles, under warranty, that are driven in a non-aggressive manner and maintained in accordance with the appropriate maintenance schedule, with less than 58,000 km (36,000 mi) or driven at legal speeds in an unloaded (for trucks) condition.

Important: This rate **does not apply** to vehicles that are driven in an aggressive manner, at high RPM, high speeds, or in a loaded condition (for trucks). Oil consumption for vehicles driven under these conditions will be more.

Many factors can affect a customer's concern with oil consumption. Driving habits and vehicle maintenance vary from owner to owner. Thoroughly evaluate each case before deciding whether the vehicle in question has abnormal engine oil consumption.

Gasket and External Leaks

Inspect the oil pan and engine covers for leakage due to over-tightened, damaged, or out of place gaskets. Inspect oil lines and fittings for signs of leakage.

How To Identify If A Vehicle Idles More Than An Average Vehicle

Note: Use this formula as a diagnostic aid and in the administration of a maintenance schedule. It should NOT be used to determine warranty coverage.

Some vehicles may spend a lot of time idling. Use the formula to aid in determining the equivalent mileage (kilometers):

- Check and record the total engine hours on the Driver Information Center (DIC). You may need to go into the settings menu on the DIC to display the engine hours.

- Multiply this time by 33 miles or 53 km. This represents an average speed of 54 km/h (33 mph).
- The result should be close to or lower than the mileage on the odometer.
 - **Example 1:** If a vehicle has 1812.3 engine hours and 60,837 miles (97,908 km) on the odometer, the engine run time would equate to about 59,806 miles (96,052 km) ($1812.3 \times 33 = 59,806$) ($1812.3 \times 53 = 96,052$).
Because the calculated mileage is less than the actual mileage, this vehicle does not spend an excessive amount of time idling.
 - **Example 2:** If the vehicle has 626.9 engine hours and 7,269 miles (11,698 km) on the odometer, the engine run time would equate to about 20,688 miles (33,226 km) ($626.9 \times 33 = 20,688$) ($626.9 \times 53 = 33,226$).
Because the calculated mileage is more than the actual mileage, this vehicle would be considered a vehicle that idles a lot and this information may be useful in diagnosing any issues.

Improper Reading of the Oil Level Indicator (Dipstick)

Verify that the dipstick tube is fully seated in the block. When checking the oil level, make sure the dipstick is wiped clean before taking an oil level reading and fully depress the dipstick until the shoulder bottoms out on the dipstick tube. The dipstick should be the proper part number for the engine/vehicle that is being checked.

Notice: Operating your vehicle with an oil level that is below the minimum level indicated on the engine oil dipstick can result in severe engine damage. Repairs resulting from operating an engine with insufficient oil are not covered under the terms of the New Vehicle Warranty.

Important: Refer to Owner Manual in SI for checking and adding engine oil.

Not Waiting Long Enough After Running Engine to Check Oil Level

Some engines require more time than others for the oil to drain back into the crankcase. To assure a sufficient amount of oil has drained back to the crankcase, and an accurate reading can be obtained, the vehicle should be allowed to sit for at least 15 minutes, after the engine has been shut off, before taking an oil level reading. In order to ensure accurate results, the temperature of the oil should be close to the same temperature as the last time the oil level was checked.

Important: This does not apply to 2006-2009 Corvette Z06 equipped with the 7.0L LS7 and the 2009 Corvette ZR-1 with the 6.2L LS9 engines (dry sump) or 2020-2024 Corvette with the LT2 engine. Follow the instructions in the Owner Manual for checking the oil in this application.

Improper Oil Fill After an Oil Change

Following an oil change, verify that the proper amount and type of oil was put in the engine and that the oil level on the dipstick is not above the full mark or below the add marks. Refer to the Owner Manual or Service Manual for information on recommended oil quantity, viscosity, and quality.

Aggressive Driving, High Speed or High RPM Driving

Aggressive driving and/or continuous driving at high speeds/high RPMs will increase oil consumption. Because this may not always be an everyday occurrence, it is hard to determine exactly how much the oil economy will be affected.

A higher rate of oil consumption is normal for vehicles equipped with manual transmissions that are driven aggressively. By "aggressive," we mean operation at high RPM (3,000 RPM to redline), with frequent use of engine braking (using the engine to slow the vehicle). Vehicles that are driven aggressively may consume engine oil at a rate of up to 0.946 L (1 quart) every 805 km (500 mi). This is normal for a vehicle that is driven aggressively. No repair is necessary. This characteristic does, however, require the owner to check the engine oil level at sufficiently frequent intervals, especially when driving aggressively, to assure the oil level remains within the recommended operating range. As the Owner Manual recommends, you should check the oil level every time you get fuel.

Towing or Heavy Usage

Towing a trailer will increase oil consumption and may cause oil consumption to fall below the normal accepted rate referenced in this bulletin for an unloaded vehicle in a personal use application. Large frontal area trailers will further increase the work required from the engine, especially at highway speeds, and thus increases the rate of oil consumption.

Crankcase Ventilation System

Verify that the positive crankcase ventilation (PCV) system is operating properly. Blockages, restrictions, or damage to the PCV system can result in increased oil use.

Oil Dilution (Fuel and Water)

On vehicles that are usually driven short distances, less than 8 km (5 mi), especially in colder weather, unburned fuel and condensation generated from cold engine operation may not get hot enough to evaporate out of the oil. When this occurs, the dipstick may indicate that the oil level is over-full. Subsequent driving on a trip of sufficient length to enable normal engine operating temperature for 30 minutes or more, in order to vaporize excess moisture and fuel, may give the customer the impression of excessive oil consumption.

Engine Temperature

If an engine is run at overheated temperatures (see Owner's Manual or Service Manual) for more than brief periods, oil will oxidize at a faster than normal rate. In addition, gaskets may distort, piston rings may stick, and excessive wear may result. Verify that all cooling system components are in proper working order.

Engine Wear

Piston scuffing, excessive piston-to-wall clearance, tapered or out of round cylinders, worn, damaged or improperly installed valve guides, seals and piston rings will all cause an increase in oil consumption.

Measurement of Oil Consumption

Engines require a period of time to BREAK IN so that moving parts are properly seated. Therefore, oil economy should not be tested until the vehicle has accumulated at least 6400 km (4000 mi). An exception would be allowed only if an engine is reported to be using more than 0.946 liter (1 qt) in 1600 km (1000 mi).

1. Verify that the engine has no external leaks. Repair as necessary.
2. Verify that the engine is at normal operating temperature (see Owner Manual or Service Manual).
3. Park the vehicle on a level surface.
4. Wait at least 15 minutes, after the engine is shut off, before checking the oil level to make sure that the oil has had time to drain back into the crankcase.
5. Verify that the oil level is at, but not above, the full mark on the dipstick, and that the proper viscosity and quality oil are being used as recommended in the Owner Manual.
6. Record the vehicle mileage, date, and exact oil level on the form included in this bulletin.
7. Ask the customer to verify the oil level, each time the vehicle is fueled, following steps 1–6 and return the vehicle to the dealership if the oil level is found at or below the add mark, 0.946 liter (1 qt) low. If the oil level remains above the add mark, the customer should continue to operate the vehicle and verify the engine oil level until 3200 km (2000 mi) has accumulated before returning to the dealership for a final evaluation.
8. If the final evaluation shows that the engine uses more than 0.946 liter (1 qt) in 3200 km (2000 mi), follow the published symptom diagnostics as described in the appropriate Service Manual. If the oil consumption test shows that the engine uses less than 0.946 liter (1 qt) in 3200 km (2000 mi), explain to the customer that their engine meets the guidelines for oil consumption.

Oil Economy Test — Data Sheet

Dealer
 Name: _____
 Customer
 Name: _____
 Phone: (____)____-____ Phone:
 (____)____-____
 VIN: _____
 Oil Type Used: _____
 R.O. #: _____

Step	Date	Mileage	Oil Level	Engine Hours	Equivalent Odometer Value	Driving Conditions (City, Highway, Both)
1						(Start of Test)
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						

GM bulletins are intended for use by professional technicians, NOT a "do-it-yourselfer". They are written to inform these technicians of conditions that may occur on some vehicles, or to provide information that could assist in the proper service of a vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do a job properly and safely. If a condition is described, DO NOT assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See your GM dealer for information on whether your vehicle may benefit from the information.



WE SUPPORT VOLUNTARY
 TECHNICIAN
 CERTIFICATION