02/22/2023

MY 12-18 JK, 11-20 RT 18-23 JL, 17-23 RU, 11-16 JS, 20-23 JT, 11-23 LX, 11-23 WD, 13-23 DS 19-23 DT, 15-17 UF, 14-23 DX, 11-22 WK, 21-23 WL, 22 WS, 14-22 KL, 14-23 VF, 15-23 LA, 11-14 LC, 11-23 LD, 12-20 JC, 11-14 RM, 11-16 JF.

## **GPOP - Issue Review System**

Part Number: 05184294A\$, 68105583A\$, 68308741A\$, 68310865A\$, 68365925A\$,

68365931A\$

Part Description: ADAPTER, Engine Oil Filter (Pentastar V6)

**Issue** For all 2014MY replace the Oil Filter Adapter (OFA). For any other MY review and follow **Description:** instructions from the latest STAR Online S1809000007 available on Dealer Connect. Also, consider the following:

1) Remove OFA 2) Replace only the oil inlet O-ring and gaskets (seals kit in SOL above). 3) Re-install the OFA. For 2023MY and beyond use black O-ring. For 2022MY and prior use red O-ring, Note:

When replacing OFA, it may be necessary to transfer the Oil Temp/Pressure Sensor from the old OFA to the new OFA.