



Service Bulletin

Bulletin No.: 19-NA-255

Date: January, 2024


TECHNICAL

Subject: Wax Coating on Frame Peeling, Metal Shows Corrosion/Rusting (U.S. and Canada Only)

Attention: This Bulletin also applies to any of the models that may be Export from North America vehicles.

Brand:	Model:	Model Year:		VIN:		Engine:	Transmission:
		from	to	from	to		
Cadillac	Escalade Models	2011	2024				
Chevrolet	Avalanche	2011	2013			All	All
	Express	2011	2024				
	Suburban						
	Tahoe						
	Silverado	2011	2018				
	Silverado 1500 (New Model - 12th VIN Digit = 7) - 4WD	2019	2019				
	Silverado 1500 (New Model)						
	Silverado LD						
	Silverado 2500/3500						
	Silverado 1500	2020	2021				
	Silverado 2500HD/3500HD	2020	2024				
	Silverado 1500 LTD (RPO J21, VIN Digit 5 = W / Y)	2022	2022				
	Silverado 1500 New (RPO J22, VIN Digit 5 = A / D)	2022	2022				
	Silverado 1500	2023	2024				

Brand:	Model:	Model Year:		VIN:		Engine:	Transmission:
		from	to	from	to		
GMC	Savana	2011	2024			All	All
	Yukon Models						
	Sierra	2011	2018				
	Sierra 1500 (New Model)	2019	2019				
	Sierra Limited						
	Sierra 2500/3500	2020	2021				
	Sierra 1500						
	Sierra 2500HD/3500HD	2020	2024				
	Sierra 1500 Limited (RPO J21, VIN Digit 5 = 8 / 9)	2022	2022				
	Sierra 1500 New (RPO J22, VIN Digit 5 = H / U)	2022	2022				
	Sierra 1500	2023	2024				

Involved Region or Country	North America, Europe, Middle East, Israel, Palestine, Chile, Columbia, Ecuador, Paraguay, Peru, Uruguay, Japan, S Korea, China, Taiwan, Thailand, Africa and Egypt, Russia, Uzbekistan, S. Africa, Australia and New Zealand.
Condition	<p>Some customers may comment that areas of the frame wax coating are peeling off and rust/corrosion is visible on the metal in these areas. Several examples of this condition are shown in each group of graphics below.</p> <p>Truck Example Photos</p> 



2708906



2708908

Van Example Photos



3396076



3396078



3396079

3396080

<p>Cause</p>	<p>The cause of this condition may be that the frame supplier may not have properly prepped the metal before the wax coating was applied.</p>
<p>Correction</p>	<p>Note: A combination of specialized metal coating products manufactured by Lloyds and Daubert have been found to be the most suitable products to provide corrosion control and protection to address this type of repair. Our recommendation is to prep the metal surface using *Lloyd's Pure Prep™ Metal Surface Preparation P/N 25418, then topcoat with both *Lloyds Kryptonite™ Metal Treatment* - P/N 36500 High Temp Satin Black 455 ml (16 oz), and *Daubert Non-Rust® P/N X-121B One Coat Rust Preventative Coating. It is strongly recommended they be applied according to the manufacturer's procedures.</p> <p>*We believe this source and their products to be reliable. There may be additional manufacturers of such products/materials. General Motors does not endorse, indicate any preference for, or assume any responsibility for the products or material from this firm or for any such items that may be available from other sources.</p> <p>Prep the frame and apply the Lloyds and Daubert coatings following the steps in the Service Procedure below:</p>

Service Procedure

Important: Important: Service agents must comply with all International, Federal, State, Provincial, and/or Local laws applicable to the activities it performs under this bulletin, including but not limited to handling, deploying, preparing, classifying, packaging, marking, labeling, and shipping dangerous goods. In the event of a conflict between the procedures set forth in this bulletin and the laws that apply to your dealership, you must follow those applicable laws.

Important: To ensure proper coating performance, all of the manufacturer's "Applications Guidelines" MUST be followed.

Note: The graphics below show the bed and/or cab removed from the vehicle. These pictures are provided for reference only. Bed and/or Cab removal are not necessary. Dealers should only repair the locations that show the condition. The following procedure should be utilized to return the truck to a factory look.

1. Raise and suitably support the vehicle. Refer to *Lifting and Jacking the Vehicle* in the Service Manual.



2708909

2. If labels are in the area to be reworked, remove any of the visible white labels on the frame (usually one per side).
3. Remove any components as required to gain access to the corroded component or area.


Important: Any corrosion damage noted to the extent of weakening the component will require component replacement.

4. Determine a start and finish point on each side for the section/area of the frame to be repaired.



3611133

5. Using a rag and wax/grease removing solvent, remove the wax coating and any grease, oil, or undercoating from the truck frame in the affected repair area. The graphic above shows an example of a small portion of the wax coating removed.



2708911

Important: Lloyds Krytonite is designed to apply directly onto brown rust or clean surfaces; however any loose flakes/scale of rust need to be removed prior to application.

6. Any loose rust or loose flakes should be scraped, wire brushed or ground off.
7. Remove any residual wax, oil or rust by wiping the frame down with a towel or Scotch-Brite™ (3M) pad soaked with wax/grease remover.



3611135


8. Using Lloyd's Pure Prep™ Metal Surface Preparation P/N 25418 (10 fluid ounce bottle), or equivalent, saturate a towel or Scotch-Brite™ (3M) pad with the pre-diluted solution and scrub the area well, rendering a foaming of the Pure Prep.™ This will greatly improve adhesion and corrosion resistance in the repair areas.



2708913

Important: The frame must be dry and free of wax/oily substances prior to application of the new coating.

9. Using a water dampened clean towel, remove any residue and dry the affected area. Dry the repair area completely using an air hose to blow dry the frame.
10. Check the repair area for phosphate treatment by wiping it to see if any corrosion residue can be picked up. Correctly treated areas will not have any residue on the surface.



3611138

Note: For application of the Lloyds Kryptonite P/N 36500, it can be sprayed, rolled, dipped or painted.

11. To retain corrosion protection, apply a light coat of Lloyds Kryptonite™ Metal Treatment* - P/N 36500 High Temp Satin Black 455 ml (16 oz), or equivalent, to all rusted and bare areas of the frame where the wax coating was removed. This first coat should flash in approximately 3-5 minutes.
12. Apply a second coat of Lloyds Kryptonite. This can be a heavy coat; double and triple passes with this product, over a light first coat, are not a problem.

Note: Dried Lloyds Kryptonite will perform beautifully over time and actually get harder and more durable as it experiences heat.



3611142

13. We suggest top coating the Lloyds Kryptonite with Daubert Nox-Rust® P/N X-121B "One Coat Rust Preventative Coating" (aerosol), or equivalent.

Note: As shown in the graphic below, besides adding a corrosion resistant layer, it dries to firm, wax-like film which will more closely resemble the appearance of the unrepaired areas of the frame.



3611143

14. Lower the vehicle and allow the final coat to dry as recommended by the manufacturer.

Parts Information

Dealers should obtain 25418 and 36500 by contacting Lloyds by e-mail at sales@lloydslaboratories.com, or by calling 1-800-361-6766.

U.S. Dealers can obtain the X-121B topcoat by contacting the Daubert website at www.daubertchemical.com or inside the U.S. only, by calling 1-800-914-0034.

Canadian dealers must contact the Daubert distributor in Canada, Corrosion Control Coatings Ltd, by faxing the form below to 1-800-563-8078.

Important: ONLY Canadian Dealers should use this form.



February 1, 2022

**GENERAL MOTORS DEALERSHIP ORDER FORM
FOR CANADIAN DEALERS ONLY**

U.S. Dealers can order 35-3180 spray-on rust prevention for GM cars and vans in the U.S. or Canada. For more information, call 1-800-563-9378.

Fax Order to: 1-800-563-9378

Address: <u> </u> <u> </u> <u> </u>		Ship To: <u> </u> <u> </u> <u> </u>	
Bill To: <u> </u> <u> </u> <u> </u>		Dealer #: <u> </u> <u> </u> <u> </u>	
Phone: <u> </u>		Contact Name: <u> </u>	
Fax: <u> </u>		Phone: <u> </u>	
Next Rust X1210 Aerosol Rust Preventive Coating Cases (12 cans per case) # <u> </u> of cases # <u> </u> of cans		Cost per Case \$ 225.00 + shipping & applicable tax Cost per Can \$18.75 + shipping & applicable tax	
Order Desk Information: Corrosion Control Coatings Ltd. 106 Colborne Street Walkerton, Ontario N0G 2V0 Phone: 519-861-1594 or 800-934-7771 Fax: 500-563-9378 E-Mail: CanadaSales@corrosion.com		Payment Information: All orders require payment by Credit Card. Please include credit card information. Credit Card # <u> </u> Expiry Date: <u> </u> CVV: <u> </u> Only Visa or MasterCard Accepted	
Special Notes: <u> </u> <u> </u> <u> </u>			
Confirmation: (CC Use only)		Ship Date: <u> </u> Rec'd By: <u> </u>	

Warranty Information

For vehicles repaired under the Bumper-to-Bumper coverage (Canada Base Warranty coverage), use the following labor operation, **and include material cost**. Reference the Applicable Warranties section of Investigate Vehicle History (IVH) for coverage information.

Labor Operation	Description	Labor Time
1480098*	Remove Frame Wax, Apply Metal Coating	Up to 7.0 hrs
*This is a unique Labor Operation for Bulletin use only.		

Version	6
Modified	Released November 18, 2019 Revised July 22, 2020 – Added 2019 and 2020 T1 Pickup Models. Revised March 10, 2021 – Added 2021 Model Year. Revised February 07, 2022 – Added 2022 Model Year Revised November 07, 2022 – Added 2023 Model Year and Because Lloyds Kryptonite Metal Treatment P/N 36502 Lifelong Rust Protection is No Longer Available we Updated the Product to Lloyds Kryptonite™ Metal Treatment* - P/N 36500 High Temp Satin Black 455 ml (16 oz). Revised January 18, 2024 – Updated Model Years.

