



# Service Bulletin

Bulletin No.: 22-NA-039

Date: January, 2024

## INFORMATION

**Subject:** Information on Front License Plate Adapter Bracket Installation During PDI

Brand:	Model:	Model Year:		VIN:		Engine:	Transmission:
		from	to	from	to		
GMC	HUMMER EV	2022	2024			All	All

<b>Involved Region or Country</b>	United States, Canada, Middle East
<b>Condition</b>	Installation of front license plate adapter bracket during PDI.
<b>Correction</b>	Follow the appropriate installations if a front license plate is or is not required.

### Service Procedure

**Important:** This technical service bulletin (TSB) can only be completed by certified repair facilities who have met all specific training, tool and equipment requirements pertaining to the vehicle Brand and Model serviced. Repairs must be performed by a technician who has successfully completed the required training.

**Important:** Service agents must comply with all International, Federal, State, Provincial, and/or Local laws applicable to the activities it performs under this bulletin, including but not limited to handling, deploying, preparing, classifying, packaging, marking, labeling, and shipping dangerous goods. In the event of a conflict between the procedures set forth in this bulletin and the laws that apply to your dealership, you must follow those applicable laws.

**Note:** In the dealer PDI trunk kit from the factory, you will find the silver front license plate adapter and a set of 4 retainers and screws.

### Procedure Without Front License Plate



5990749

**Note:** When not equipped with a front license plate, the silver license plate bracket is to be secured to the front bumper assembly.

1. Remove the black bolt/screws (1) from the lower portion of the fascia.
2. Align the bottom of the license plate bracket to the black T-shaped retainers (2).

3. Push the bracket into place while aligning and securing the 4 tabs across the top into the fascia. Push gently to fully seat the bracket assembly.
4. Secure the black bolt/screws (1) into the lower portion of the fascia.

**Tighten**

Tighten the bolt/screws to 2,5 Nm (22 lb in).



5990750

**Procedure With Front License Plate**



5990751

**Note:** This installation procedure should only be completed when the front license plate is ready to be installed.

1. Drill four 4.5 mm (3/16") holes into the license plate bracket. There are 4 small dimples on the back of the bracket that must be drilled out.



5990752

**Note:** If the retainers are already installed, give any extra retainers to the customer.

2. In the dealer PDI trunk kit, there are 4 white retainer and 4 license plate screws. Insert the white retainers into the front bumper.



5990749

3. Install the pre-drilled license plate bracket onto the front bumper. Refer to Steps #1-4 from the above procedure.



5990753

**Caution:** To avoid damaging the license plate, do NOT over torque the screws.

4. Install the customers license plate over the top side of the silver painted bracket and secure with the 4 license plate screws.

### Warranty Information

The labor time for installing the front license plate adapter is included in the PDI time.

<b>Version</b>	4
<b>Modified</b>	Released February 18, 2022 Revised December 15, 2022 - Added 2023 Model Year. Revised April 26, 2023 - Added two Important statements under the Service Procedure and 2024 HUMMER EV SUV. Revised January 25, 2024 - Added 2024 HUMMER EV and Middle East.

