Service Alert

Mazda North American Operations Irvine, CA 92618-2922



Subject:

GEN 6 INFOTAINMENT CENTER DISPLAY REPAIR KIT (GHOST TOUCH, SPIDER CRACKING, SURFACE PEELING, WHITE DOTS)

Service Alert No.: SA-027/24

Last Issued: 04/26/2024

BULLETIN NOTES

This SA supersedes the previously issued Service Alert(s) listed below. The changes are noted in Red.

Previous SAs:	Date(s) Issued:				
SA-001/23	01/03/23 and 01/12/23				
SA-041/22	11/22/22, 09/13/22, 08/17/22 and 06/22/22				

APPLICABLE MODEL(S)/VINS

2016-2021 Mazda2 (Mexico/Puerto Rico) with VINS lower than 3MDDJ******409029 (produced before July 13, 2021) 2022 Mazda2 (Mexico) with VINS between 3MDDJ******450001 - 452967 (produced from July 20, 2021 to February 3, 2022)

2014-2016 Mazda3

2017-2018 Mazda3 (Japan built) with VINS between JM1BN******100017 - 199538 (produced from June 27, 2016 to October 31, 2018)

2017-2018 Mazda3 (Mexico built) with VINS between 3MZBN******100013 - 277187 (produced from September 1, 2016 to December 20, 2018)

2016 Mazda6 (equipped with Center Display P/N GRT7-61-1J0 or GRT7-61-1J0A)

2017-2021 Mazda6

2016-2022 CX-3 with VINS lower than JM1DK******604871 (produced before April 28, 2022)

2017-2020 CX-5 (equipped with Center Display P/N K123-61-1J0 or K123-61-1J0A)

2016-2020 CX-9 with VINS lower than JM3 TC **** ** 424641 (produced before July 13, 2020)

2016-2022 MX-5

Page 1 of 28

DESCRIPTION

Some customers may complain about infotainment center display:

Ghost Touch DTC B108E:04 may be stored	(Touch screen operates by itself)
Surface Peeling DTC B108E:04 may be stored	
Spider Cracks	87.9
White dots	

IMPORTANT NOTE: <u>DO NOT</u> replace the infotainment center display assembly. Low cost repair kits are available to repair the infotainment center display screen.

Customers having this concern should have their vehicle repaired using the following repair procedure.

Page 2 of 28

REPAIR PROCEDURE

IMPORTANT NOTE: Repair kits will only fix the symptoms shown in the table below.

Index

		Symptom					
Model	Year	Ghost Touch DTC B108E:04 may be stored	Surface Peeling DTC B108E:04 may be stored	Spider Cracking	White dots		
Mazda2	2016-2021 (Mexico/Puerto Rico) with VINS lower than 3MDDJ*****409029 (produced before July 13, 2021) 2022 (Mexico) with VINS between 3MDDJ*****450001 - 452967 (produced from July 20, 2021 to February 3, 2022)	Go to 09-003/ 23	Go to 09-003/23	Go to 09-003/ 23	Go to 09- 003/23		
Mazda3	2014-2016	Go to SSPB6	Go to Mazda3 Repair	Go to Mazda3 Repair	N/A		
Mazda3	2017-2018 Japan built - with VINS between JM1BN******100017 - 199538 (produced from June 27, 2016 to October 31, 2018) Mexico built - with VINS between 3MZBN******100013 - 277187 (produced from September 1, 2016 to December 20, 2018)	Go to 09-045/ 22	Go to 09-045/22	N/A	N/A		
Mazda6	2016 equipped with Center Display P/N GRT7- 61-1J0 or GRT7-61-1J0A 2017 with VINS lower than JM1GL*****156205 produced on or before December 29, 2017	Go to TSB 09- 021/22	Go toTSB 09- 021/22	Go toTSB 09- 021/22	N/A		
	2017-2021 with VINS higher than JM1GL*****156205 produced after December 29, 2017	Go to Mazda6 Repair	Go to Mazda6 Repair	Go to Mazda6 Repair	N/A		
CX-3	2016-2022 with VINS lower than JM1DK*****604871 (produced before April 28, 2022)	Go to 09-003/ 23	Go to 09-003/23	Go to 09-003/ 23	Go to 09- 003/23		
CX-5	2017-2020 with VINs lower than JM3KF*****869655 (produced before August 25, 2020)	Go to TSB 09- 003/22	Go to TSB 09- 003/22	Go to CX-5 Repair	N/A		
CX-9	2016-2020 with VINS between JM3 TC **** ** 100001 -	N/A	Order exchange un Note: United Radi				

Page 3 of 28

	424641 (produced before July 13, 2020)		customer pay or going is out of warranty	oodwill purchase	es if vehicle
			Note: VINs below extension (SSPB9	•	ranty
			127083	JM3 TC**** G0 1 JM3 TC**** H0 1	
MX-5	2016-2022	Go to TSB 09- 003/23	Go to TSB 09- 003/23	Go to TSB 09- 003/23	Go to 09- 003/23


Page 4 of 28

- 1. Verify the customer concern.
- 2. Disassemble the center display and replace the lens (inner part) with a newly established part according to the following steps:
- 3. Print the Parts Flash table and provide to the parts counterperson.

NOTE: Wear the rubber gloves to protect the lens, cable and electronic circuit.

Repair parts set:

No.	No. Description		Notes
(1)	Center Display Lens	1	Cushion materials for packa ging are used to protect the I ens surface when disassem bled.
(2)	Rubber gloves	1	Anti-static






NOTE:

- Center display lens is packaged in bubble wrap and cushion material.
- Unwrap the package carefully so the cushion material can be used to protect the lens surface when disassembling the center display.
- The center display lens is equipped with cables (FPC: Flexible Printed Circuit), so be careful when handling it.

Page **5** of **28**



(1) Bubble wrap



(2) Cushion material

CENTER DISPLAY DISASSEMBLY:


Remove the center display according to the instructions on MGSS:

- Mazda3 CENTER DISPLAY REMOVAL/INSTALLATION
- Mazda6 CENTER DISPLAY REMOVAL/INSTALLATION
- CX-5 CENTER DISPLAY REMOVAL/INSTALLATION

Page 6 of 28

Mazda3 Repair

1. Remove the 4 screws (1), then remove the connectivity master unit (CMU) (2) from the center display (3).



- 2. Place the cushion sheet (1) that wrapped lens before, on a clean, flat surface.
- 3. Put on the rubber gloves.
- 4. Place the center display (2) on the cushion sheet (1) with the display side facing downward.




5. Remove the 4 screws from the center display cover panels.






Page 7 of 28


6. Remove the lower cover panel by pulling it up off the bracket, then lift off the back cover panel.




7. Remove the 4 screws from the bracket.



8. Unlock the bracket with a flat head screw driver by carefully prying out and upward on the bracket.






CAUTION: DO NOT pry on the printed circuit board.

Page **8** of **28**


9. Remove the bracket.



10. Unlock and disconnect the printed wiring harness.




11. Remove the electric circuit board (1) from the display lens (2).



CAUTION: Be very careful handling the electric circuit board as it will be reused.


Page 9 of 28

12. Assemble the modified display lens with the removed electric circuit board.



NOTE 1:

- Peel off the protection film from the inside lens surface when replacing.
- Peel off the protection film on the outside lens surface after installing the center display to the vehicle.



NOTE 2: Solidly connect the printed wiring harness to the connector in order to avoid the half insertion of the printed wiring harness.

13. Install the center display in the reverse order of removal.

NOTE: DO NOT tighten the screws too tightly, but tighten them so that they do not come loose.

14. Verify the repair.


Page 10 of 28


Mazda6 Repair

1. Check the Center Display Part Number (1-2).


Is the Part Number GRT7-61-1J0 or GRT7-61-1J0A?

- Yes Go to next step.
- No This service information does not apply. Replace the Center Display unit. Go to MGSS CENTER DISPLAY REMOVAL/INSTALLATION






2. Remove the 4 screws (1), then remove the connectivity master unit (CMU) (2) from the center display (3).





- 3. Place the cushion sheet (1) that the lens was wrapped on a working table.
- 4. Put on the rubber gloves.
- 5. Place the center display (2) on the cushion sheet (1) with the display side facing downward.





Page 11 of 28

6. Remove the 4 screws (1) that assemble the center display (2) and the bracket (3), then separate the bracket (3) and the cover panel (4).












7. Remove the 2 screws (1) on the back of the center display.




Page 12 of 28

8. Insert a tip of a flathead screwdriver (3) in the gap (2) between the lens and the rear cover.






Detail of (1)




Page 13 of 28

9. Pull up the rear cover with a flathead screwdriver (1) while being careful to not touch the connector, then remove the rear cover.


CAUTION: Be careful not to damage the circuit board and the connectors when removing the rear cover.





Pull the rear cover outward so that the cover does not touch the connectors.

Center display (joint with rear cover)



Rear cover (joint with center display)




Page 14 of 28

10. Remove the 4 screws (circled in yellow).

Service Alert No.: SA-027/24




11. Push the locking tab (2) on the connector (1) to unlock it while pushing the circuit board, then remove the cable (FPC: Flexible Printed Circuit) (3).



Page 15 of 28

NOTE: Pull out the cable by holding both side-edges of it to avoid damaging the cable.





- 12. Remove the center display from the lens.
- 13. Replace the lens with a modified one, reusing the center display

Replace the lens with a modified one.



Reuse the center display.



14. Assemble the center display in the reverse order of disassemble.

NOTE:

- DO NOT tighten the screws too tightly, but tighten them so that they do not come loose.
- · When attaching the cable to the circuit board, be careful not to engage with the connector half-fit.
- 15. Install the center display in the reverse order of removal.
- 16. Verify the repair.


Page **16** of **28**

CX-5 Repair


1. Check the Center Display Part Number (1-2).

Is the Part Number K123-61-1J0 or K123-61-1J0A?


- Yes Go to next step.
- No This service information does not apply. Replace the Center Display unit. Go to MGSS CENTER DISPLAY REMOVAL/INSTALLATION



2. Remove the 4 four screws (1), then remove the connectivity master unit (CMU) (2) from the center display (3).




- 3. Place the cushion material (1) that the lens was wrapped in, on a workbench.
- 4. Put on the rubber gloves.
- 5. Place the center display (2) on the cushion material (1) with the display side facing downward.




Page 17 of 28

6. Remove the 4 screws (1) that assemble the center display (2) and the bracket (3), then separate the bracket (3) and




7. Remove the 2 screws (1) that assemble the center display and the rear cover (2).



Page 18 of 28


- 8. Remove the rear cover according to the following steps.
 - There are 3 three fitting sections of the rear cover and the center display.
 - The number in the image below is the order in which to unhook the ribs.



Rear cover





Center display




Page 19 of 28


a. Unhook rib (1) by inserting the tip of a flathead screwdriver in the gap (2) between the lens and the rear cover below connectors (4), then unhooking the rib (3).








Rib (3) of the rear cover



Rib (3) of the rear cover



Hook (5) of the center display


Page 20 of 28


b. Unhook rib (2) by inserting the tip of a flathead screwdriver in the gap (2) between the lens and the rear cover, then unhooking the rib.






c. Unhook rib (3) by inserting the tip of a flathead screwdriver in the gap (3) between the lens and the rear cover, then unhooking the rib.






Page 21 of 28

9. Pull up the rear cover (1) carefully so that the rib (3) does not touch the connectors (2), then remove the rear cover.





Rear cover



Center display



Page 22 of 28

10. Remove the 4 screws shown below.




Bracket



Center display



11. Remove the cable (FPC: Flexible Printed Circuit) in order (1), (2), (3) as shown in the image below. **NOTE:** To unlock the connector, pull up the locking tab while holding the circuit board.



Page 23 of 28


ATTENTION: Pull out the cable by holding both side-edges to avoid damaging the cable.








Locked





Unlocked



- (1) Cable
- (2) Locking tab
- 12. Remove the center display from the lens.
- 13. Replace the lens with a modified one, but reuse the center display Lens







Page 24 of 28

14. Assemble the center display in the reverse order of disassembly.

NOTE:

- When attaching the cable to the circuit board, be sure the connection is secure.
- DO NOT use electric tools to tighten the screws. Overtightening the screws (circled in yellow in the following figures) may cause uneven brightness of the display. If uneven brightness occurs, loosen the screws and retighten them to the point to avoid coming loose.










Example of the uneven brightness:



Page 25 of 28

- 15. Install the center display in the reverse order of removal.
- 16. Verify the repair.

Page **26** of **28**

PARTS INFORMATION

Year	Model	Part Number	Description	Qty.	Note Verify Vehicle Infotainment Center Display Part Label
2016-2017	Mazda2	D0YP-61- 1JZ	Center Display Lens Kit	1	Kit repairs P/N D09H-61-1J0B or older
2018-2019	Mazda2	DY1P-61- 1JZ	Center Display Lens Kit	1	Kit repairs D23N-61-1J0A or older
2019-2021	Mazda2	D2YN-61-	Center Display	1	Kit ropoiro D/N D22N 61 1 IOP only
2022	Mazda2	1JZA	Lens Kit	ı	Kit repairs P/N D23N-61-1J0B only
2014-2016	Mazda3	BHY1-61- 1JZ	Center Display Lens Kit	1	
2017-2018	Mazda3	B6YA-61- 1JZ	Center Display Lens Kit	1	For verhicles equipped with display B61A-61- 1J0* Includes a center display lens and antistatic rubber gloves
2016	Mazda6	GRY7-61- 1JZ	Center Display Lens Kit	1	Kit repairs P/N GRT7-61-1J0 or GRT7-61-1J0A only Vehicles equipped with center display P/N GML8-611J0 do not apply to this service information.
2017-2021	Mazda6	GRY7-61- 1JZ	Center Display Lens Kit	1	If the display part number IS NOT GRT7-61-1J0 or GRT7-61-1J0A, this is not applicable.
2016-2017	CX-3	D0YP-61- 1JZ	Center Display Lens Kit	1	Kit repairs P/N D09H-61-1J0B or older
2018-2020	CX-3	DY1P-61- 1JZ	Center Display Lens Kit	1	Kit repairs D23N-61-1J0A or older
2019-2022	CX-3	D2YN-61- 1JZA	Center Display Lens Kit	1	Kit repairs P/N D23N-61-1J0B only
2017-2020	CX-5	K1Y3-61- 1JZ	Center Display Lens Kit	1	Kit repairs P/N K123-61-1J0 or K123-61-1J0A only Vehicles equipped with center display P/N K123-61-1J0B or later suffix are already modified and do not apply to this service information.
2016-2020	CX-9	TK48-61- 1J0	Display,Information	1	Place an order for exchange unit to United Radio Center Display 7 inches (Exchange part)

Page 27 of 28

		TK49-61- 1J0B	Display,Information	1	Place an order for exchange unit to United Radio Center Display 8 inches (Exchange part)
2016-2017	MX-5	D0YP-61- 1JZ	Center Display Lens Kit	1	Kit repairs P/N NA1P-61-1J0B or older
2018-2020	MX-5	D1YP-61- 1JZ	Center Display Lens Kit	1	Kit repairs P/N ND1F-61-1J0A or older
2020-2022	MX-5	D2YN-61- 1JZA	Center Display Lens Kit	1	Kit repairs P/N ND1F-61-1J0B or ND1F-61-1J0C only

Page 28 of 28