

Diagnosis and Handling of 12-Volt Lithium-Ion Battery (Vehicle Electrical System Battery) (31/20)



Information

Please also refer to the Standard Form PNA 000 162 QM — Lithium-Ion Battery Checklist - Lightweight battery 60 Ah (I-no. J2A), which can be found on PCSS.

For more information on the component protection functions of the 12-volt on—board battery and how they work, see the → *Technical Information 'Technical Background'* section.

Change overview

Version	Date	Change
0	06/29/2020	• First publication
1	10/13/2021	• Update of Technical background and Procedure
2	01/06/2023	• TI setup adapted • Information on battery diagnosis supplemented
3	03/30/2023	• Checklist added in the "Battery diagnosis" section (prerequisite for invoicing with Porsche AG)
4	08/11/2023	• Information for Battery diagnosis updated
5	02/08/2024	• Information for fault status of the battery separator added
6	05/24/2024	• Omission of the checklist within this Technical Information (TI)

Vehicle Type: **Cayenne (9YA/9YB)**
911 Carrera (992)
Taycan (Y1A/Y1B/Y1C)

Model Year: **As of 2018**

Equipment: All lightweight batteries including Taycan (standard equipment) and Cayenne and 911 Carrera (I-no. J2A)

Concerns: **12-volt lithium-ion battery (12-volt vehicle on—board battery)**

Cause: **On vehicles in which a lithium-ion vehicle electrical system battery is installed, the battery is sometimes replaced even though it is not defective.**

This Technical Information is intended to help you to diagnose the battery in order to identify whether a battery is actually defective or whether only a temporary component protection function, which can be reset using appropriate measures, i.e. is reversible, was activated.

- Content:
- Battery diagnosis ⇒ *Technical Information 'Battery diagnosis'*
 - Technical background ⇒ *Technical Information 'Technical background'*
 - Charging 12-volt vehicle electrical system battery ⇒ *Technical Information 'Charging the battery'*
 - Questions and Answers ⇒ *Technical Information 'Questions & Answers'*

Battery diagnosis



Information

If in doubt about the status of the lithium-ion battery (e.g. due to smoke, steam, heat development, odor or other abnormalities), first classify the lithium-ion battery according to the Workshop Manual ⇒ *Workshop Manual '2X00IN Classification of lithium-ion battery'*.

Otherwise, continue with the battery diagnosis as described below.



Information

There is no approved battery tester for the lithium-ion battery. The existing battery testers do not work for lithium-ion batteries because the algorithms for the acid/gel/AGM batteries are different.

By evaluating the actual values/measured values in the PIWIS Tester, it is possible that the status of the battery can be checked by evaluating the values that are actually present. The battery must already be installed in the vehicle at this time.

- Work Procedure: 1 Connect a battery charger suitable for lithium starter batteries with a rated current of at least 90 A (e.g. **VAS 5908 battery charger 90 A**) to the external power supply for jump-lead starting in the engine compartment and operate in automatic mode.
For instructions, see: ⇒ *Workshop Manual '2706IN External power connection, jump-lead starting'* and
⇒ *Workshop Manual '270689 Charging vehicle electrical system and battery'*

- 2 Connect **P90999 - PIWIS Tester 4** to the vehicle communication module (VCI) via the **USB cable**. Then connect the communication module to the vehicle and switch on the PIWIS Tester.

- 3 Switch on ignition.



Information

Please note that, **during the entire test** on the 12-volt vehicle electrical system battery, the **engine must not be started**.

- 4 Create vehicle analysis protocol (VAL) and mark it with the attribute 'Pre-VAL'.

- 5 Read out the fault memory of the Gateway control unit and check for the following fault memory entries.



Information

If the **test procedure** has already been **carried out twice** from step 5 and has led to an **identical result**, the 12-Volt vehicle electrical system battery must be replaced under the following circumstances:

- Test procedure was performed twice in full (e.g. step 5 to step 10)
- Test procedure was completed **twice** with the **same result** (e.g. allow 12-volt vehicle electrical system battery to rest for 24 hours or charge the 12-volt vehicle electrical system battery)
- Fault still persists

Assessment	Action
One of the following fault memory entries is stored in the gateway control unit: <ul style="list-style-type: none"> • P1B0200 – 12-volt battery monitoring, no function (8201CA) • P1D6C00 – 12-volt battery monitoring, no function (82000C) 	Check the fault status of the 12-volt vehicle electrical system battery. Continue with Step 6.
A fault memory entry is stored in the control unit gateway with reference to a faulty line connection.	Observe the guided troubleshooting for the respective specified fault memory entry.

- 6 Check the fault status of the 12-volt vehicle electrical system battery.
 - 6.1 Select the **gateway control unit** in the control unit selection.
 - 6.2 Select the **'Actual values / input signals'** menu.
 - 6.3 Check battery status.
 To do this, proceed as follows:
 - **Cayenne (9YA/9YB)**: Select the actual value group **'Battery (12 V)'** and press **•F12"** ("next") to confirm your selection. In the subsequent overview, select the value **'Battery (12 V)'**: **Select "Fault status"** and press **•F12"** ("next") to confirm.
 - **Taycan (Y1A/Y1B/Y1C)**: Select the actual value group **'Battery (12 V)'** and press **•F12"** ("next") to confirm your selection. In the subsequent overview, select the value **'Lithium-ion starter battery'**: **Select "Battery, fault status"** and press **•F12"** ("next") to confirm.
 - **911 (992)**: Select the actual value group **'Battery/battery sensor'** and press **•F12"** ("next") to confirm your selection. In the subsequent overview, select the value **'Battery (12 V)'**: **Select Fault status** and press **•F12"** ("next") to confirm.

Then read off the respective status in the 'Value' field and evaluate it with the help of the following table.

**Information**

If the **fault status** of the **battery separator** ("Lithium-ion starter battery: battery separator, fault status" or "Battery (12 V): battery separator, fault status") **displays a fault**, the **12-volt lithium-ion battery (vehicle electrical system battery)** must be **replaced** regardless of the battery status ("Lithium-ion starter battery: battery, fault status" or "Battery (12 V): fault status").

Corresponding proof must be appended to any request.

Battery status	Action
<ul style="list-style-type: none"> This is not a fault Internal sensor fault Battery deep discharge 	12-volt vehicle electrical system battery can be reactivated. Continue with Step 7.
<ul style="list-style-type: none"> Restricted performance Battery sensor defective Fuse defective 	Replace 12-volt vehicle electrical system battery. For instructions, see: ⇒ <i>Workshop Manual '270655 Replacing battery'</i>

- 7 Erase fault memory entries for all control units.
- 8 Switch off ignition.
- 9 Disconnect **P90999 - PIWIS Tester 4** from the vehicle.
- 10 After waiting for approx. 1 minute, read off the charging current on the charger.

Assessment	Action
The charging current increased significantly (generally 60 A - 90 A).	Fully charge 12-volt vehicle electrical system battery. Then create another VAL and check the gateway control unit again for existing fault memory entries analogous to step 5.
The charging current is <5 A.	12-volt vehicle electrical system battery is over-charged. Continue with Step 11.
The charging current is <5 A and the " Battery deep discharge " battery status was read out beforehand.	Replace 12-volt vehicle electrical system battery. For instructions, see: ⇒ <i>Workshop Manual '270655 Replacing battery'</i>

- 11 Switch off and disconnect the battery charger.
Then allow the 12-volt vehicle electrical system battery to rest for 24 hours.
- 12 After 24 hours of rest, measure the voltage at the 12-volt vehicle electrical system battery with a suitable measuring device.

Assessment	Action
The voltage of the 12-volt vehicle electrical system battery is > 13 V.	Connect the battery charger and fully charge the 12-volt vehicle electrical system battery. Then create another VAL and check the gateway control unit again for existing fault memory entries analogous to step 5.
The voltage of the 12-volt vehicle electrical system battery is 0 V.	<p>For a few seconds, connect a voltage of 14.4 V directly to the 12-volt vehicle electrical system battery. If necessary, the separating element can be closed (in this case, a single clicking noise is audible).</p> <ul style="list-style-type: none"> • If the separating element closes, charge the 12-volt vehicle electrical system battery via the external starting points using a suitable charger. • If the isolation element does not close or opens again directly after removing the power source, the 12-volt vehicle electrical system battery must be replaced. For instructions, see: ⇒ <i>Workshop Manual '270655 Replacing battery'</i>

Technical background

Information: The battery control unit, the battery sensor and an isolating element (contactor) are integrated in the lithium-ion battery. This control unit monitors the charging and discharging of the battery and opens the disconnecting element in the event of overcharging, deep discharge or overheating, for example, by interrupting the power supply to the battery. As a result, there is no voltage present at the battery terminals. Therefore, no voltage can be measured at the battery terminals (value is between 0 V - 2 V).

If the separating element is open, the vehicle is de-energized. This may be perceived as a battery fault, for example.

Opening conditions for the separating element:



Information

The voltage values given below are internal battery voltage values that cannot be read or measured. The status in the current VAL is always decisive for a battery diagnosis. The overview is only intended to provide information about the behavior of the 12-volt on-board power supply battery and its separating element.

- The separating element opens when the charge state (SoC) drops below 15% or the battery voltage drops below 10 V.

- The separating element opens when the battery voltage exceeds 16 V.
- The separating element opens permanently if the voltage falls below 6.5 V or exceeds 18 V. This state is irreversible. The battery must be replaced.
- The separating element opens in the event of overheating or short circuit. A classification document for the 12 V lithium-ion battery is stored in the PCSS, see ⇒ *Workshop Manual '2X00IN Classification of lithium-ion battery'*.

Charging 12-volt vehicle electrical system battery

- Use a suitable battery charger
- Set the correct charge voltage and charging current
- Work procedure for a discharged battery
- Work procedure for an overcharged battery
- Work procedure for a totally discharged battery

NOTICE

Important!

- **Only use Deutronic charger VAS 5908.**
- ⇒ **Battery chargers that are not suitable for lithium-ion batteries cannot be used.**

To prevent damage to the battery and vehicle electrical system, a charger that is suitable for lithium-ion batteries must be used - **Battery charger 90A**. The charger must also be set correctly. To do this, change the charging values as shown below.



Information

If the battery charging current is lower than the power consumption of the vehicle, the contactor will open if the system voltage drops.

When the contactor opens, non-certified chargers can cause voltage peaks above 28 V at present. This can damage the battery.



Information

In most cases, the charging values must be changed.

Detailed information can be found under Special tools in the PPN or in the Workshop Manual/operating instructions for the charger.

Set charging values as follows:

Voltage:	14.4 V
Maximum charging current:	90 A
Trickle charge voltage:	13.5 V DC

Cut-in voltage:	5.0 V DC
Trickle current:	5.0 A
Capacitive charging current:	5.0 A

Work procedure for a discharged battery



Information

If the battery is **discharged**, charge the battery as described and set the charging values specified above.

Questions & Answers

Is it possible to jump-start a vehicle with a lithium-ion battery?

See relevant section in the Owner's Manual of the vehicle.

What happens if a standard AGM battery is installed in the vehicle instead of the specified lithium-ion battery?

The installation of a standard AGM battery in Cayenne (9YA/9YB) / Taycan (Y1A) / 911 Carrera (992) vehicles equipped with a lithium-ion battery is not permitted.

If a standard AGM battery is installed in the vehicle, a warning message will be displayed because there is no LIN communication. The power supply network switches to emergency operation.

Can customers charge the battery at home?

The 12-volt lithium-ion battery can be charged using the Porsche Charge-o-mat Pro. For further information, refer to the operating instructions for the charger or contact Porsche Tequipment.



Information

Not relevant for the Taycan

Taycan vehicles cannot be charged using the Charge-o-mat Pro charger.

Warranty



Information

In order to invoice Porsche AG for work for diagnosis and, if necessary, for replacing the 12-volt lithium-ion on-board battery, the Standard Form PNA 000 162 QM—Lithium-Ion Battery Checklist – Lightweight battery 60 Ah (I-no. J2A), must be completed and attached to the relevant PCSS line. Otherwise, we reserve the right to reject or charge back the claim.

For documentation and warranty invoicing, enter the working position and PCSS encryption specified below in the warranty claim:

APOS	Labor operation	I No.
03350050	On board diagnostic - PIWIS tester	
03350053	On board diagnostic - Create VAL	
27060104	Vehicle electrical system battery check	
27065500	Vehicle electrical system battery replace	
03350060	On board diagnostic - System test after repair	

PCSS encryption:

Location (FES5)	27060	Vehicle electrical system battery*
Damage type (SA4)	4000	Electrical faults

*** PID 27050 Battery sensor, must not be used as this is only relevant for models with a separate battery sensor and not for the 12-volt lithium-ion battery**

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2024 Porsche Cars North America, Inc.