

Manufacturer's Certificate

Taycan (Y1A)

21/24 ENU 4400

4

Approved: Wheels and Tires (21/24)

Vehicle type: **Sport Sedan: Taycan / Taycan 4S / Taycan Turbo / Taycan Turbo S / Turbo GT**
Cross Turismo: Taycan 4 / Taycan 4S / Taycan Turbo / Taycan Turbo S
Sport Turismo: Taycan / Taycan 4S / Taycan Turbo / Taycan Turbo S

Model Year: **As of 2025**

Cause: Approval status: May 2024

Sizes: **Permissible summer tires and wheel sizes**
(RO = rim offset in mm, FA = front axle, RA = rear axle)

Tires	Tire sizes	Wheel sizes	Snow chains
Taycan Sport Sedan: Standard / Standard 4 / 4S			
Summer	19" FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	No
	20" FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 ZR 21 101 Y XL RA: 305/30 ZR 21 104 Y XL	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
	21" FA: 245/40 R 21 100 Y XL RA: 285/35 R 21 105 Y XL	FA: 9.0J x 21, RO 56 RA: 11.0J x 21, RO 59	
All-season	19" FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	
	20" FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 ZR 21 101 Y XL RA: 305/30 ZR 21 104 Y XL	FA: 9.5J x 21, RO 60	

Tires	Tire sizes	Wheel sizes	Snow chains
	FA: 265/35 R 21 101H XL RA: 305/30 R 21 104H XL	RA: 11.5J x 21, RO 66	
Winter	19" FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	RA only
	20" FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 R 21 103V RA: 305/30 R 21 107V	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	No

Tires	Tire sizes	Wheel sizes	Snow chains
Taycan Sport Sedan: GTS / Turbo / Turbo S / Turbo GT (Black Edition / Silver Edition)			
Summer	20" FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL Not for Turbo S vehicles. Not for Turbo GT.	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	No
	21" FA: 265/35 ZR 21 101 Y XL RA: 305/30 ZR 21 104 Y XL for Turbo vehicles: not standard for USA. Not for Turbo GT.	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
	21" FA: 245/40 R 21 100 Y XL RA: 285/35 R 21 105 Y XL for Turbo vehicles: not standard for USA. Not for Turbo GT.	FA: 9.0J x 21, RO 56 RA: 11.0J x 21, RO 59	
	21" FA: 265/35 ZR 21 (101Y) XL RA: 305/30 ZR 21 (104Y) XL	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	

Tires	Tire sizes	Wheel sizes	Snow chains
All-season	20" FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL Not for Turbo S vehicles. Not for Turbo GT.	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 R 21 101H XL RA: 305/30 R 21 104H XL Not for Turbo GT.	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
Winter	20" FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	RA only
	21" FA: 265/35 R 21 103V RA: 305/30 R 21 107V	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	No

Tires	Tire sizes	Wheel sizes	Snow chains
Taycan Cross Turismo: Standard / 4S / Turbo / Turbo S			
Summer	19" FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL Not for Turbo and Turbo S. *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	No
	20" FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 ZR 21 101 Y XL RA: 305/30 ZR 21 104 Y XL for Turbo vehicles: not standard for USA.	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
	21" FA: 245/40 R 21 100 Y XL RA: 285/35 R 21 105 Y XL	FA: 9.0J x 21, RO 56	

Tires	Tire sizes	Wheel sizes	Snow chains
	for Turbo vehicles: not standard for USA.	RA: 11.0J x 21, RO 59	
	21" FA: 265/35 ZR 21 (101Y) XL RA: 305/30 ZR 21 (104Y) XL Not for Standard: Not for 4S:	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
All-season	19" FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL Not for Turbo and Turbo S. *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	
	20" FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 R 21 101H XL RA: 305/30 R 21 104H XL	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
Winter	19" FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL Not for Turbo and Turbo S. *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	
	20" FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 R 21 103V RA: 305/30 R 21 107V	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	

Taycan Sport Turismo: Standard / 4S / GTS / Turbo / Turbo S			
Tires	Tire sizes	Wheel sizes	Snow chains
Summer	19" FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL Not for GTS. Not for Turbo and Turbo S. *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	No
	20" FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL Not for Turbo S vehicles.	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 ZR 21 101 Y XL RA: 305/30 ZR 21 104 Y XL for Turbo vehicles: not standard for USA.	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
	21" FA: 245/40 R 21 100 Y XL RA: 285/35 R 21 105 Y XL for Turbo vehicles: not standard for USA.	FA: 9.0J x 21, RO 56 RA: 11.0J x 21, RO 59	
	21" FA: 265/35 ZR 21 (101Y) XL RA: 305/30 ZR 21 (104Y) XL Not for Standard: Not for 4S:	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
All-season	19" FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL Not for GTS. Not for Turbo and Turbo S. *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	

Tires	Tire sizes	Wheel sizes	Snow chains
	20" FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL Not for Turbo S vehicles.	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 R 21 101H XL RA: 305/30 R 21 104H XL	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	
Winter	19" FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL Not for GTS. Not for Turbo and Turbo S. *)	FA: 8.0J x 19, RO 50 RA: 10.0J x 19, RO 47	RA only
	20" FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	FA: 9.0J x 20, RO 54 RA: 11.0J x 20, RO 60	
	21" FA: 265/35 R 21 103V RA: 305/30 R 21 107V	FA: 9.5J x 21, RO 60 RA: 11.5J x 21, RO 66	No

*) Not with Porsche Ceramic Composite Brake (PCCB) or Porsche Surface Coated Brake (PSCB).

The country code for the specific. Vehicle can be found in the PCSS under VEHICLE SEARCH WITH VIN, GENERAL DATA, COUNTRY EQUIPMENT.

Wheels:

Overview of Porsche wheels

Identification on the inside of the wheel:

Wheel size, rim offset (RO) in mm, part number (without color code marking FFF) and Porsche logo

19-inch Taycan Aero wheel

FA: 8.0J x 19, RO 50

Part No. 9J1.601.025.DB_FFF

RA: 10.0J x 19, RO 47

Part No. 9J1.601.025.DC_FFF



19-inch Taycan Aero wheel

19-inch Taycan S Aero wheel

FA: 8.0J x 19, RO 50

Part No. 9J1.601.025.DB_FFF

RA: 10.0J x 19, RO 47

Part No. 9J1.601.025.DC_FFF



19-inch Taycan S Aero wheel

20-inch Taycan Turbo Aero wheel 2

FA: 9.0J x 20, RO 54

Part No. 9J1.601.025.BN_FFF

RA: 11.0J x 20, RO 60

Part No. 9J1.601.025.BP_FFF

20-inch Turbo Wheel

FA: 9.0J x 20, RO 54
Part No. 9J1.601.025.AJ_FFF
RA: 11.0J x 20, RO 60
Part No. 9J1.601.025.AK_FFF

*20-inch Taycan Turbo wheel***20-inch Taycan Sport Aero wheel**

FA: 9.0J x 20, RO 54
Part No. 9J1.601.025.J_FFF,
Part No. 9J1.601.025.CR_FFF
RA: 11.0J x 20, RO 60
Part No. 9J1.601.025.K_FFF,
Part No. 9J1.601.025.CS_FFF

*20-inch Taycan Sport Aero wheel***20-inch Taycan Turbo S Aero Design**

FA: 9.0J x 20, RO 54
Part No. 9J1.601.025.AG_FFF
RA: 11.0J x 20, RO 60
Part No. 9J1.601.025.AH_FFF

*20-inch Taycan Turbo S Aero Design*

20-inch TEQ Design

FA: 9.0J x 20, RO 54

Part No. 9J1.601.025.DD_FFF

RA: 11.0J x 20, RO 60

Part No. 9J1.601.025.DE_FFF



20-inch Taycan TEQ Design wheel

20-inch Taycan off-road wheel

FA: 9.0J x 20, RO 54

Part No. 9J1.601.025.AS_FFF

RA: 11.0J x 20, RO 60

Part No. 9J1.601.025.AT_FFF



20-inch Taycan off-road wheel

21-inch Mission E Design wheel

FA: 9.5J x 21, RO 60

Part No. 9J1.601.025.BQ_FFF

RA: 11.5J x 21, RO 66

Part No. 9J1.601.025.BR_FFF

*21-inch Mission E Design wheel*

21-inch Cross Turismo Design wheel

FA: 9.5J x 21, RO 60

Part No. :9J1.601.025.AL_FFF

RA: 11.5J x 21, RO 66

Part No.: 9J1.601.025.AM_FFF



21-inch Cross Turismo Design wheel

21-inch RS Spyder Design wheel

FA: 9.5J x 21, RO 60

Part No. 9J1.601.025.BC_FFF

RA: 11.5J x 21, RO 66

Part No. 9J1.601.025.BD_FFF



21-inch RS Spyder Design wheel



Information

Improper handling can damage the wheel surface.

Carry out tire removal and mounting using a bead holding-down device only.

Use a leather pad on the rim flange to support the valve insertion tool.

Only use the Porsche centring clamping set for balancing.

Do not use hard brushes to clean the wheels as these can cause deep scratches that cannot be removed by polishing.

Never use solvents or other chemical substances not approved by Porsche on tires.

**Information**

Only install wheels with identical part number on each axle.

Exception: 21-inch Exclusive Design wheel and 21-inch Exclusive Design wheels with carbon-fiber aeroblades

Wheel
Mounting:

using wheel bolts:

Tightening torque 160 Nm (118 ftlb.)

Summer Tires:

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Sedan: Standard / Standard 4 / 4S	FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL	Continental Premium Contact 6 NFO FA: https://eprel.ec.europa.eu/qr/483380 RA: https://eprel.ec.europa.eu/qr/482780
		Hankook ventus S1 evo NFO FA: https://eprel.ec.europa.eu/qr/463553 RA: https://eprel.ec.europa.eu/qr/463560
		Michelin Pilot Sport 4 NFO FA: https://eprel.ec.europa.eu/qr/412377 RA: https://eprel.ec.europa.eu/qr/410806
	FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL	Michelin Pilot Sport 4 NFO FA: https://eprel.ec.europa.eu/qr/409571 RA: https://eprel.ec.europa.eu/qr/409604
		Pirelli CintuRato P7 Blue NFO FA: https://eprel.ec.europa.eu/qr/595725 RA: https://eprel.ec.europa.eu/qr/595726
	FA: 265/35 ZR 21 101Y XL RA: 305/30 ZR 21 104Y XL	Goodyear Eagle F1 Asymmetric3 NFO FA: https://eprel.ec.europa.eu/qr/529944 RA: https://eprel.ec.europa.eu/qr/529969
		Pirelli P-ZERO NFO FA: https://eprel.ec.europa.eu/qr/1832923 RA: https://eprel.ec.europa.eu/qr/1832924
	FA: 245/40 R 21 100Y XL RA: 285/35 R 21 105Y XL	Continental SportContact 7 NFO FA: https://eprel.ec.europa.eu/qr/808735 RA: https://eprel.ec.europa.eu/qr/808734
		Hankook iOn evo NFO FA: https://eprel.ec.europa.eu/qr/1676447 RA: https://eprel.ec.europa.eu/qr/1676435

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Sedan: GTS / Turbo / Turbo S / Turbo GT (Black Edition / Silver Edition)	FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL Not for Turbo S vehicles. Not for Turbo GT.	Michelin Pilot Sport 4 NFO FA: https://eprel.ec.europa.eu/qr/409571 RA: https://eprel.ec.europa.eu/qr/409604
		Pirelli CintuRato P7 Blue NFO FA: https://eprel.ec.europa.eu/qr/595725 RA: https://eprel.ec.europa.eu/qr/595726
	FA: 265/35 ZR 21 101Y XL RA: 305/30 ZR 21 104Y XL For Turbo vehicles: not standard for USA Not for Turbo GT.	Goodyear Eagle F1 Asymmetric3 NFO FA: https://eprel.ec.europa.eu/qr/529944 RA: https://eprel.ec.europa.eu/qr/529969
		Pirelli P-ZERO NFO FA: https://eprel.ec.europa.eu/qr/1832923 RA: https://eprel.ec.europa.eu/qr/1832924
	FA: 245/40 R 21 100Y XL RA: 285/35 R 21 105Y XL For Turbo vehicles: not standard for USA Not for Turbo GT.	Continental SportContact 7 NFO FA: https://eprel.ec.europa.eu/qr/808735 RA: https://eprel.ec.europa.eu/qr/808734
		Hankook iOn evo NFO FA: https://eprel.ec.europa.eu/qr/1676447 RA: https://eprel.ec.europa.eu/qr/1676435
	FA: 265/35 ZR 21 (101Y) XL RA: 305/30 ZR 21 (104Y) XL	Pirelli P-Zero R NFO FA: https://eprel.ec.europa.eu/qr/1790369 RA: https://eprel.ec.europa.eu/qr/1790370
		Pirelli P-Zero Trofeo RS NFO FA: currently no values available RA: currently no values available

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Cross Turismo: Standard / 4S / Turbo / Turbo S	FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL Not for Turbo and Turbo S.	Continental Premium Contact 6 NFO FA: https://eprel.ec.europa.eu/qr/483380 RA: https://eprel.ec.europa.eu/qr/482780
		Hankook ventus S1 evo NFO FA: https://eprel.ec.europa.eu/qr/463553 RA: https://eprel.ec.europa.eu/qr/463560
		Michelin Pilot Sport 4 NFO FA: https://eprel.ec.europa.eu/qr/412377 RA: https://eprel.ec.europa.eu/qr/410806
	FA: 245/45 R 20 103Y XL	Michelin Pilot Sport 4 NFO FA: https://eprel.ec.europa.eu/qr/409571

Model	Tire size	Tire make and type / Label value (link to EU database)
	RA: 285/40 R 20 108Y XL	RA: https://eprel.ec.europa.eu/qr/409604
		Pirelli Cinturato P7 Blue NFO FA: https://eprel.ec.europa.eu/qr/595725 RA: https://eprel.ec.europa.eu/qr/595726
	FA: 265/35 ZR 21 101Y XL RA: 305/30 ZR 21 104Y XL For Turbo vehicles: not standard for USA	Goodyear Eagle F1 Asymmetric3 NFO FA: https://eprel.ec.europa.eu/qr/529944 RA: https://eprel.ec.europa.eu/qr/529969
		Pirelli P-ZERO NFO FA: https://eprel.ec.europa.eu/qr/1832923 RA: https://eprel.ec.europa.eu/qr/1832924
	FA: 245/40 R 21 100Y XL RA: 285/35 R 21 105Y XL For Turbo vehicles: not standard for USA	Continental SportContact 7 NFO FA: https://eprel.ec.europa.eu/qr/808735 RA: https://eprel.ec.europa.eu/qr/808734
		Hankook iOn evo NFO FA: https://eprel.ec.europa.eu/qr/1676447 RA: https://eprel.ec.europa.eu/qr/1676435
	FA: 265/35 ZR 21 (101Y) XL RA: 305/30 ZR 21 (104Y) XL Not for Standard: Not for 4S:	Pirelli P-Zero R NFO FA: https://eprel.ec.europa.eu/qr/1790369 RA: https://eprel.ec.europa.eu/qr/1790370
		Pirelli P-Zero Trofeo RS NFO FA: currently no values available RA: currently no values available

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Turismo: Standard / 4S / GTS / Turbo / Turbo S	FA: 225/55 R 19 103Y XL RA: 275/45 R 19 108Y XL Not for GTS. Not for Turbo and Turbo S.	Continental Premium Contact 6 NFO FA: https://eprel.ec.europa.eu/qr/483380 RA: https://eprel.ec.europa.eu/qr/482780
		Hankook ventus S1 evo NFO FA: https://eprel.ec.europa.eu/qr/463553 RA: https://eprel.ec.europa.eu/qr/463560
		Michelin Pilot Sport 4 NFO FA: https://eprel.ec.europa.eu/qr/412377 RA: https://eprel.ec.europa.eu/qr/410806
	FA: 245/45 R 20 103Y XL RA: 285/40 R 20 108Y XL Not for Turbo S vehicles.	Michelin Pilot Sport 4 NFO FA: https://eprel.ec.europa.eu/qr/409571 RA: https://eprel.ec.europa.eu/qr/409604

Model	Tire size	Tire make and type / Label value (link to EU database)
		Pirelli CintuRato P7 Blue NFO FA: https://eprel.ec.europa.eu/qr/595725 RA: https://eprel.ec.europa.eu/qr/595726
	FA: 265/35 ZR 21 101Y XL RA: 305/30 ZR 21 104Y XL For Turbo vehicles: not standard for USA	Goodyear Eagle F1 Asymmetric3 NFO FA: https://eprel.ec.europa.eu/qr/529944 RA: https://eprel.ec.europa.eu/qr/529969
		Pirelli P-ZERO NFO FA: https://eprel.ec.europa.eu/qr/1832923 RA: https://eprel.ec.europa.eu/qr/1832924
	FA: 245/40 R 21 100Y XL RA: 285/35 R 21 105Y XL For Turbo vehicles: not standard for USA	Continental SportContact 7 NFO FA: https://eprel.ec.europa.eu/qr/808735 RA: https://eprel.ec.europa.eu/qr/808734
		Hankook iOn evo NFO FA: https://eprel.ec.europa.eu/qr/1676447 RA: https://eprel.ec.europa.eu/qr/1676435
	FA: 265/35 ZR 21 (101Y) XL RA: 305/30 ZR 21 (104Y) XL Not for Standard:	Pirelli P-Zero R NFO FA: https://eprel.ec.europa.eu/qr/1790369 RA: https://eprel.ec.europa.eu/qr/1790370
	Not for 4S:	Pirelli P-Zero Trofeo RS NFO FA: currently no values available RA: currently no values available

All-season tires:

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Sedan: Standard / Standard 4 / 4S	FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/483273 RA: https://eprel.ec.europa.eu/qr/482743
	*)	Goodyear Eagle Touring NFO FA: https://eprel.ec.europa.eu/qr/529945 RA: https://eprel.ec.europa.eu/qr/529946
	FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/483338 RA: https://eprel.ec.europa.eu/qr/481297
		Pirelli CintuRato P7 A/S NFO FA: https://eprel.ec.europa.eu/qr/595727 RA: https://eprel.ec.europa.eu/qr/595728
	FA: 265/35 R 21 101 H XL	Continental ProContact RX NFO

Model	Tire size	Tire make and type / Label value (link to EU database)
	RA: 305/30 R 21 104 H XL	FA: https://eprel.ec.europa.eu/qr/482746 RA: https://eprel.ec.europa.eu/qr/481299
		Goodyear Eagle Touring NF1 FA: https://eprel.ec.europa.eu/qr/1621908 RA: https://eprel.ec.europa.eu/qr/1585163

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Sedan: GTS / Turbo / Turbo S / Turbo GT (Black Edition / Silver Edition)	FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL Not for Turbo S vehicles. Not for Turbo GT.	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/483338 RA: https://eprel.ec.europa.eu/qr/481297
		Pirelli CintuRato P7 A/S NFO Turbo Sedan: not for USA. FA: https://eprel.ec.europa.eu/qr/595727 RA: https://eprel.ec.europa.eu/qr/595728
	FA: 265/35 R 21 101 H XL RA: 305/30 R 21 104 H XL Not for Turbo GT.	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/482746 RA: https://eprel.ec.europa.eu/qr/481299
		Goodyear Eagle Touring NF1 FA: https://eprel.ec.europa.eu/qr/1621908 RA: https://eprel.ec.europa.eu/qr/1585163

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Cross Turismo: Standard / 4S / Turbo / Turbo S	FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL Not for Turbo and Turbo S. *)	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/483273 RA: https://eprel.ec.europa.eu/qr/482743
		Goodyear Eagle Touring NFO FA: https://eprel.ec.europa.eu/qr/529945 RA: https://eprel.ec.europa.eu/qr/529946
	FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/483338 RA: https://eprel.ec.europa.eu/qr/481297
		Pirelli CintuRato P7 A/S NFO FA: https://eprel.ec.europa.eu/qr/595727 RA: https://eprel.ec.europa.eu/qr/595728
	FA: 265/35 R 21 101 H XL	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/482746

Manufacturer's Certificate

Taycan (Y1A)

21/24 ENU 4400

4

Model	Tire size	Tire make and type / Label value (link to EU database)
	RA: 305/30 R 21 104 H XL	RA: https://eprel.ec.europa.eu/qr/481299
		Goodyear Eagle Touring NF1 FA: https://eprel.ec.europa.eu/qr/1621908 RA: https://eprel.ec.europa.eu/qr/1585163

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Turismo: Standard / 4S / GTS / Turbo / Turbo S	FA: 225/55 R 19 103H XL RA: 275/45 R 19 108H XL	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/483273 RA: https://eprel.ec.europa.eu/qr/482743
	Not for GTS.	Goodyear Eagle Touring NFO FA: https://eprel.ec.europa.eu/qr/529945 RA: https://eprel.ec.europa.eu/qr/529946
	Not for Turbo and Turbo S.	
	*)	
	FA: 245/45 R 20 103H XL RA: 285/40 R 20 108H XL	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/483338 RA: https://eprel.ec.europa.eu/qr/481297
	Not for Turbo S vehicles.	Pirelli CintuRato P7 A/S NFO FA: https://eprel.ec.europa.eu/qr/595727 RA: https://eprel.ec.europa.eu/qr/595728
	FA: 265/35 R 21 101 H XL RA: 305/30 R 21 104 H XL	Continental ProContact RX NFO FA: https://eprel.ec.europa.eu/qr/482746 RA: https://eprel.ec.europa.eu/qr/481299
		Goodyear Eagle Touring NF1 FA: https://eprel.ec.europa.eu/qr/1621908 RA: https://eprel.ec.europa.eu/qr/1585163

Winter tires:

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Sedan: Standard / Standard 4 / 4S	FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL	Continental TS 860 S NFO FA: https://eprel.ec.europa.eu/qr/479702 RA: https://eprel.ec.europa.eu/qr/620844
	*)	Pirelli P-Zero Winter NFO FA: https://eprel.ec.europa.eu/qr/595723 RA: https://eprel.ec.europa.eu/qr/595724
	FA: 245/45 R 20 103V XL	Goodyear UltraGrip Performance Gen1 NFO FA: https://eprel.ec.europa.eu/qr/529947

Model	Tire size	Tire make and type / Label value (link to EU database)
	RA: 285/40 R 20 108V XL	RA: https://eprel.ec.europa.eu/qr/529948
		Pirelli P-Zero Winter NFO FA: https://eprel.ec.europa.eu/qr/595729 RA: https://eprel.ec.europa.eu/qr/595730
	FA: 265/35 R 21 103V RA: 305/30 R 21 107V	Continental WinterContact TS 860 S NDO FA: https://eprel.ec.europa.eu/qr/1838265 RA: https://eprel.ec.europa.eu/qr/1838260

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Sedan: GTS / Turbo / Turbo S / Turbo GT (Black Edition / Silver Edition)	FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	Goodyear UltraGrip Performance Gen1 NFO FA: https://eprel.ec.europa.eu/qr/529947 RA: https://eprel.ec.europa.eu/qr/529948
		Pirelli P-Zero Winter NFO FA: https://eprel.ec.europa.eu/qr/595729 RA: https://eprel.ec.europa.eu/qr/595730
	FA: 265/35 R 21 103V RA: 305/30 R 21 107V	Continental WinterContact TS 860 S NDO FA: https://eprel.ec.europa.eu/qr/1838265 RA: https://eprel.ec.europa.eu/qr/1838260

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Cross Turismo: Standard / 4S / Turbo / Turbo S	FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL Not for Turbo and Turbo S. *)	Continental TS 860 S NFO FA: https://eprel.ec.europa.eu/qr/479702 RA: https://eprel.ec.europa.eu/qr/620844
		Pirelli P-Zero Winter NFO FA: https://eprel.ec.europa.eu/qr/595723 RA: https://eprel.ec.europa.eu/qr/595724
	FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	Goodyear UltraGrip Performance Gen1 NFO FA: https://eprel.ec.europa.eu/qr/529947 RA: https://eprel.ec.europa.eu/qr/529948
		Pirelli P-Zero Winter NFO FA: https://eprel.ec.europa.eu/qr/595729 RA: https://eprel.ec.europa.eu/qr/595730
	FA: 265/35 R 21 103V RA: 305/30 R 21 107V	Continental WinterContact TS 860 S NDO FA: https://eprel.ec.europa.eu/qr/1838265 RA: https://eprel.ec.europa.eu/qr/1838260

Model	Tire size	Tire make and type / Label value (link to EU database)
Taycan Sport Turismo: Standard / 4S / GTS / Turbo / Turbo S	FA: 225/55 R 19 103V XL RA: 275/45 R 19 108V XL	Continental TS 860 S NFO FA: https://eprel.ec.europa.eu/qr/479702 RA: https://eprel.ec.europa.eu/qr/620844
	Not for GTS.	Pirelli P-Zero Winter NFO FA: https://eprel.ec.europa.eu/qr/595723 RA: https://eprel.ec.europa.eu/qr/595724
	Not for Turbo and Turbo S. *)	Goodyear UltraGrip Performance Gen1 NFO FA: https://eprel.ec.europa.eu/qr/529947 RA: https://eprel.ec.europa.eu/qr/529948
	FA: 245/45 R 20 103V XL RA: 285/40 R 20 108V XL	Pirelli P-Zero Winter NFO FA: https://eprel.ec.europa.eu/qr/595729 RA: https://eprel.ec.europa.eu/qr/595730
	FA: 265/35 R 21 103V RA: 305/30 R 21 107V	Continental WinterContact TS 860 S NDO FA: https://eprel.ec.europa.eu/qr/1838265 RA: https://eprel.ec.europa.eu/qr/1838260

Arrow with inscription "Rotation"

= Directional mounting

"Inside/Outside" inscription

= Mounting on specified side only

Arrow with both inscriptions "Rotation" and "Inside/Outside"

= Directional mounting on specified side only.



Information

In principle, only tires that at least correspond to the maximum vehicle speed may be installed on the vehicle.

There may be national exemptions for winter tires marked for M+S and 3PMSF (3 peak mountain snow flake), which also permit tires that do not correspond to the maximum vehicle speed.



Information

"N..." = Specification code of the tire, e.g. "NFO", "NF1", "NF2" ... The complete "N ..." code of the relevant tire makes must be shown on the tire sidewall near the type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.

**Information**

As a general rule, Porsche does not recommend having tires repaired. Local legislation must always be observed.

It is advisable to install winter tires for temperatures below 7 °C (44 °F), because the driving characteristics of summer tires and UHP tires are reduced at low temperatures. Subfreezing temperatures can cause permanent damage to summer tires and UHP tires.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire by more than 30%. If this value is exceeded, we recommend that you replace both tires.

**WARNING****Incorrect tire pressure**

- **Uncontrollable vehicle handling**
- ⇒ **Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.**
- ⇒ **Check age of tires. Recommendation: Replace tires that are more than 6 years old.**
- ⇒ **Perform visual inspections.**
- ⇒ **Use only tires approved by Porsche.**

**WARNING****Driving with different tires (mixed tires)**

- **Uncontrollable vehicle handling**
- ⇒ **Only use tires of the same make and type, with the same speed index and the same specification code (NF0, NF1, NF2, etc.) on a vehicle.**

**Information**

The tire pressure applies only to the tire makes and types approved by Porsche and is specified for cold tires (approx. 20 °C/ 68 °F). The tire pressure must not be lower than the specified values.

Standard tire pressure for summer tires + UHP, 4/5 seats

Standard tire pressure for summer tires + UHP, 4/5 seats

Wheel size	Taycan Standard 2wd (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.4 bar 35 psi	-	2.4 bar 35 psi	-
	-	2.3 bar 33 psi	-	2.6 bar 37 psi
20-inch wheels	2.4 bar 35 psi	-	2.4 bar 35 psi	-
	-	2.3 bar 33 psi	-	2.6 bar 37 psi
21-inch narrow wheels	2.6 bar 37 psi	-	2.6 bar 37 psi	-
	-	2.5 bar 36 psi	-	2.8 bar 41 psi
21-inch wheels	2.3 bar 33 psi	-	2.5 bar 36 psi	-
	-	2.5 bar 36 psi	-	3.0 bar 44 psi

Wheel size	Taycan Standard 4wd (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
20-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch narrow wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	2.9 bar 42 psi
21-inch wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi

Wheel size	Taycan S			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
20-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.8 bar 41 psi
21-inch narrow wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.8 bar 41 psi	-	3.0 bar 44 psi
21-inch wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi

Wheel size	Taycan GTS			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.8 bar 41 psi
21-inch narrow wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi
21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.8 bar 41 psi
21-inch narrow wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.8 bar 41 psi	-	3.0 bar 44 psi
21-inch wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo S (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
21-inch narrow wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.8 bar 41 psi	-	3.0 bar 44 psi
21-inch wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan Standard (Cross Turismo), 4S (Cross Turismo), 4S (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi

20-inch wheels	2.6 bar 37 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch narrow wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi
21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo (Cross Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.8 bar 41 psi
21-inch narrow wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.8 bar 41 psi	-	3.0 bar 44 psi
21-inch wheels	2.6 bar 37 psi	-	2.7 bar 39 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo S (Cross Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.6 bar 37 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi

21-inch narrow wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi
21-inch wheels	2.6 bar 37 psi	-	2.7 bar 39 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan Sport Turismo			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.6 bar 37 psi	-	2.6 bar 37 psi	-
	-	2.3 bar 33 psi	-	2.6 bar 37 psi
20-inch wheels	2.6 bar 37 psi	-	2.6 bar 37 psi	-
	-	2.3 bar 33 psi	-	2.6 bar 37 psi
21-inch narrow wheels	2.5 bar 36 psi	-	2.5 bar 36 psi	-
	-	2.5 bar 36 psi	-	2.9 bar 42 psi
21-inch wheels	2.4 bar 35 psi	-	2.5 bar 36 psi	-
	-	2.6 bar 37 psi	-	3.0 bar 44 psi

Wheel size	Taycan GTS (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.8 bar 41 psi

21-inch narrow wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi
21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.8 bar 41 psi
21-inch narrow wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi
21-inch wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.8 bar 41 psi	-	3.2 bar 46 psi

Wheel size	Taycan Turbo S (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
21-inch narrow wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi
21-inch wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.8 bar 41 psi	-	3.2 bar 46 psi

Wheel size	Taycan Turbo GT (Silver Edition)			
	Part load		Full load	
	FA	RA	FA	RA
21-inch Performance/Track	3.3 bar 48 psi	-	3.5 bar 51 psi	-
	-	3.3 bar 48 psi	-	3.5 bar 51 psi

Wheel size	Taycan Turbo GT (Black Edition)			
	Part load		Full load	
	FA	RA	FA	RA
21-inch Performance/Track	3.1 bar 45 psi	-	3.3 bar 48 psi	-
	-	3.2 bar 46 psi	-	3.5 bar 51 psi

Standard tire pressure for all-season tires, 4/5 seats

Wheel size	Taycan Standard 2wd (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.3 bar 33 psi	-	2.5 bar 36 psi	-
	-	2.3 bar 33 psi	-	2.7 bar 39 psi
20-inch wheels	2.3 bar 33 psi	-	2.5 bar 36 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch wheels	2.5 bar 36 psi	-	2.6 bar 37 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Standard 4wd (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.5 bar 36 psi	–	2.7 bar 39 psi	–
	–	2.3 bar 33 psi	–	2.7 bar 39 psi
20-inch wheels	2.5 bar 36 psi	–	2.7 bar 39 psi	–
	–	2.3 bar 33 psi	–	2.7 bar 39 psi
21-inch wheels	2.7 bar 39 psi	–	2.8 bar 41 psi	–
	–	2.7 bar 39 psi	–	3.0 bar 44 psi

Wheel size	Taycan S			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.5 bar 36 psi	–	2.7 bar 39 psi	–
	–	2.3 bar 33 psi	–	2.7 bar 39 psi
20-inch wheels	2.5 bar 36 psi	–	2.7 bar 39 psi	–
	–	2.3 bar 33 psi	–	2.7 bar 39 psi
21-inch wheels	2.7 bar 39 psi	–	2.8 bar 41 psi	–
	–	2.7 bar 39 psi	–	3.0 bar 44 psi

Wheel size	Taycan GTS			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.4 bar 35 psi	–	2.6 bar 37 psi	–
	–	2.4 bar 35 psi	–	2.7 bar 39 psi

21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.5 bar 36 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo S (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
21-inch wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Standard (Cross Turismo), 4S (Cross Turismo), 4S (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
20-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi

21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo (Cross Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch wheels	2.6 bar 37 psi	-	2.7 bar 39 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo S (Cross Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch wheels	2.6 bar 37 psi	-	2.7 bar 39 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan Sport Turismo			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi

20-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan GTS (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.4 bar 35 psi	-	2.6 bar 37 psi	-
	-	2.4 bar 35 psi	-	2.7 bar 39 psi
21-inch wheels	2.6 bar 37 psi	-	2.7 bar 39 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Wheel size	Taycan Turbo S (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA

21-inch wheels	2.6 bar 37 psi	-	2.7 bar 39 psi	-
	-	2.8 bar 41 psi	-	3.1 bar 45 psi

Standard tire pressure for winter tires, 4/5 seats

Wheel size	Taycan Standard 2wd (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.5 bar 36 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.9 bar 42 psi
20-inch wheels	2.5 bar 36 psi	-	2.7 bar 39 psi	-
	-	2.5 bar 36 psi	-	2.9 bar 42 psi
21-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.8 bar 41 psi	-	3.2 bar 46 psi

Wheel size	Taycan Standard 4wd (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.6 bar 37 psi	-	3.0 bar 44 psi
20-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.6 bar 37 psi	-	3.0 bar 44 psi
21-inch wheels	2.8 bar 41 psi	-	3.1 bar 45 psi	-
	-	2.8 bar 41 psi	-	3.2 bar 46 psi

Wheel size	Taycan S			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.6 bar 37 psi	-	3.0 bar 44 psi
20-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.6 bar 37 psi	-	3.0 bar 44 psi
21-inch wheels	2.8 bar 41 psi	-	3.1 bar 45 psi	-
	-	2.8 bar 41 psi	-	3.2 bar 46 psi

Wheel size	Taycan GTS			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.6 bar 37 psi	-	3.0 bar 44 psi
21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.2 bar 46 psi

Wheel size	Taycan Turbo (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi

21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.2 bar 46 psi

Wheel size	Taycan Turbo S (Sedan)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi
21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.2 bar 46 psi

Wheel size	Taycan Standard (Cross Turismo), 4S (Cross Turismo), 4S (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi
20-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi
21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.3 bar 48 psi

Wheel size	Taycan Turbo (Cross Turismo)			
	Part load		Full load	
	FA	RA	FA	RA

20-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi
21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.3 bar 48 psi

Wheel size	Taycan Turbo S (Cross Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi
21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.3 bar 48 psi

Wheel size	Taycan Sport Turismo			
	Part load		Full load	
	FA	RA	FA	RA
19-inch wheels	2.5 bar 36 psi	-	2.7 bar 39 psi	-
	-	2.6 bar 37 psi	-	2.9 bar 42 psi
20-inch wheels	2.5 bar 36 psi	-	2.7 bar 39 psi	-
	-	2.6 bar 37 psi	-	2.9 bar 42 psi
21-inch wheels	2.6 bar 37 psi	-	2.7 bar 39 psi	-
	-	2.9 bar 42 psi	-	3.2 bar 46 psi

Wheel size	Taycan GTS (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.0 bar 44 psi
21-inch narrow wheels	2.5 bar 36 psi	-	2.5 bar 36 psi	-
	-	2.5 bar 36 psi	-	2.9 bar 42 psi
21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.2 bar 46 psi

Wheel size	Taycan Turbo (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi
21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.3 bar 48 psi

Wheel size	Taycan Turbo S (Sport Turismo)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	3.1 bar 45 psi

Manufacturer's Certificate

Taycan (Y1A)

21/24 ENU 4400

4

21-inch wheels	2.8 bar 41 psi	-	3.0 bar 44 psi	-
	-	2.9 bar 42 psi	-	3.3 bar 48 psi

Wheel size	Taycan Turbo GT (Silver Edition)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.6 bar 37 psi	-	2.8 bar 41 psi	-
	-	2.4 bar 35 psi	-	2.6 bar 37 psi
21-inch wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.7 bar 39 psi	-	2.9 bar 42 psi

Wheel size	Taycan Turbo GT (Black Edition)			
	Part load		Full load	
	FA	RA	FA	RA
20-inch wheels	2.7 bar 39 psi	-	2.8 bar 41 psi	-
	-	2.6 bar 37 psi	-	2.8 bar 41 psi
21-inch wheels	2.8 bar 41 psi	-	2.9 bar 42 psi	-
	-	2.9 bar 42 psi	-	3.0 bar 44 psi

The permitted speed threshold for Comfort tire pressure depends on the vehicle's country equipment and cannot be selected.

Comfort tire pressure for summer tires up to 270 km/h (168 mph)

Wheel size	Taycan Turbo GT (Silver Edition, Black Edition)	
	FA	RA
21-inch Performance/Track	2.6 bar 37 psi	-
	-	2.6 bar 37 psi

⚠ WARNING**Incorrectly installed snow chains**

- **Uncontrollable vehicle handling**
- ⇒ **Do not exceed top speed of 50 km/h (30 mph).**
- ⇒ **Read assembly instructions (see also TEQUIPMENT accessory finder on the Internet).**
- ⇒ **Observe country-specific regulations.**

Snow Chains Porsche offers the following snow chains as accessories:

Tire size	Porsche Part No.	Type of snow chain
275/45 R 19 M+S	9J1.073.690.A	Quick fit
285/40 R 20 M+S	9J1.073.690.A	Quick fit

- Wheel Storage:
- Tires must be stored in a cool, dry and dark room with adequate ventilation.
 - Tires must never come into contact with fuel, oil, grease or chemicals.
 - Do not store summer tires in storage areas with ambient temperatures of less than 5° F (-15° C).
 - Complete wheel & tire assemblies can be stacked for storage; we recommend that you increase the tire pressure by approximately 6 psi (0.4 bar).
 - Optimum conditions for storage of the complete wheels are provided by the Original Porsche storage trolley, Part No. 000.044.000.38.
 - If the tires are not mounted on wheels, it is best to store them in a vertical position.
 - We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots.
 - Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.

- General Information:
- Always use new valves when changing tires.
 - Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on.
 - Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily.
 - In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.
 - In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

Matching (uncontrolled and controlled) is explained below: Uncontrolled matching:

- Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

Controlled matching:

- With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching.
- Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm -ideally approx. 0.5 mm - are desirable.
- The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

New Tires (Replacements):

- If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, type and with the same specification code must always be used on each of the two axles.
- If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling.
- This is especially the case if new tires are mounted on the rear axle.
- This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire on the same axle by more than 30 %.

Refer to WM 449503 for specific details of the vehicle you are working on.

- >The 2mm specification will be given here.
- > If there is none listed then the default is 30%.

Repairs to Tires:

- If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.
- Repairs to "V", "W", "Y", and "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires.

Tire Aging:

- Tires age due to chemical and physical processes, which can impair their function.
- Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use.
- Hairline aging cracks can occur on older tires.

- On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.
- Therefore, attention should be paid not only to the tread depth but also to the age of the tire.
- Tires should not be older than 6 years.
- The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201 = 22nd week of 2001.

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2024 Porsche Cars North America, Inc.