

Manufacturer's Certificate

982

34/24 ENU 4400

4

Approved: Wheels and Tires (34/24)

Revision: This bulletin replaces bulletin Group 4 31/23, dated November 17, 2023.

Model Year: **As of 2017**

Vehicle Type: **982:**

718 Boxster, 718 Boxster S, 718 Boxster GTS, 718 Boxster GTS 4.0, 718 Boxster T, 718 Boxster 25 Years, 718 Boxster Style Edition,

718 Cayman, 718 Cayman S, 718 Cayman GTS, 718 Cayman GTS 4.0, 718 Cayman T, 718 Cayman Style Edition

Cause: Approval status: July 2024

Sizes: **Permissible tire and wheel sizes**
(RO = rim offset in mm, FA = front axle, RA = rear axle)

Tires	Tire sizes	Wheel sizes	Snow chains
718 Boxster, 718 Boxster S, 718 Boxster Style Edition, 718 Cayman, 718 Cayman S, 718 Cayman Style Edition			
Summer	FA: 235/45 ZR18 94Y RA: 265/45 ZR18 101Y basic models only	FA: 8.0J x 18, RO 57 RA: 9.5J x 18, RO 49	No
	FA: 235/40 ZR19 (92Y) RA: 265/40 ZR19 (98Y) not for Style Edition	FA: 8.0J x 19, RO 57 RA: 10J x 19, RO 45	No
	FA: 235/35 ZR20 (88Y) RA: 265/35 ZR20 (95Y)	FA: 8J x 20, RO 57 RA: 10J x 20, RO 45	No
	FA: 235/35 ZR20 (92Y) RA: 265/35 ZR20 (99Y)	FA: 8.5J x 20, RO 57 RA: 10.5J x 20, RO 47	No
Winter	FA: 235/45 R18 94VM+S RA: 265/45 R18 101VM+S	FA: 8.0J x 18, RO 57 RA: 9.5J x 18, RO 49	RA only
	FA: 235/40 R19 92VM+S RA: 265/40 R19 98VM+S	FA: 8.0J x 19, RO 57 RA: 10J x 19, RO 45	No

Tires	Tire sizes	Wheel sizes	Snow chains
718 Boxster GTS, 718 Boxster GTS 4.0, 718 Boxster T, 718 Cayman GTS, 718 Cayman GTS 4.0, 718 Cayman T, 718 Boxster 25 years			
Summer	FA: 235/35 ZR20 (88Y) RA: 265/35 ZR20 (95Y)	FA: 8J x 20, RO 57 RA: 10J x 20, RO 45 not for 25-year model	No
	FA: 235/35 ZR20 (92Y) RA: 265/35 ZR20 (99Y)	FA: 8.5J x 20, RO 57 RA: 10.5J x 20, RO 47	No
Winter	FA: 235/45 R18 94VM+S RA: 265/45 R18 101VM+S	FA: 8.0J x 18, RO 57 RA: 9.5J x 18, RO 49	RA only
	FA: 235/40 R19 92VM+S RA: 265/40 R19 98VM+S	FA: 8.0J x 19, RO 57 RA: 10J x 19, RO 45	No

Wheels:

Overview of Porsche wheels for summer and winter tires

Identification on the inside of the wheel:

Wheel size, rim offset (RO) in mm, part number (without color code marking FFF) and Porsche logo

18-inch "Boxster 4" wheel

FA: 8J x 18, RO 57

Part No. 982.601.025.M_FFF

RA: 9.5J x 18, RO 49

Part No. 982.601.025.AL_FFF



18-inch Boxster 4

18-inch "Cayman 3" wheel

FA: 8J x 18, RO 57

Part No. 982.601.025.P_FFF

RA: 9.5J x 18, RO 49

Part No. 982.601.025.Q_FFF

Not for 718 Cayman GTS 4.0



18-inch Cayman 3

19-inch wheel "Boxster S 4"

FA: 8J x 19, RO 57

Part No. 982.601.025_FFF

RA: 10J x 19, RO 45

Part No. 982.601.025.AM_FFF

*19-inch Boxster S 4***19-inch wheel "Cayman S 4"**

FA: 8J x 19, RO 57

Part No. 982.601.025.B_FFF

RA: 10J x 19, RO 45

Part No. 982.601.025.C_FFF

*19-inch Cayman S 4***20-inch wheel "Carrera S 4"**

FA: 8J x 20, RO 57

Part No. 982.601.025.AJ_FFF /

982.601.029.AD_FFF

RA: 10J x 20, RO 45

Part No. 982.601.025.AK_FFF /

982.601.029.AE_FFF

not for Style Edition**not for 25-year model***20-inch Carrera S 4*

20-inch "Carrera Classic II" wheel

FA: 8J x 20, RO 57
Part No. 981.362.160.14_FFF

RA: 10J x 20, RO 45
Part No. 982.601.025.S_FFF

Not for 718 Cayman GTS 4.0

not for Style Edition

not for 25-year model



20-inch Carrera Classic II

20-inch wheel "Carrera Sport"

FA: 8.5J x 20, RO 57
Part No. 982.601.025.K_FFF /
982.601.029.AF_FFF /
982.601.025.BG_FFF

RA: 10.5J x 20, RO 47
Part No. 982.601.025.AG_FFF /
982.601.029.AG_FFF /
982.601.025.BH_FFF



20-inch Carrera Sport

20-inch wheel "911 Turbo 4"

FA: 8.5J x 20, RO 57

Part No. 982.601.025.F_FFF

RA: 10.5J x 20, RO 47

Part No. 982.601.025.AF_FFF

*20-inch 911 Turbo 4***20-inch wheel "982 GTS"**

FA: 8.5J x 20, RO 57

Part No. 982.601.025.T_FFF /

982.601.025.AS_FFF

RA: 10.5J x 20, RO 47

Part No. 982.601.025.AH_FFF /

982.601.025.AT_FFF

*20-inch 982 GTS*

20-inch wheel "982 25 years"

FA: 8.5J x 20, RO 57
Part No. 982.601.025.AD_FFF/
982.601.025.AQ_FFF

RA: 10.5J x 20, RO 47
Part No. 982.601.025.AE_FFF /
982.601.025.AR_FFF



20-inch 982 25 years

20-inch wheel "Edition"

FA: 8.5J x 20, RO 57
Part No. 982.601.025.AN_FFF

RA: 10.5J x 20, RO 47
Part No. 982.601.025.AP_FFF



20-inch Edition



Information

Improper handling can damage the wheel surface.
Carry out tire removal and mounting using a bead holding-down device only.
Use a leather pad on the rim flange to support the valve insertion tool.
Only use the Porsche centring clamping set for balancing.
Do not use hard brushes to clean the wheels as these can cause deep scratches that cannot be removed by polishing.
Never use solvents or other chemical substances not approved by Porsche on tires.



Information

Only install wheels with identical part numbers on each axle.

Wheel **Tightening torque 160 Nm**
Mounting:

**WARNING****Driving with different tires (mixed tires)**

- **Uncontrollable vehicle handling**

⇒ **Only use tires of the same make and type, with the same speed index and the same specification code (NO, N1, N2, ...) on a vehicle.**

Summer Tires:

Model	Tire size	Tire make and type / Label value (link to EU database)
718 Boxster, 718 Boxster S, 718 Boxster Style Edition, 718 Cayman, 718 Cayman S, 718 Cayman Style Edition	FA: 235/45 ZR18 94Y RA: 265/45 ZR18 101Y basic models only,	Pirelli PZero N1 (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/595052 RA: https://eprel.ec.europa.eu/qr/595051
		Goodyear Eagle F1 Asymmetric 2 NO (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/531122 RA: https://eprel.ec.europa.eu/qr/531117
	FA: 235/40 ZR19 (92Y) RA: 265/40 ZR19 (98Y) not for Style Edition	Pirelli PZero N1 (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/595050 RA: https://eprel.ec.europa.eu/qr/595049
		Yokohama Advan Sport V105 NO (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/578237 RA: https://eprel.ec.europa.eu/qr/578239
		Hankook veNtus S1 evo3 NO (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/542669 RA: https://eprel.ec.europa.eu/qr/542670
	FA: 235/35 ZR20 (88Y)	Pirelli PZero N1 (Inside/Outside)

Model	Tire size	Tire make and type / Label value (link to EU database)
	RA: 265/35 ZR20 (95Y)	FA: https://eprel.ec.europa.eu/qr/595048 RA: https://eprel.ec.europa.eu/qr/595047
	FA: 235/35 ZR20 (92Y) RA: 265/35 ZR20 (99Y)	Michelin Pilot Sport 4 S NO (Inside/Outside) Style Edition: not for Japan FA: https://eprel.ec.europa.eu/qr/410928 RA: https://eprel.ec.europa.eu/qr/410518

Model	Tire size	Tire make and type / Label value (link to EU database)
718 Boxster GTS, 718 Boxster GTS 4.0, 718 Boxster T, 718 Cayman GTS, 718 Cayman GTS 4.0, 718 Cayman T, 718 Boxster 25 years	FA: 235/35 ZR20 (88Y) RA: 265/35 ZR20 (95Y)	Pirelli PZero N1 (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/595048 RA: https://eprel.ec.europa.eu/qr/595047
	FA: 235/35 ZR20 (92Y) RA: 265/35 ZR20 (99Y)	Michelin Pilot Sport 4 S NO (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/410928 RA: https://eprel.ec.europa.eu/qr/410518

Winter Tires:

Model	Tire size	Tire make and type / Label value (link to EU database)
718 Boxster, 718 Boxster S, 718 Boxster GTS, 718 Boxster GTS 4.0, 718 Boxster T, 718 Boxster 25 Years, 718 Boxster Style Edition, 718 Cayman, 718 Cayman S, 718	FA: 235/45 R18 94V M+S RA: 265/45 R18 101V M+S	Pirelli Winter 240 Sottozero Serie II NO (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/594296 RA: https://eprel.ec.europa.eu/qr/594298
	FA: 235/40 R19 92V M+S RA: 265/40 R19 98V M+S	Continental ContiWinterContact TS830P NO (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/506096 RA: https://eprel.ec.europa.eu/qr/506089
		Michelin Pilot Alpin PA4 NO

Model	Tire size	Tire make and type / Label value (link to EU database)
Cayman GTS, 718 Cayman GTS 4.0, 718 Cayman T, 718 Cayman Style Edition		(Rotation) FA: https://eprel.ec.europa.eu/qr/409286 RA: https://eprel.ec.europa.eu/qr/409268
		Pirelli P Zero Winter N1 (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/595901 RA: https://eprel.ec.europa.eu/qr/595902

Arrow with inscription "Rotation"

= Directional mounting

inscription "Inside/Outside" or "Left" or "Right"

= Mounting on specified side only

Arrow with both inscriptions "Rotation" and
"Inside/Outside"

= directional mounting on specified side only.

Arrow with inscriptions "Rotation" and "Left" or
"Right"

= directional mounting on specified side only.



Information

In principle, only tires that at least correspond to the maximum vehicle speed may be installed on the vehicle.

There may be national exemptions for winter tires marked for M+S and 3PMSF (3 peak mountain snow flake), which also permit tires that do not correspond to the maximum vehicle speed.



Information

"N..." = Specification code of the tire, e.g. "N0", "N1", "N2" ... The complete "N ..." code of the tires in question must be shown on the tire sidewall near the tire type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.



Information

As a general rule, Porsche does not recommend having tires repaired. Local legislation must always be observed.

It is advisable to install winter tires for temperatures below 7 °C (44 °F), because the driving characteristics of summer tires and UHP tires are reduced at low temperatures. Subfreezing temperatures can cause permanent damage to summer tires and UHP tires.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire by more than 30%. If this value is exceeded, we recommend that you replace both tires.

Tire Pressure:



WARNING

Incorrect tire pressure

- **Uncontrollable vehicle handling**
- ⇒ **Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.**
- ⇒ **Check age of tires. Recommendation: Replace tires that are more than 6 years old.**
- ⇒ **Perform visual inspections.**
- ⇒ **Use only tires approved by Porsche.**



Information

The tire pressure applies only to the tire makes and types approved by Porsche and is specified for cold tires (approx. 20 °C/ 68 °F). The tire pressure must not be lower than the specified values.

Standard tire pressure for summer tires

Wheel size	718 Boxster, 718 Boxster S, 718 Boxster T, 718 Boxster GTS, 718 Boxster Style Edition, 718 Cayman, 718 Cayman S, 718 Cayman T, 718 Cayman GTS, 718 Cayman Style Edition.	
	Full load	
	FA	RA
18-inch wheels	2.0 bar 29 psi	2.0 bar 29 psi

19-inch wheels	2.0 bar 29 psi	2.1 bar 30 psi
20-inch wheels	2.3 bar 33 psi	2.3 bar 33 psi

Wheel size	718 Boxster GTS 4.0, 718 Cayman GTS 4.0	
	Full load	
	FA	RA
20-inch wheels	2.4 bar 35 psi	2.4 bar 35 psi

Standard tire pressure for winter tires

Wheel size	718 Boxster, 718 Boxster S, 718 Boxster GTS, 718 Boxster GTS 4.0 718 Boxster T, 718 Boxster 25 Years, 718 Boxster Style Edition, 718 Cayman, 718 Cayman S, 718 Cayman GTS, 718 Cayman GTS 4.0, 718 Cayman T, 718 Cayman Style Edition.	
	Full load	
	FA	RA
18-inch wheels	2.2 bar 31 psi	2.2 bar 31 psi
19-inch wheels	2.2 bar 31 psi	2.2 bar 31 psi

Comfort tire pressure for summer tires up to 270 km/h (165 mph) – only for vehicles with Tire Pressure Monitoring (TPM) and “Comfort pressure” menu in the multi-function display (depending on the country)



WARNING

Driving at high speed with low tire pressure

- Irreparable damage to tires
- ⇒ Set comfort and performance air pressure for tires only on vehicles with “Comfort pressure” and “Performance pressure” selected in the instrument cluster.

Wheel size	718 Boxster, 718 Boxster S, 718 Boxster GTS, 718 Boxster GTS 4.0, 718 Boxster T, 718 Boxster 25 Years, 718 Boxster Style Edition, 718 Cayman, 718 Cayman S, 718 Cayman GTS, 718 Cayman GTS 4.0 MT, 718 Cayman T, 718 Cayman Style Edition.	
	FA	RA
20-inch wheels	2.1 bar 30 psi	2.1 bar 30 psi

Wheel size	718 Cayman GTS 4.0 PDK	
	FA	RA
20-inch wheels	2.2 bar 32 psi	2.2 bar 32 psi

Snow Chains:



Incorrectly installed snow chains

- Uncontrollable vehicle handling
- ⇒ Do not exceed top speed of 50 km/h (30 mph).
- ⇒ Read assembly instructions (see also **TEQUIPMENT** accessory finder on the Internet).
- ⇒ Observe country-specific regulations.

Porsche offers the following snow chains as accessories:

Tire size	Porsche Part No.	Type of snow chain
265/45 R 18 M+S	982.044.600.00	Link-type chain, quick fit

- Wheel Storage:
- Tires must be stored in a cool, dry and dark room with adequate ventilation.
 - Tires must never come into contact with fuel, oil, grease or chemicals.
 - Do not store summer tires in storage areas with ambient temperatures of less than 5° F (-15° C).
 - Complete wheel & tire assemblies can be stacked for storage; we recommend that you increase the tire pressure by approximately 6 psi (0.4 bar).
 - Optimum conditions for storage of the complete wheels are provided by the Original Porsche storage trolley, Part No. 000.044.000.38.
 - If the tires are not mounted on wheels, it is best to store them in a vertical position.
 - We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots.

General
Information:

- Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.
- Always use new valves when changing tires.
- Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on.
- Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily.
- In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.
- In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

Matching (uncontrolled and controlled) is explained below: Uncontrolled matching:

- Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

Controlled matching:

- With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching.
- Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm - ideally approx. 0.5 mm - are desirable.
- The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

New Tires (Replacements):

- If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, type and with the same specification code must always be used on each of the two axles.
- If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling.
- This is especially the case if new tires are mounted on the rear axle.
- This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire on the same axle by more than 30 %.

Refer to WM 449503 for specific details of the vehicle you are working on.

- >The 2mm specification will be given here.
- > If there is none listed then the default is 30%.

Repairs to Tires:

- If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.
- Repairs to "V", "W", "Y", and "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires.

Tire Aging:

- Tires age due to chemical and physical processes, which can impair their function.
- Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use.
- Hairline aging cracks can occur on older tires.
- On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.
- Therefore, attention should be paid not only to the tread depth but also to the age of the tire.
- Tires should not be older than 6 years.
- The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201 = 22nd week of 2001.

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2024 Porsche Cars North America, Inc.