



Service Information

Offboard Diagnostic Information System Service (ODIS Service) Number: VOS-25-12

Subject: TSB 27-24-01 – 12V Battery is Drained Hotfix Instructions Date: Jan. 27, 2025

Important:

We recommend installation of this hotfix on one diagnostic device ONLY. Hotfix must be removed immediately after performing the procedure.

1.0 – Introduction

The hotfix is for **all VW models for 2024 and 2025.**

This is for: TSB 27-24-01 – 12V Battery is Drained, Battery Check Procedure and Required Documents before Replacement.

Test program 2072849 - A_X_1_0720_11_Batteriepruefung_TPI_00000 -

!! The Hotfix must be removed after performing the diagnostic procedure. !!

2.0 – Prerequisite

ODIS Service **latest Diagnostic Content version** must be installed.


To confirm the installed diagnostic content version in ODIS Service, go to:


Info >  Versions>Diagnostic data; didb_GFS-v.en_US: xxxxxxxx **X.XX.XX**




Service Information

3.0 – Download Hotfix

1. Open a **Web Browser** on the diagnostic device and logon to **vwhub.com**
2. Navigate to **Elsa2Go>Service References>Software/Hardware Updates**
3. Search for the **12V Battery is Drained Hotfix Zip File**
4. Click the **12V Battery is Drained Hotfix Zip File**  and **save** it to your Windows desktop.
5. Close your browser.
6. Browse to the desktop and double-click the **12V Battery is Drained Hotfix Zip File** to open it.
7. Right click the file (example only) name and select **Copy**:



8. Right click anywhere on the Windows desktop and select **Paste**. This file icon (example) must appear on the desktop:




(continued)




Service Information

4.0 – Install Hotfix into ODIS Service

1. Open ODIS Service (“Run as Administrator”)
2. Expand the **Data** submenu and click **Download** (under **Hotfix**):



3. Click **Continue**:




(continued)




Service Information

- The Directory selection window will appear. Browse to and **highlight the Hotfix file** (*example only*), then click **Select Folder**:



- Click **OK**:



- Perform the diagnostic procedure.

Important:

The Hotfix must be removed after performing the procedure. Failure to do so will cause other vehicle diagnostics sessions to malfunction.


(continued)




Service Information

5.0 – Uninstall the Hotfix from ODIS Service

1. Select **Erase** (under Hotfix), then **Continue**:



2. Click **OK** and close ODIS Service:



Please contact Diagnostic Tester Software Support by phone at 888-896-1298 or email softwaresupport@vw.com with any questions or concerns.