



Technical Service Bulletin

SUBJECT:				No: TSB-25-00-009	
TECHNICAL SPECIFICATIONS - 2025 OUTLANDER				DATE: February 2025	
				MODEL: 2025 Outlander	
CIRCULATE TO:		<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER		<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR		<input checked="" type="checkbox"/> SERVICE MANAGER		<input checked="" type="checkbox"/> WARRANTY PROCESSOR	
		<input checked="" type="checkbox"/> SALES MANAGER			

Feature Description	ES 2WD	ES S-AWC	SE 2WD	SE S-AWC	SEL 2WD	SEL S-AWC	SEL Prem 2WD	SEL Prem S-AWC	Platinum Edition S-AWC
	GM4WXTMCL2M	GM4WXTMCZL2M	GM4WXTXCL2M	GM4WXTXCZL2M	GM4WXTUCL2M	GM4WXTUCZL2M	GM4WXTUCL2M	GM4WXTUCZL2M	GM4WXTUCZL2M
Model Code	3	13	4	14	6	16	6	16	16
Engine									
Type	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection	2.5L MIVEC DOHC 4-cylinder Direct-Injection
Engine Code	PR25DD	PR25DD	PR25DD	PR25DD	PR25DD	PR25DD	PR25DD	PR25DD	PR25DD
Materials	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads	Aluminum block/aluminum cylinder heads
Bore x Stroke	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm	89.0 mm x 100.0 mm
Compression Ratio	12.0:1	12.0:1	12.0:1	12.0:1	12.0:1	12.0:1	12.0:1	12.0:1	12.0:1
Displacement	2.5L / 2,488 cc	2.5L / 2,488 cc	2.5L / 2,488 cc	2.5L / 2,488 cc	2.5L / 2,488 cc	2.5L / 2,488 cc	2.5L / 2,488 cc	2.5L / 2,488 cc	2.5L / 2,488 cc
Horsepower	181 @ 6,000 rpm	181 @ 6,000 rpm	181 @ 6,000 rpm	181 @ 6,000 rpm	181 @ 6,000 rpm	181 @ 6,000 rpm	181 @ 6,000 rpm	181 @ 6,000 rpm	181 @ 6,000 rpm
Torque	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm	181 lb-ft @ 3,600 rpm
Redline RPM	6000	6000	6000	6000	6000	6000	6000	6000	6000
Emissions	LEV III SULEV30 / Tier 3 bin 30	LEV III ULEV50 / Tier 3 bin 50	LEV III SULEV30 / Tier 3 bin 30	LEV III ULEV50 / Tier 3 bin 50	LEV III SULEV30 / Tier 3 bin 30	LEV III ULEV50 / Tier 3 bin 50	LEV III SULEV30 / Tier 3 bin 30	LEV III ULEV50 / Tier 3 bin 50	LEV III ULEV50 / Tier 3 bin 50
Engine Oil type	0W-20	0W-20	0W-20	0W-20	0W-20	0W-20	0W-20	0W-20	0W-20
Recommended Fuel Type	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded
Transmission									
Continuously Variable Transmission (CVT)	STD	STD	STD	STD	STD	STD	STD	STD	STD
CVT Automatic Ratios	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378
Reverse	1.960	1.960	1.960	1.960	1.960	1.960	1.960	1.960	1.960
Final Drive	5.694	5.694	5.694	5.694	5.694	5.694	5.694	5.694	5.694
Suspension									
Front	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar	MacPherson strut with stabilizer bar
Rear	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar
Steering									
Type	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering
Overall Ratio	14.2 : 1	14.2 : 1	14.2 : 1	14.2 : 1	14.2 : 1	14.2 : 1	14.2 : 1	14.2 : 1	14.2 : 1
Turns, lock to lock	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6
Turning circle	36.1 ft	36.1 ft	36.1 ft	36.1 ft	36.1 ft	36.1 ft	36.1 ft	36.1 ft	36.1 ft
Brakes/ Tires/ Wheels									
Front	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in	Ventilated disc, 13.8 in
Rear	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in	Ventilated disc, 13.0 in
ABS	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD) and Brake Assist
Wheels	18 x 7 1/2J aluminum alloy	18 x 7 1/2J aluminum alloy	20 x 8J aluminum alloy	20 x 8J aluminum alloy	20 x 8J aluminum alloy	20 x 8J aluminum alloy	20 x 8J aluminum alloy	20 x 8J aluminum alloy	20 x 8J aluminum alloy
Tires	P235/60 R18	P235/60 R18	P255/45 R20	P255/45 R20	P255/45 R20	P255/45 R20	P255/45 R20	P255/45 R20	P255/45 R20
Exterior Dimensions									
Wheelbase (inches)	106.5	106.5	106.5	106.5	106.5	106.5	106.5	106.5	106.5
Overall length (inches)	185.8	185.8	185.8	185.8	185.8	185.8	185.8	185.8	185.8
Overall width (inches) w/ mirror folded	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7
Overall width (inches) w/ mirror unfolded	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
Overall height (inches)	68.7	68.7	68.8	68.8	68.8	68.8	68.8	68.8	68.8
Track, front (inches)	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7
Track, rear (inches)	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1
Ground clearance (inches)	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.4	8.4

Copyright 2025, Mitsubishi Motors North America

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com).

Feature Description	ES 2WD	ES S-AWC	SE 2WD	SE S-AWC	SEL 2WD	SEL S-AWC	SEL Prem 2WD	SEL Prem S-AWC	Platinum Edition S-AWC
K-Model	GM4WXTMCL2M	GM4WXTMCZL2M	GM4WXTXCL2M	GM4WXTXCZL2M	GM4WXTUCL2M	GM4WXTUCZL2M	GM4WXTUCL2M	GM4WXTUCZL2M	GM4WXTUCZL2M
Model Code	3	13	4	14	6	16	6	16	16
Interior Dimensions									
Head Room (with sunroof)									
Front (inches)	40.6	40.6	40.6 (38.8)	40.6 (38.8)	40.6 (38.8)	40.6 (38.8)	40.6 (38.8)	40.6 (38.8)	40.6 (38.8)
2nd row (inches)	39.1	39.1	39.1(37.4)	39.1(37.4)	39.1(37.4)	39.1(37.4)	39.1(37.4)	39.1(37.4)	39.1(37.4)
3rd row (inches)	34.5	34.5	34.5(34.5)	34.5(34.5)	34.5(34.5)	34.5(34.5)	34.5(34.5)	34.5(34.5)	34.5(34.5)
Leg room									
Front (inches)	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7
2nd row (inches)	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
3rd row (inches)	18.7	18.7	18.7	18.7	18.7	18.7	18.7	18.7	18.7
Shoulder room									
Front (inches)	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9
2nd row (inches)	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9
3rd row (inches)	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
Hip room									
Front (inches)	54	54	54	54	54	54	54	54	54
2nd row (inches)	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3	53.3
3rd row (inches)	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1	42.1
SAE volume (with sunroof)									
SAE passenger volume (cu ft.)	125.5	125.5	125.5(120.8)	125.5(120.8)	125.5(120.8)	125.5(120.8)	125.5(120.8)	125.5(120.8)	125.5(120.8)
SAE cargo volume - Behind front seats (with sunroof) (cu.ft)	-	-	64.3	64.3	64.3	64.3	64.3	64.3	64.3
SAE cargo volume - Behind front seats (w/o sunroof) (cu.ft)	64.3	64.3	-	-	-	-	-	-	-
SAE cargo volume - Behind 2nd row seats (with sunroof) (cu ft.)	-	-	30.6	30.6	30.6	30.6	30.6	30.6	30.6
SAE cargo volume - Behind 2nd row seats (w/o sunroof) (cu ft.)	30.6	30.6	-	-	-	-	-	-	-
SAE cargo volume - Behind 3rd row seats (with sunroof) (cu ft.)	-	-	10.9	10.9	10.9	10.9	10.9	10.9	10.9
SAE cargo volume - Behind 3rd row seats (w/o sunroof) (cu ft.)	10.9	10.9	-	-	-	-	-	-	-
Capacities									
Passenger Seating	7	7	7	7	7	7	7	7	7
Fuel	14.5 gallons	14.5 gallons	14.5 gallons	14.5 gallons	14.5 gallons	14.5 gallons	14.5 gallons	14.5 gallons	14.5 gallons
Oil	4.5 qt	4.5 qt	4.5 qt	4.5 qt	4.5 qt	4.5 qt	4.5 qt	4.5 qt	4.5 qt
Towing Capacity (lbs.)	2000	2000	2000	2000	2000	2000	2000	2000	2000
Trailer Tongue Weight (lbs.)	200	200	200	200	200	200	200	200	200
Weights									
Curb Weight (lbs.)	3681	3803	3703	3836	3770	3903	3770	3903	3903
GVWR (lbs.)	5181	5302	5181	5302	5181	5302	5181	5302	5302
Weight distribution	58 / 42 %	58 / 42 %	58 / 42 %	58 / 42 %	58 / 42 %	57 / 43 %	58 / 42 %	57 / 43 %	57 / 43 %
Fuel Economy									
City	24	24	24	24	24	24	24	24	24
Highway	31	30	31	30	31	30	31	30	30
Combined	27	26	27	26	27	26	27	26	26
Warranties									
Basic	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles
Limited Powertrain	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles
Anti-corrosion	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles
Roadside Assistance	5-year / Unlimited miles	5-year / Unlimited miles	5-year / Unlimited miles	5-year / Unlimited miles	5-year / Unlimited miles	5-year / Unlimited miles	5-year / Unlimited miles	5-year / Unlimited miles	5-year / Unlimited miles