

Technical Service Bulletin

Topic	Showroom Charging Instructions
Market area	Bentley: worldwide (2WBE)
Brand	Bentley
Transaction No.	2076695/1
Level	EH
Status	Released for publishing
Release date	Feb 14, 2025

New customer code

Object of complaint	Complaint type	Position
power, vehicle electrical system, data transfer -> power supply -> starter battery	electrical -> voltage too low	

Vehicle data

25MY Continental GT, GTC & Flying Spur

Sales types

Type	MY	Brand	Designation	Engine code	Gearbox code	Final drive code
Z23*	2025	E		*	*	*
Z24*	2025	E		*	*	*
Z32*	2025	E		*	*	*

Documents

Document name
master.xml

Condition

12V battery voltage drop when on showroom display.

Technical Background

To preserve the life of the 12V battery and to ensure it does not go flat, follow the process described in the measure section.

Production Solution

Not applicable

Service

When using the HV charger, please remove the charger from the vehicle as soon as the HV battery has achieved 100% state of charge.

Please ensure that all 25MY Continental GT, GTC & Flying Spur models are connected to an approved 12V lithium battery charger for 30 minutes per day when in the showroom. The charger must be connected on the approved jump posts under the bonnet.

This prevents the 12V battery going flat when in normal showroom use and helps preserve the long term life of the 12V battery.