

# HELP CENTER

What can we help you find?

Search

[Help Center Home](#) / [Article](#)

03/11/2025

## 2014+ Chieftain Battery Removal and Installation

### Indian Chieftain Battery Removal and Installation - Indian Motorcycle



Required Tools and Supplies	
Dielectric Grease or Petroleum Jelly	10mm Socket
5mm Allen Socket	6mm Allen Socket
Ratchet	Torque Wrench
Shop Rags	Safety Glasses & Nitrile Gloves

Always wear safety glasses and nitrile gloves when servicing your Indian Motorcycle. To remove and replace the battery on your Chieftain, follow these steps:

1. Park the motorcycle on a flat, level surface.
2. Ensure the bike is powered OFF.
3. Remove the upper side covers by pulling the corners straight out to disengage from the rubber grommets in the frame.

4. To remove the seat, first use a 6mm Allen socket to remove the two fasteners securing the driver's seat to the frame.
  5. Then remove the passenger seat fastener with a 5mm Allen socket.
  6. Lift the rear of the seat and pull rearward to disengage the front retaining arms.
  7. Use a 5mm Allen socket to remove the fastener securing the Vehicle Control Module mounting plate to the top of the battery box.
  8. Slide the VCM assembly forward to disengage the tabs.
  9. Carefully place it out of the way. Do not disconnect the VCM. Ensure the VCM does not touch the positive battery terminal or cable. This can cause the VCM to short out.
  10. Remove the negative battery cable first with a 10mm socket. Position the cable well clear of the terminal.
  11. Remove the positive protector boot from the positive battery cable. Then remove the cable from the terminal with a 10mm socket. Position the cable well clear of the terminal.
  12. Reinstall the fasteners onto the posts to prevent misplacement.
  13. Lift the battery straight up and out of the battery box.
  14. Inspect the battery box and cover for damage. Ensure the pads are properly located and in good condition.
  15. If reinstalling the battery, ensure it is fully charged and free of any debris or damage. Follow the instructions in the Battery Charging section of your [Owner's Manual](#) before installing the battery.
  16. Carefully position the battery into the battery box with the negative terminal toward the front of the motorcycle.
  17. Route the positive cable perpendicular to the long side of the battery. Install the positive cable first to prevent arcing. **Torque** to 45 in-lbs (5 Nm).
  18. Reinstall the positive cable protector boot.
  19. Then install the negative cable. Route the cable perpendicular to the battery. **Torque** to 45 in-lbs (5 Nm).
  20. Apply a light film of dielectric grease or petroleum jelly to the terminals.
  21. Verify the cables are secure and properly routed.
-

- 22.** Carefully reinstall the VCM mounting plate and fastener, avoiding any contact with the positive battery cable. **Torque** to 84 in-lbs (9.5 Nm).
- 23.** Turn the bike ON to verify the battery has been connected properly.
- 24.** Reinstall the seat by engaging the front retainers and aligning the mounting holes.
- 25.** Reinstall the two driver's seat fasteners. **Torque** to 84 in-lbs (9.5 Nm).
- 26.** Align the passenger seat bracket over the rubber washer. **Torque** the fastener to 84 in-lbs (9.5 Nm).
- 27.** Finally, align the three side panel grommets and reinstall each upper side panel.

For more information, see your authorized Indian Motorcycle Dealer. Find a dealer near you with the [Dealer Locator](#).

Maintenance tips, procedures and specifications can be found in your [Owner's Manual](#).

To find diagrams and replacement part numbers, use the [online parts catalog](#).

*YouTube® is a registered trademark of Google LLC*

*Unless noted, trademarks are the property of Indian Motorcycle International, LLC*

*© 2022 Indian Motorcycle International, LLC*

Was this article helpful?

- Yes, it answers my question
- No, it's missing information or visuals
- No, the instructions are unclear
- No, What are the next steps?
- No, I'm experiencing a technical error
- Other

---

\* [-] **How can we improve this article? We'd love to hear your suggestions**

Tell us what you would like to see in this article

Send

---