

Manufacturer's Certificate

911 (992)

10/25 ENU 4400

4

Approved: Wheels and Tires (10/25)

Revision: This bulletin replaces bulletin Group 4 52/24, dated February 28, 2025.

Model Year: **As of 2025**

Vehicle Type: **Type 992PA (Coupé / Cabriolet):**
911 Carrera / 911 Carrera T / 911 Carrera S / 911 Carrera GTS / 911 Carrera 4 GTS / 911 Targa 4 GTS

Cause: Approval status: December 2024

Sizes: **Permissible tire and wheel sizes**
(RO = rim offset in mm, FA = front axle, RA = rear axle)

Tire sizes	Wheel sizes	Snow chains
911 Carrera / 911 Carrera T / 911 Carrera S		
WITHOUT hybrid engine		
Summer		
19-/20-inch FA: 235/40 ZR 19 (96Y) XL RA: 295/35 ZR 20 (105Y) XL Not for 911 Carrera T not for 911 Carrera S	FA: 8.5J x 19, RO 52 RA: 11.5J x 20, RO 81	No
20/21-inch FA: 245/35 ZR 20 (95Y) XL RA: 305/30 ZR 21 (104Y) XL	FA: 8.5J x 20, RO 50 RA: 11.5J x 21, RO 79	No
20/21-inch FA: 245/35 ZR 20 (91Y) RA: 305/30 ZR 21 (100Y)		
Winter		
19-/20-inch FA: 235/40 R 19 96V XL RA: 295/35 R 20 105V XL not for 911 Carrera S	FA: 8.5J x 19, RO 52 RA: 11J x 20, RO 80	RA only

4911 (992)
4400 ENU **10/25**

Manufacturer's Certificate

20/21-inch FA: 245/35 R 20 95V XL RA: 305/30 R 21 104V XL	FA: 8.5J x 20, RO 50 RA: 11J x 21, RO 82	RA only
---	---	---------

Tire sizes	Wheel sizes	Snow chains
911 Carrera GTS / 911 Carrera 4 GTS / 911 Targa 4 GTS WITH hybrid engine		
Summer		
20-/21 inch FA: 245/35 ZR 20 (95Y) XL RA: 315/30 ZR 21 (105Y) XL	FA: 8.5J x 20, RO 50 RA: 11.5J x 21, RO 79	No
Winter		
20-/21 inch FA: 245/35 R 20 95V XL RA: 305/30 R 21 104V XL	FA: 8.5J x 20, RO 50 RA: 11J x 21, RO 82	RA only

Wheels:

Overview of Porsche wheels for summer and winter tires

Identification on the inside of the wheel:

Wheel size, rim offset (RO) in mm, part number (without color code marking FFF) and Porsche logo

19/20-inch – "Carrera 7" wheel

FA: 8.5J x 19, RO 52 (summer, winter)

Part No. 992.601.025.FR_FFF

RA: 11.5J x 20, RO 81 (summer)

Part No. 992.601.025.GC_FFF

RA: 11J x 20, RO 80 (winter)

Part No. 992.601.025.GE_FFF



Carrera 7

20/21-inch "RS Spyder Design 2" wheel

FA: 8.5J x 20, RO 50 (summer)

Part No. 992.601.025.EG_FFF

RA: 11.5J x 21, RO 67 (summer)

Part No. 992.601.025.CT_FFF

RA: 11J x 21, RO 82 (winter)

Part No. 992.601.025.BL_FFF



RS Spyder Design 2

20/21-inch "Carrera S6" wheel

FA: 8.5J x 20, RO 50 (summer)
Part No. 992.601.025.BJ_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.025.BK_FFF

or

FA: 8.5J x 20, RO 50 (summer)
Part No. 992.601.029.M_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.029.N_FFF



Carrera S6

20/21-inch "911 Carrera Exclusive Design" wheel TEQ range

FA: 8.5J x 20, RO 50 (summer)
Part No. 992.601.025.ET_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.025.GG_FFF

or

FA: 8.5J x 20, RO 50 (summer)
Part No. 992.601.029.P_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.029.Q_FFF



Carrera Exclusive Design

20-inch/21-inch "911 Carrera Exclusive Design with CFRP Aeroblades" wheel

FA: 8.5J x 20, RO 50 (summer)
Part No. 992.601.025.ET_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.025.GG_FFF

or

FA: 8.5J x 20, RO 50 (summer)
Part No. 992.601.029.P_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.029.Q_FFF



911 Carrera Exclusive Design with CFK Aeroblades

20-inch/21-inch "911 Carrera Classic 4" wheel
TEQ offer

FA: 8.5J x 20, RO 50 (summer)
Part No. 992.601.025.BM_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.025.BN_FFF



911 Carrera Classic 4

20/21-inch "911 Carrera Exclusive Design with CFRP Aeroblades" wheel

FA: 8.5J x 20, RO 50 (summer)
Part No.:
ASSY: 992.601.075
Wheel: 992.601.025.BR__FFF
Cover: 992.601.235
Screw: WHT.009.498

RA: 11.5J x 21, RO 79 (summer)
ASSY: 992.601.076
Wheel: 992.601.025.BS__FFF
RA trim: 992.601.235.A
Screw: WHT.009.498



Carrera Exclusive Design with CFK Aeroblades

20/21-inch "GTS" wheel

FA: 8.5J x 20, RO 50 (summer, winter)
Part No. 992.601.025.BT_FFF

RA: 11.5J x 21, RO 79 (summer)
Part No. 992.601.025.CA_FFF

RA: 11J x 21, RO 82 (winter)
Part No. 992.601.025.FD_FFF

*GTS*

20-inch/21-inch – “Manthey” wheel, Carrera lightweight wheel

TEQ offer

FA: 8.5J x 20, RO 50 (summer)

Part No.: 992.044.612

RA: 11.5J x 21, RO 79 (summer)

Part No.: 992.044.613



Manthey wheel, Carrera lightweight wheel

20-inch/21-inch – “Manthey” wheel, Carrera lightweight wheel

TEQ offer

FA: 8.5J x 20, RO 50 (summer)

Part No. 992.044.612.A

RA: 11.5J x 21, RO 79 (summer)

Part No. 992.044.613.A

Only for GTS



Manthey wheel, Carrera lightweight wheel



Information

Improper handling can damage the wheel surface.

Carry out tire removal and mounting using a bead holding-down device only.

Use a leather pad on the rim flange to support the valve insertion tool.

Only use the Porsche centring clamping set for balancing.

Do not use hard brushes to clean the wheels as these can cause deep scratches that cannot be removed by polishing.

Never use solvents or other chemical substances not approved by Porsche on tires.

**Information**

Only install wheels with identical part numbers on each axle.

Wheel
Mounting:

using wheel bolts:

Tightening torque 160 Nm (118 ftlb.)

using central wheel lock:

Tightening torque 600 Nm (442.5 ftlb.)

Summer Tires:

Tire size	Tire make and type / Label value (link to EU database)
911 Carrera / 911 Carrera T / 911 Carrera S WITHOUT hybrid engine	
FA: 235/40 ZR 19 (96Y) XL RA: 295/35 ZR 20 (105Y) XL Not for 911 Carrera T not for 911 Carrera S	Michelin Pilot Sport 4S NAO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/413170 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/410061
	Pirelli PZero NAO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/595483 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/595482
FA: 245/35 ZR 20 (91Y) RA: 305/30 ZR 21 (100Y)	Pirelli PZero NA1 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/596523 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/596522
FA: 245/35 ZR 20 (95Y) XL RA: 305/30 ZR 21 (104Y) XL	Goodyear EAGLE F1 ASYMMETRIC 3 NAO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/529783 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/529788
	Michelin Pilot Sport 4S NAO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/409939 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/411576

Manufacturer's Certificate

911 (992)

10/25 ENU 4400

4

Tire size	Tire make and type / Label value (link to EU database)
911 Carrera GTS / 911 Carrera 4 GTS / 911 Targa 4 GTS	
WITH hybrid engine	
FA: 245/35 ZR 20 (95Y) XL RA: 315/30 ZR 21 (105Y) XL	Pirelli PZero R NA2 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1417986 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1790585
	Goodyear EAGLE F1 SuperSport R NA2 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1608128 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1608129

Winter Tires:

Tire size	Tire make and type / Label value (link to EU database)
911 Carrera / 911 Carrera T / 911 Carrera S	
WITHOUT hybrid engine	
FA: 235/40 R 19 96V XL RA: 295/35 R 20 105V XL not for 911 Carrera S	Pirelli P Zero Winter 2 NA2 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1973064 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1955871
FA: 245/35 R 20 95V XL RA: 305/30 R 21 104V XL	Goodyear Ultragrip Performance 3 NA2 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/2150488 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/2128506
	Michelin Pilot Alpin 5 NA2 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/2038237 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/2038238

Tire size	Tire make and type / Label value (link to EU database)
911 Carrera GTS / 911 Carrera 4 GTS / 911 Targa 4 GTS	
WITH hybrid engine	
FA: 245/35 R 20 95V XL RA: 305/30 R 21 104V XL	Goodyear Ultragrip Performance 3 NA2 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/2150488 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/2128506
	Michelin Pilot Alpin 5 NA2

Tire size	Tire make and type / Label value (link to EU database)
	Michelin Pilot Alpin 5 NA2 FA: HTTPS://EPREL.EC.EUROPA.EU/QR/2038237 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/2038238

Arrow with inscription "Rotation"

= Directional mounting

"Inside/Outside" inscription

= Mounting on specified side only

Arrow with inscriptions "Rotation" and
"Inside/Outside"

= Directional mounting on specified side only.



Information

In principle, only tires that at least correspond to the maximum vehicle speed may be installed on the vehicle.

There may be national exemptions for winter tires marked for M+S and 3PMSF (3 peak mountain snow flake), which also permit tires that do not correspond to the maximum vehicle speed.



Information

"N..." = Specification code of the tire, e.g. "NA0", "NA1", "NA2" ... The complete "N ..." code of the relevant tire makes must be shown on the tire sidewall near the type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.



Information

As a general rule, Porsche does not recommend having tires repaired. Local legislation must always be observed.

It is advisable to install winter tires for temperatures below 7 °C (44 °F), because the driving characteristics of summer tires and UHP tires are reduced at low temperatures. Subfreezing temperatures can cause permanent damage to summer tires and UHP tires.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire by more than 30%. If this value is exceeded, we recommend that you replace both tires.



WARNING

Driving with different tires (mixed tires)

- **Uncontrollable vehicle handling**
- ⇒ **Only use tires of the same make and type, with the same speed index and the same specification code (NA0, NA1, NA2, etc.) on a vehicle.**

Tire Pressure:



Incorrect tire pressure

- **Uncontrollable vehicle handling**
- ⇒ **Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.**
- ⇒ **Check age of tires. Recommendation: Replace tires that are more than 6 years old.**
- ⇒ **Perform visual inspections.**
- ⇒ **Use only tires approved by Porsche.**



Driving at high speed with low tire pressure

- **Irreparable damage to tires**
- ⇒ **Set comfort and performance air pressure for tires only on vehicles with "Comfort pressure" and "Performance pressure" selected in the instrument cluster.**



Information

The tire pressure applies only to the tire makes and types approved by Porsche and is specified for cold tires (approx. 20 °C/ 68 °F). The tire pressure must not be lower than the specified values.

Standard tire pressure for summer tires

Standard tire pressure for summer tires					
911 Carrera					
Tire size	Wheel size	Axle	Part load	Full load	Part load, comfort air pressure up to 270 km/h (168 mph)
235/40 ZR 19	8.5J x 19	FA	2.3 bar 33 psi	2.4 bar 35 psi	2.0 bar 29 psi
295/35 ZR 20	11.5J x 20	RA	2.6 bar 37 psi	3.0 bar 44 psi	2.2 bar 31 psi

245/35 ZR 20	8.5J x 20	FA	2.3 bar 33 psi	2.6 bar 37 psi	2.0 bar 29 psi
305/30 ZR 21	11.5J x 21	RA	2.7 bar 39 psi	3.2 bar 46 psi	2.2 bar 31 psi

Standard tire pressure for summer tires**911 Carrera T**

Tire size	Wheel size	Axle	Part load	Full load	Part load, comfort air pressure up to 270 km/h (168 mph)
245/35 ZR 20	8.5J x 20	FA	2.3 bar 33 psi	2.6 bar 37 psi	2.0 bar 29 psi
305/30 ZR 21	11.5J x 21	RA	2.7 bar 39 psi	3.2 bar 46 psi	2.2 bar 31 psi

Standard tire pressure for summer tires**911 Carrera S****C2S Coupé / C4S Coupé**

Tire size	Wheel size	Axle	Part load	Full load	Part load, comfort air pressure up to 270 km/h (168 mph)	Full load, comfort air pressure up to 270 km/h (168 mph)
245/35 ZR 20	8.5J x 20	FA	2.3 bar 33 psi	2.5 bar 36 psi	2.0 bar 29 psi	2.3 bar 33 psi
305/30 ZR 21	11.5J x 21	RA	2.6 bar 37 psi	3.1 45 psi	2.2 bar 31 psi	2.6 bar 37 psi

Standard tire pressure for summer tires						
911 Carrera S						
C2S Coupé Aerokit / C4S Coupé Aerokit						
C2S convertible / C4S convertible						
Tire size	Wheel size	Axle	Part load	Full load	Part load, comfort air pressure up to 270 km/h (168 mph)	Full load, comfort air pressure up to 270 km/h (168 mph)
245/35 ZR 20	8.5J x 20	FA	2.3 bar 33 psi	2.5 bar 36 psi	2.0 bar 29 psi	2.3 bar 33 psi
305/30 ZR 21	11.5J x 21	RA	2.7 bar 39 psi	3.2 bar 46 psi	2.2 bar 31 psi	2.7 bar 39 psi

Standard tire pressure for summer tires						
911 Carrera S						
C4S Targa						
Tire size	Wheel size	Axle	Part load	Full load	Part load, comfort air pressure up to 270 km/h (168 mph)	Full load, comfort air pressure up to 270 km/h (168 mph)
245/35 ZR 20	8.5J x 20	FA	2.3 bar 33 psi	2.5 bar 36 psi	2.0 bar 29 psi	2.3 bar 33 psi
305/30 ZR 21	11.5J x 21	RA	2.8 bar 41 psi	3.2 bar 46 psi	2.2 bar 31 psi	2.8 bar 41 psi

Standard tire pressure for summer tires						
911 Carrera GTS / 911 Carrera 4 GTS / 911 Targa 4 GTS						
Tire size	Wheel size	Axle	Part load	Full load	Part load, comfort air pressure up to 270 km/h (168 mph)	

245/35 ZR 20	8.5J x 20	FA	2.3 bar 33 psi	2.6 bar 37 psi	2.0 bar 29 psi
315/30 ZR 21	11.5J x 21	RA	2.7 bar 39 psi	3.2 bar 46 psi	2.2 bar 31 psi

Standard tire pressure for winter tires

Standard tire pressure for winter tires				
911 Carrera / 911 Carrera T				
Tire size	Wheel size	Axle	Part load	Full load
235/40 R 19	8.5J x 19	FA	2.2 bar 31 psi	2.3 bar 33 psi
295/35 R 20	11J x 20	RA	2.4 bar 35 psi	2.7 bar 39 psi
245/35 R 20	8.5J x 20	FA	2.2 bar 31 psi	2.4 bar 35 psi
305/30 R 21	11J x 21	RA	2.5 bar 36 psi	2.8 bar 41 psi

Standard tire pressure for winter tires				
911 Carrera S				
Tire size	Wheel size	Axle	Part load	Full load
245/35 R 20	8.5J x 20	FA	2.2 bar 31 psi	2.3 bar 33 psi
305/30 R 21	11J x 21	RA	2.4 bar 35 psi	2.7 bar 39 psi

Standard tire pressure for winter tires				
911 Carrera GTS / 911 Carrera 4 GTS / 911 Targa 4 GTS				
Tire size	Wheel size	Axle	Part load	Full load
245/35 R 20	8.5J x 20	FA	2.3 bar 33 psi	2.4 bar 35 psi
305/30 R 21	11J x 21	RA	2.6 bar 37 psi	2.9 bar 42 psi

Snow Chains:



Incorrectly installed snow chains

- **Uncontrollable vehicle handling**
- ⇒ **Do not exceed top speed of 50 km/h (30 mph).**
- ⇒ **Read assembly instructions (see also EQUIPMENT accessory finder on the Internet).**
- ⇒ **Observe country-specific regulations.**

Porsche offers the following snow chains as accessories:

Snow chain overview		
	19/20" (295/35 R 20)	20/21" (305/30R21)
GTS	—	992.044.690.A Link-type chain
Basic, T	992,044,690.A Link-type chain	992.044.690.C Quick-lock chain
S	—	

- Wheel Storage:
- Tires must be stored in a cool, dry and dark room with adequate ventilation.
 - Tires must never come into contact with fuel, oil, grease or chemicals.
 - Do not store summer tires in storage areas with ambient temperatures of less than 5° F (-15° C).
 - Complete wheel & tire assemblies can be stacked for storage; we recommend that you increase the tire pressure by approximately 6 psi (0.4 bar).
 - Optimum conditions for storage of the complete wheels are provided by the Original Porsche storage trolley, Part No. 000.044.000.38.
 - If the tires are not mounted on wheels, it is best to store them in a vertical position.
 - We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots.
 - Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.

- General Information:
- Always use new valves when changing tires.
 - Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on.
 - Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily.

- In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.
- In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

Matching (uncontrolled and controlled) is explained below: Uncontrolled matching:

- Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

Controlled matching:

- With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching.
- Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm - ideally approx. 0.5 mm - are desirable.
- The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

New Tires (Replacements):

- If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, type and with the same specification code must always be used on each of the two axles.
- If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling.
- This is especially the case if new tires are mounted on the rear axle.
- This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire on the same axle by more than 30 %.

Refer to WM 449503 for specific details of the vehicle you are working on.

- >The 2mm specification will be given here.
- > If there is none listed then the default is 30%.

Repairs to Tires:

- If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.
- Repairs to "V", "W", "Y", and "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires.

Tire Aging:

- Tires age due to chemical and physical processes, which can impair their function.

- Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use.
- Hairline aging cracks can occur on older tires.
- On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.
- Therefore, attention should be paid not only to the tread depth but also to the age of the tire.
- Tires should not be older than 6 years.
- The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201= 22nd week of 2001.

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2025 Porsche Cars North America, Inc.