

Search

[Help Center Home](#) / [Article](#)

05/08/2025

2022+ Chief Drive Belt Inspection and Tension Adjustment

Indian Chief Drive Belt Inspection and Tension Adjustment (2022 and newer) - ...



Required Tools and Supplies	
6mm Allen Socket	Belt Tension Tool or 10-Pound Weight
15mm Socket	Measurement Tool
27mm Socket	Marking Tool
Ratchet	Shop Rags
Torque Wrench	Safety Glasses
Nitrile Gloves	

To learn more about tools, read the [Tools and Fasteners Guide](#).

Always wear safety glasses and nitrile gloves when servicing your Indian Motorcycle. To inspect and adjust the drive belt tension on your model year 2022 and newer Indian Chief, Chief Dark Horse, Chief Bobber, Chief Bobber Dark Horse, Super Chief or Super Chief Limited, follow these steps:

1. Park the bike on a flat, level surface, and allow it to cool completely.
 2. Place the bike in an upright position, with the front wheel clamped in a wheel vise.
 3. Remove the saddlebags, if equipped, by freeing the buttons on the side and unbuckling the lid clasp.
 4. Open the lid, and remove the saddlebag fastener bolts inside with a 6mm Allen socket.
 5. Remove the saddlebag lower support bolts from the passenger foot peg mount with a 6mm Allen socket.
 6. Lift the saddlebag straight up and out to remove.
 7. Ensure the motorcycle is in NEUTRAL.
 8. Safely elevate the rear wheel so the tire can freely rotate. **Caution:** The motorcycle must be stable before proceeding.
 9. Inspect the entire length of the drive belt for wear or damage. Refer to your [Owner's Manual](#) for belt wear analysis and see your authorized [Indian Motorcycle Dealer](#) if replacement is needed.
 10. Check and record the belt deflection, applying 10 pounds of force. Ensure the belt is dry before measuring. Locking a tape measure will make it easier to maintain consistent measurements.
 11. Using the tire valve stem as a reference, measure at three additional points 90 degrees apart. The deflection should measure 28 mm (1.1 inches).
 12. If adjustment is needed, rotate the wheel forward and mark the tightest measurement point on the tire for reference.
 13. Mark the current adjuster locations on both sides of the rear wheel for reference.
 14. Count or measure the exposed threads past the adjuster nuts for reference.
 15. With a 27mm socket, loosen but do not remove the axle nut.
 16. **Torque** the nut to 15 ft-lbs (20 Nm) with a 27mm socket.
 17. Turn the right-side adjuster nut with a 15mm socket as needed to achieve proper belt tension.
 18. Use the left-side adjuster only to make final adjustments for belt alignment. Ensure the axle is seated forward against axle adjusters.
 19. While rotating the wheel backward, tighten the left-side adjuster until the belt comes off the inside sprocket flange. Sprocket teeth should be visible on both sides of the drive belt.
-

20. Once the desired setting is achieved, rotate the wheel forward, and verify the sprocket teeth are still visible on both sides of the drive belt.
21. If necessary, revert back to the initial settings and repeat this process as needed.
22. Re-check drive belt tension to verify it is still within specification. Improper tension or alignment can cause drive line noise and damage the drive belt.
23. Once the tension has been confirmed, **torque** the rear axle nut to 65 ft-lbs (88 Nm).
24. Pump the rear brake pedal several times to reset brake pad distance.
25. When the brake pedal is released, verify that the wheel rotates smoothly and freely, without drag.
26. Safely lower your motorcycle to the ground. Refer to your [Owner's Manual](#) for helpful hints and techniques.
27. Begin reinstalling the saddlebags by placing them into position and aligning the mounting holes.
28. Reinstall the fasteners. **Torque** to 18 ft-lbs (24 Nm).
29. Close and secure the saddlebag lids.

For more information, see your authorized Indian Motorcycle Dealer. Find a dealer near you with the [Dealer Locator](#).

Maintenance tips, procedures and specifications can be found in your [Owner's Manual](#). To find diagrams and replacement part numbers, use the [online parts catalog](#).

Pirelli® is a registered trademark of PIRELLA & C.S.P.A.

YouTube® is a registered trademark of Google LLC

Unless noted, trademarks are the property of Indian Motorcycle International, LLC

© 2022 Indian Motorcycle International, LLC

Was this article helpful?

- ☐ Yes, it answers my question
 - ☐ No, it's missing information or visuals
 - ☐ No, the instructions are unclear
 - ☐ No, What are the next steps?
-