

Manufacturer's Certificate

Cayenne (9YA)

28/25 ENU 4400

4

Approved: Wheels and Tires (28/25)

Revision: **This bulletin replaces bulletin Group 4 42/24 dated December 3, 2024.**

Vehicle Type: **Cayenne - incl. Coupé/ Cayenne S - incl. Coupé/ Cayenne PHEV - incl. Coupé/ Turbo GT Coupé USA/ Cayenne Turbo PHEV - incl. Coupé/ Cayenne Turbo PHEV Coupé with GT package/ Cayenne S PHEV - incl. Coupé**

Model Year: **As of 2024**

General Information: This Manufacturer's Certificate contains information about

- technically permissible wheel/tire combinations,
- measures that may be required when changing the wheel/tire combination fitted at the factory,
- approved original Porsche alloy wheels and
- approved summer, all-season and winter tires and their tire pressures.

Cause: Approval status: June 2025

Sizes: **Permissible tire and wheel sizes**
(RO = rim offset in mm, FA = front axle, RA = rear axle)



Information

Porsche Ceramic Composite Brakes (PCCB) are only permitted for 21-inch wheels, depending on wheel type.



Information

Porsche Surface Coated Brakes (PSCB) are only permitted for 20-inch or bigger wheels.



Information

For vehicles equipped with 19-inch and 20-inch wheels at the factory on which 21-inch or 22-inch wheels are to be retrofitted, the wheel arch extension set with Part No. 9Y0 044 820 must always be installed.

Cayenne, Cayenne Coupé / Cayenne S, Cayenne S Coupé / Cayenne PHEV, Cayenne PHEV Coupé / Turbo GT Coupé USA / Cayenne Turbo PHEV, Cayenne Turbo PHEV Coupé / Cayenne S PHEV, Cayenne S PHEV Coupé / Cayenne Turbo PHEV Coupé with GT package / Cayenne GTS, Cayenne GTS Coupé			
Tires	Tire sizes	Wheel sizes	Snow chains
Summer	FA: 255/55 ZR20 110Y XL RA: 295/45 ZR20 114Y XL or FA: 255/55 ZR20 (110Y) XL RA: 295/45 ZR20 (114Y) XL not for Turbo GT Coupé USA not for Turbo PHEV incl. Coupé not for GTS incl. Coupé not for Turbo PHEV Coupé with GT package	FA: 9.0Jx20 R050 Saloon, RA: 10.5Jx20 R064 Coupé, RA: 10.5Jx20 R055	No
	FA: 285/45 ZR21 (113Y) XL RA: 315/40 ZR21 (115Y) XL not for Turbo GT Coupé USA not for Turbo PHEV Coupé with GT package	FA: 9.5Jx21 R046 Saloon, RA: 11Jx21 R058 Coupé, RA: 11Jx21 R049	No
	FA: 285/40 ZR22 (110Y) XL RA: 315/35 ZR22 (111Y) XL	FA: 10.0Jx22 R048 Saloon, RA: 11.5Jx22 R061 Coupé, RA: 11.5Jx22 R052	No
Winter	FA: 255/55 R20 110V XL RA: 295/45 R20 114V XL not for Turbo GT Coupé not for Turbo PHEV incl. Coupé not for Cayenne Turbo PHEV Coupé with GT package	FA: 9.0Jx20 R050 Saloon, RA: 10.5Jx20 R064 Coupé, RA: 10.5Jx20 R055	RA only 9Y0.091.3 55.C
	FA: 285/45 R21 113V XL RA: 305/40 R21 113V XL	FA: 9.5Jx21 R046 Saloon, RA: 11Jx21 R058 Coupé, RA: 11Jx21 R049	RA only 9Y0.091.3 55.C
	FA: 285/40 R22 110V XL RA: 315/35 R22 111V XL	FA: 10Jx22 R048 Saloon, RA: 11.5Jx22 R061 Coupé, RA: 11.5Jx22 R052	No

Cayenne, Cayenne Coupé / Cayenne S, Cayenne S Coupé / Cayenne PHEV, Cayenne PHEV Coupé / Turbo GT Coupé USA / Cayenne Turbo PHEV, Cayenne Turbo PHEV Coupé / Cayenne S PHEV, Cayenne S PHEV Coupé / Cayenne Turbo PHEV Coupé with GT package / Cayenne GTS, Cayenne GTS Coupé			
Tires	Tire sizes	Wheel sizes	Snow chains
All-season	FA: 255/55 R20 110V XL RA: 295/45 R20 114V XL not for Turbo GT Coupé USA not for Turbo PHEV incl. Coupé not for GTS incl. Coupé not for Turbo PHEV Coupé with GT package	FA: 9.0Jx20 R050 Saloon, RA: 10.5Jx20 R064 Coupé, RA: 10.5Jx20 R055	No
	FA: 285/45 ZR21 113V XL RA: 315/40 ZR21 115V XL not for Turbo GT Coupé USA not for Turbo PHEV Coupé with GT package	FA: 9.5Jx21 R046 Saloon, RA: 11Jx21 R058 Coupé, RA: 11Jx21 R049	No
	FA: 285/40 R22 110V XL RA: 315/35 R22 111V XL not for Turbo GT Coupé USA	FA: 10.0Jx22 R048 Saloon, RA: 11.5Jx22 R061 Coupé, RA: 11.5Jx22 R052	No

Wheels:

Overview of Porsche wheels for summer, winter and all-season tires

Identification on the inside of the wheel:

Wheel size, rim offset (RO) in mm, part number (without color code marking FFF) and Porsche logo

20 inches- "Cayenne Design III"

FA:

9.0Jx20 R050

Part No.: 9Y0.601.025.CT FFF

RA:

Saloon: 10.5Jx20 R064

Part No.: 9Y0.601.025.DA FFF

Coupé: 10.5Jx20 R0 55

Part No. 9Y3.601.025.BM FFF

not for Turbo GT Coupé*20-inch Cayenne Design III wheel***20 inches- "Basic Aero"**

FA:

9.0Jx20 R050

Part No.: 9Y0.601.025.CR FFF

RA:

Saloon: 10.5Jx20 R064

Part No.: 9Y0.601.025.CS FFF

Coupé: 10.5Jx20 R055

Part No.: 9Y3.601.025.BL FFF

Only for PHEV*20 inches Basic Aero*

20 inches - "Cayenne S"

FA:
9.0Jx20 R050
Part No.: 9Y0.601.025.CB FFF

RA:
Saloon: 10.5Jx20 R064
Part No.: 9Y0.601.025.CC FFF

Coupé: 10.5Jx20 R055
Part No. 9Y3.601.025.CF FFF

not for Turbo GT Coupé



20 inches Cayenne S

20 inches - "Cayenne Sport Design III"

FA:
9.0Jx20 R050
Part No.: 9Y0.601.025.DH FFF

RA:
Saloon: 10.5Jx20 R064
Part No.: 9Y0.601.025.DJ FFF

Coupé: 10.5Jx20 R055
Part No.: 9Y3.601.025.BQ FFF

not for Turbo GT Coupé



20-inch Cayenne Sport Design III wheel

21 inches - "RS Spyder Design"

FA:
9.5Jx21 R046
Part No.: 9Y0.601.025.CD FFF (CDW)
Part No.: 9Y0.601.025.GA_FFF (Ronal)

RA:
Saloon: 11.0Jx21 R058
Part No.: 9Y0.601.025.GB_FFF (Ronal)
Part No.: 9Y0.601.029.BM FFF (SKS)

Coupé: 11.0Jx21 R049
Part No.: 9Y3.601.025.DJ_FFF (Ronal)
Part No.: 9Y3.601.029.AE FFF (SKS)

not for Turbo GT Coupé



21 inches RS Spyder Design

21 inches - "Turbo"

FA:
9.5Jx21 R046
Part No.: 9Y0.601.025.DP FFF

RA:
Saloon: 11.0Jx21 R058
Part No.: 9Y0.601.025.DQ FFF

Coupé: 11.0Jx21 R049
Part No. 9Y3.601.025.BT FFF

not for Turbo GT Coupé



21 inches Turbo

21 inches - "Aero Design"

FA:
9.5Jx21 R046
Part No.: 9Y0.601.025.EC FFF

RA:
Saloon: 11.0Jx21 R058
Part No.: 9Y0.601.025.CG FFF

Coupé: 11.0Jx21 R049
Part No.: 9Y3.601.025.BD FFF

Only for PHEV



21 inches P-HEV

21 inches - "Exclusive Design"

FA:
9.5Jx21 R046
Part No.: 9Y0.601.025.DB FFF (SU)
Part No.: 9Y0.601.029.BQ FFF (SKS)

RA:
Saloon: 11.0Jx21 R058
Part No.: 9Y0.601.025.DC FFF (SU)
Part No.: 9Y0.601.029.BR FFF (SKS)

Coupé: 11.0Jx21 R049
Part No.: 9Y3.601.025.BN FFF (SU)
Part No.: 9Y3.601.029.AG FFF (SKS)

not for Turbo GT Coupé



21 inches EXC/TEQ

22 inches - "911 Turbo V Design"

FA:

10.0Jx22 R048

Part No.: 9Y0.601.025.DR FFF

RA:

Saloon: 11.5Jx22 R061

Part No.: 9Y0.601.025.DS FFF

Coupé: 11.5Jx22 R052

Part No. 9Y3.601.025.CA FFF

not for Turbo GT Coupé*911 Turbo V***22 inches - "Sport Design"**

FA:

10.0x22 R048

Part No.: 9Y0.601.025.CK FFF

RA:

Saloon: 11.5Jx22 R061

Part No.: 9Y0.601.025.CL FFF

Coupé: 11.5Jx22 R052

Part No.: 9Y3.601.025.BF FFF

not for Turbo GT Coupé*22 inches Sport Design*

22 inches - "RS Spyder Design"

FA:
10.0Jx22 R048
Part No.: 9Y3.601.025.BH FFF

RA:
11.5Jx22 R052
Part No.: 9Y3.601.025.BJ FFF

Only for Coupé

not for Turbo GT Coupé



22 inches RS Spyder Design

22 inches - "GT Design" – only Coupé

FA:
not for Turbo GT Coupé:
10.0x22 R048
Part No. 9Y3.601.025.CC FFF

Only for Turbo GT Coupé:
10.5x22 R049
Part No.: 9Y3.601.025.BA FFF

RA:
11.5Jx22 R052
Part No.: 9Y3.601.025.AP FFF



22 inches GT Design

22 inches - "Exclusive Design Sport"

FA:
10.0x22 R048
Part No.: 9Y0.601.025.EA FFF (Ronal)
Part No.: 9Y0.601.029.BS FFF (SKS)

RA:
Saloon: 11.5Jx22 R061
Part No.: 9Y0.601.025.EB FFF (Ronal)
Part No.: 9Y0.601.029.BT FFF (SKS)

Coupé: 11.5Jx22 R052
Part No.: 9Y3.601.025.CE FFF (Ronal)
Part No.: 9Y3.601.029.AH FFF (SKS)

not for Turbo GT Coupé



22 inches Exclusive Design Sport

**Information**

Improper handling can damage the wheel surface.

Carry out tire removal and mounting using a bead holding-down device only.

Use a leather pad on the rim flange to support the valve insertion tool.

Only use the Porsche centring clamping set for balancing.

Do not use hard brushes to clean the wheels as these can cause deep scratches that cannot be removed by polishing.

Never use solvents or other chemical substances not approved by Porsche on tires.

**Information**

Only install wheels with identical part numbers on each axle.

Wheel
Mounting:

Tightening torque 160 Nm (118 ftlb.)

**WARNING****Driving with different tires (mixed tires)**

- **Uncontrollable vehicle handling**

⇒ **Only use tires of the same make and type, with the same speed index and the same specification code (NC0, NC1, NC2 ...) on a vehicle.**

Manufacturer's Certificate

Cayenne (9YA)

28/25 ENU 4400

4

Summer Tires:

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
20 inches	FA: 255/55 ZR20 110Y XL RA: 295/45 ZR20 114Y XL not for Turbo GT Coupé USA not for Turbo PHEV incl. Coupé not for GTS incl. Coupé not for Turbo PHEV Coupé with GT package	Pirelli P Zero NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/596885 RA: HTTP://EPREL.EC.EUROPA.EU/QR/596884
	FA: 255/55 ZR20 (110Y) XL RA: 295/45 ZR20 (114Y) XL not for Turbo GT Coupé USA not for Turbo PHEV incl. Coupé not for GTS incl. Coupé not for Turbo PHEV Coupé with GT package	Hankook Ventus S1 EvoZ NDO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1210304 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1210306
21 inches	FA: 285/45 ZR21 (113Y) XL RA: 315/40 ZR21 (115Y) XL not for Turbo GT Coupé USA not for Turbo PHEV Coupé with GT package	Pirelli P Zero NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/596869 RA: HTTP://EPREL.EC.EUROPA.EU/QR/596870
		Nexen N'FERA SPORT SUV NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1115733 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1115736
		Michelin Pilot Sport 4 SUV NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1612611 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1612610

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
22 inches	FA: 285/40 ZR22 (110Y) XL RA: 315/35 ZR22 (111Y) XL	Pirelli P Zero NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/596883 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/596886
		Continental SportContact 7 NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1332964 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1332963
		Yokohama ADVAN Sport V107 NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1317871 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1317885
22 inches Sport	FA: 285/40 ZR22 (110Y) XL RA: 315/35 ZR22 (111Y) XL	Pirelli P Zero Corsa NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/597018 RA: HTTP://EPREL.EC.EUROPA.EU/QR/597019

Winter Tires:

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
20 inches	FA: 255/55 R20 110V XL RA: 295/45 R20 114V XL not for Turbo GT Coupé not for Turbo PHEV incl. Coupé not for Cayenne Turbo PHEV Coupé with GT package	Pirelli Scorpion Winter 2 NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/1560350 RA: HTTP://EPREL.EC.EUROPA.EU/QR/1560351
		Michelin Pilot Alpin 5 SUV NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1245777 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1245776
		Hankook Winter i*cept evo3 X NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1566893 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1566924
21-inches	FA: 285/45 R21 113V XL RA: 305/40 R21 113V XL	Pirelli Scorpion Winter 2 NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/1644843 RA: HTTP://EPREL.EC.EUROPA.EU/QR/1644842
		Michelin Pilot Alpin 5 SUV NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1574164 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1574163
22 inches	FA: 285/40 R22 110V XL RA: 315/35 R22 111V XL	Continental WinterContact TS860 S NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/658974 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/659115
		Pirelli Scorpion Winter 2 NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/1773319 RA: HTTP://EPREL.EC.EUROPA.EU/QR/1773320

All-Season
Tires:

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
20 inches	FA: 255/55 R20 110V XL RA: 295/40 R20 114V XL not for Turbo GT Coupé USA not for Turbo PHEV incl. Coupé not for GTS incl. Coupé not for Turbo PHEV Coupé with GT package	Pirelli Scorpion Zero A/S NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/596882 RA: HTTP://EPREL.EC.EUROPA.EU/QR/596881
		Hankook DynaPro HP2 plus NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1370116 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1370118
21 inches	FA: 285/45 R21 113V XL RA: 315/40 R21 115V XL not for Turbo GT Coupé USA not for Turbo PHEV Coupé with GT package	Pirelli Scorpion Zero A/S NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/596867 RA: HTTP://EPREL.EC.EUROPA.EU/QR/596868
		Bridgestone Alenza Sport A/S NCO FA: https://eprel.ec.europa.eu/qr/501917 RA: https://eprel.ec.europa.eu/qr/501988
22 inches	FA: 285/40 R22 110V XL RA: 315/35 R22 111V XL not for Turbo GT Coupé USA	Pirelli Scorpion Zero A/S NCO FA: HTTP://EPREL.EC.EUROPA.EU/QR/596900 RA: HTTP://EPREL.EC.EUROPA.EU/QR/596901
		Yokohama ADVAN V35 NCO FA: HTTPS://EPREL.EC.EUROPA.EU/QR/1319361 RA: HTTPS://EPREL.EC.EUROPA.EU/QR/1319362



Information

"N..." = Specification code of the tire, e.g. "N0", "N1", "N2" ... The complete "N ..." code of the tires in question must be shown on the tire sidewall near the tire type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.

**Information**

As a general rule, Porsche does not recommend having tires repaired. Local legislation must always be observed.

It is advisable to install winter tires for temperatures below 7 °C (44 °F), because the driving characteristics of summer tires and UHP tires are reduced at low temperatures. Subfreezing temperatures can cause permanent damage to summer tires and UHP tires.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire by more than 30%. If this value is exceeded, we recommend that you replace both tires.

**Information**

In principle, only tires that at least correspond to the maximum vehicle speed may be installed on the vehicle.

There may be national exemptions for winter tires marked for M+S and 3PMSF (3 peak mountain snow flake), which also permit tires that do not correspond to the maximum vehicle speed.

**WARNING****Incorrect tire pressure**

- **Uncontrollable vehicle handling**
- ⇒ **Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.**
- ⇒ **Check age of tires. Recommendation: Replace tires that are more than 6 years old.**
- ⇒ **Perform visual inspections.**
- ⇒ **Use only tires approved by Porsche.**

Tire Pressure:

**Information**

The tire pressure applies only to the tire makes and types approved by Porsche and is specified for cold tires (approx. 20 °C/ 68 °F). The tire pressure must not be lower than the specified values.

Standard tire pressure

Standard tire pressure

Cayenne Basis / Cayenne Basis Coupé				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
20 inches – summer wheels	2.4 bar (35 psi)	2.6 bar (38 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)
21 inches – summer wheels	2.4 bar (35 psi)	2.4 bar (35 psi)	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches – summer wheels	2.4 bar (35 psi)	2.4 bar (35 psi)	2.2 bar (32 psi)	2.2 bar (32 psi)
20 inches – winter wheels	2.5 bar (36 psi)	2.5 bar (36 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
21 inches – winter wheels	2.4 bar (35 psi)	2.5 bar (36 psi)	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches – winter wheels	2.5 bar (36 psi)	2.7 bar (39 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
20 inches – all-season	2.5 bar (36 psi)	2.8 bar (41 psi)	2.3 bar (33 psi)	2.6 bar (38 psi)
21 inches – all-season	2.4 bar (35 psi)	2.7 bar (39 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)
22 inches – all-season	2.5 bar (36 psi)	2.7 bar (39 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)

Cayenne PHEV – RoW / Cayenne PHEV Coupé – RoW				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
20 inches – summer wheels	2.4 bar (35 psi)	2.6 bar (38 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)
21 inches – summer wheels	2.4 bar (35 psi)	2.5 bar (36 psi)	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches – summer wheels	2.5 bar (35 psi)	2.7 bar (39 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)
20 inches – winter wheels	2.6 bar (38 psi)	2.7 bar (39 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)

Cayenne PHEV — RoW / Cayenne PHEV Coupé — RoW				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
21 inches – winter wheels	2.6 bar (38 psi)	2.8 bar (41 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)
22 inches – winter wheels	2.8 bar (41 psi)	3.0 bar (44 psi)	2.4 bar (35 psi)	2.5 bar (35 psi)
20 inches – all-season	2.6 bar (38 psi)	2.9 bar (42 psi)	2.4 bar (35 psi)	2.7 bar (39 psi)
21 inches – all-season	2.4 bar (35 psi)	2.7 bar (39 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)
22 inches – all-season	2.8 bar (41 psi)	3.0 bar (44 psi)	2.4 bar (35 psi)	2.5 bar (36 psi)

Cayenne S / Cayenne S Coupé				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
20 inches – summer wheels	2.5 bar (36 psi)	2.7 bar (39 psi)	2.3 bar (33 psi)	2.5 bar (36 psi)
21 inches – summer wheels	2.4 bar (35 psi)	2.4 bar (35 psi)	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches – summer wheels	2.5 bar (36 psi)	2.6 bar (38 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
20 inches – winter wheels	2.6 bar (38 psi)	2.6 bar (38 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)
21 inches – winter wheels	2.4 bar (35 psi)	2.5 bar (36 psi)	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches – winter wheels	2.6 bar (38 psi)	2.7 bar (39 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)
20 inches – all-season	2.6 bar (38 psi)	2.9 bar (42 psi)	2.4 bar (35 psi)	2.7 bar (39 psi)

Cayenne S / Cayenne S Coupé				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
21 inches – all-season	2.4 bar (35 psi)	2.7 bar (39 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)
22 inches – all-season	2.6 bar (38 psi)	2.7 bar (39 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)

Cayenne Turbo GT Coupé – USA				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
22 inches – summer wheels	3.0 bar (44 psi)	3.0 bar (44 psi)	2.8 bar (41 psi)	2.8 bar (41 psi)
21 inches – winter wheels	2.4 bar (35 psi)	2.4 bar (35 psi)	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches – winter wheels	2.6 bar (38 psi)	2.6 bar (38 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)

Cayenne Turbo PHEV / Cayenne Turbo PHEV Coupé				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
21 inches – summer wheels	2.9 bar (42 psi)	2.9 bar (42 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)
22 inches – summer wheels	3.1 bar (45 psi)	3.3 bar (48 psi)	2.9 bar (42 psi)	2.9 bar (42 psi)
21 inches – winter wheels	2.6 bar (38 psi)	2.8 bar (41 psi)	2.4 bar (35 psi)	2.5 bar (36 psi)
22 inches – winter wheels	2.8 bar (41 psi)	3.0 bar (44 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)
21 inches – all-season	2.6 bar (38 psi)	2.9 bar (42 psi)	2.4 bar (35 psi)	2.7 bar (39 psi)
22 inches – all-season	2.8 bar (41 psi)	3.0 bar (44 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)

Cayenne Turbo PHEV Coupé with GT package				
	Full load		Part load	
	Front axle	Rear axle	Front axle	Rear axle
22 inches – summer wheels	3.1 bar (45 psi)	3.1 bar (45 psi)	2.9 bar (42 psi)	2.9 bar (42 psi)
21 inches – winter wheels	2.5 bar (36 psi)	2.5 bar (36 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
22 inches – winter wheels	2.8 bar (41 psi)	2.8 bar (41 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)
22 inches – all-season	2.8 bar (41 psi)	2.8 bar (41 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)

**WARNING****Driving at high speed with low tire pressure**

- Irreparable damage to tires
- ⇒ **Set comfort and performance air pressure for tires only on vehicles with "Comfort pressure" and "Performance pressure" selected in the instrument cluster.**

**Information**

The permitted speed threshold for Comfort tire pressure depends on the vehicle's country equipment (c-option) and cannot be selected.

Comfort Tire Pressure Up to 160 km/h (100 mph):

Comfort tire pressure up to 160 km/h (100 mph)

For vehicles with "Comfort pressure" selected in the Tire Pressure Monitoring (TPM) system and speed threshold "160 km/h" ("100 mph").

Cayenne Basis / Cayenne Basis Coupé		
Wheels	Front axle	Rear axle
20, 21, 22 inches summer, winter all-season	2.2 bar (32 psi)	2.2 bar (32 psi)

Cayenne PHEV — RoW / Cayenne PHEV Coupé — RoW		
Wheels	Front axle	Rear axle
20 , 21 inches summer, winter & all-season	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches summer, winter & all-season	2.2 bar (32 psi)	2.3 bar (33 psi)

Cayenne S / Cayenne S Coupé		
Wheels	Front axle	Rear axle
20 , 21, 22 inches summer, winter & all-season	2.2 bar (32 psi)	2.2 bar (32 psi)

Cayenne S PHEV / Cayenne S PHEV Coupé		
Wheels	Front axle	Rear axle
20, 21 inches summer, winter & all-season	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches summer, winter & all-season	2.2 bar (32 psi)	2.3 bar (33 psi)

Cayenne Turbo GT Coupé – USA		
Wheels	Front axle	Rear axle
22 inches Summer & Winter / 21 inches winter	2.2 bar (32 psi)	2.2 bar (32 psi)

Cayenne Turbo PHEV / Cayenne Turbo PHEV Coupé		
Wheels	Front axle	Rear axle
21 inches summer, winter & all-season	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches summer, winter & all-season	2.4 bar (35 psi)	2.4 bar (35 psi)

4

Cayenne (9YA)

4400 ENU **28/25**

Manufacturer's Certificate

Cayenne GTS / Cayenne GTS Coupé		
Wheels	Front axle	Rear axle
20 , 21, 22 inches summer, winter & all-season	2.2 bar (32 psi)	2.2 bar (32 psi)

Cayenne Turbo PHEV Coupé with GT package		
Wheels	Front axle	Rear axle
22 inches Summer & Winter / 21 inches winter	2.2 bar (32 psi)	2.2 bar (32 psi)

Comfort Tire
Pressure Up to
270 km/h (165
mph):

Comfort Tire pressure for summer tires up to 270 km/h (165 mph)

Cayenne Turbo GT Coupé – USA		
Wheels	Front axle	Rear axle
22 inches summer	2.2 bar (32 psi)	2.2 bar (32 psi)

Cayenne Turbo PHEV/ Cayenne Turbo PHEV Coupé		
Wheels	Front axle	Rear axle
21 inches summer	2.2 bar (32 psi)	2.2 bar (32 psi)
22 inches summer	2.3 bar (33 psi)	2.3 bar (33 psi)

Cayenne GTS / Cayenne GTS Coupé		
Wheels	Front axle	Rear axle
21, 22 inches summer	2.2 bar (32 psi)	2.2 bar (32 psi)

Cayenne Turbo PHEV Coupé with GT package		
Wheels	Front axle	Rear axle
22 inches summer	2.2 bar (32 psi)	2.2 bar (32 psi)

 **WARNING**

Incorrectly installed snow chains

- **Uncontrollable vehicle handling**
- ⇒ **Do not exceed top speed of 50 km/h (30 mph).**
- ⇒ **Read assembly instructions (see also EQUIPMENT accessory finder on the Internet).**
- ⇒ **Observe country-specific regulations.**

Snow Chains: Porsche offers the following snow chains as accessories:

Tire size	Porsche Part No.
Only for 20 inches & 21 inches winter wheels – RA only All-season tires are not approved for fitting snow chains	9Y0.091.355.C

Snow chain approval is only guaranteed for the tires specified above. Can only be fitted on the rear wheels.

- Wheel Storage:
- Tires must be stored in a cool, dry and dark room with adequate ventilation.
 - Tires must never come into contact with fuel, oil, grease or chemicals.
 - Do not store summer tires in storage areas with ambient temperatures of less than 5° F (-15° C).
 - Complete wheel & tire assemblies can be stacked for storage; we recommend that you increase the tire pressure by approximately 6 psi (0.4 bar).
 - Optimum conditions for storage of the complete wheels are provided by the Original Porsche storage trolley, Part No. 000.044.000.38.
 - If the tires are not mounted on wheels, it is best to store them in a vertical position.
 - We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots.
 - Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.

- General Information:
- Always use new valves when changing tires.
 - Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on.
 - Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily.
 - In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.
 - In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

Matching (uncontrolled and controlled) is explained below: Uncontrolled matching:

- Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

Controlled matching:

- With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching.
- Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm -ideally approx. 0.5 mm - are desirable.
- The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

New Tires (Replacements):

- If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, type and with the same specification code must always be used on each of the two axles.
- If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling.
- This is especially the case if new tires are mounted on the rear axle.
- This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire on the same axle by more than 30 %.

Refer to WM 449503 for specific details of the vehicle you are working on.

- >The 2mm specification will be given here.
- > If there is none listed then the default is 30%.

Repairs to Tires:

- If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.
- Repairs to "V", "W", "Y", and "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires.

Tire Aging:

- Tires age due to chemical and physical processes, which can impair their function.
- Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use.
- Hairline aging cracks can occur on older tires.
- On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.
- Therefore, attention should be paid not only to the tread depth but also to the age of the tire.
- Tires should not be older than 6 years.
- The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201= 22nd week of 2001.

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2025 Porsche Cars North America, Inc.