

Manufacturer's Certificate

982

33/24 ENU 4400

4

Approved: Wheels and Tires (33/24)

Revision: This bulletin replaces bulletin Group 4 11/24, dated November 8, 2024

Model Year: **As of 2019**

Vehicle Type: **718 Cayman GT4 (982), 718 Cayman GT4 RS (982), 718 Spyder (982), 718 Spyder RS (982)**

Cause: Approval status: June 2025

Sizes: **Permissible tire and wheel sizes**
(RO = rim offset in mm, FA = front axle, RA = rear axle)

Tires	Tire sizes	Wheel sizes	Snow chains
718 Cayman GT4, 718 Cayman GT4 RS, 718 Spyder, 718 Spyder RS			
Summer	FA: 245/35 ZR20 (95Y) XL RA: 295/30 ZR20 (101Y) XL	FA: 8,5 J x 20, RO 61 RA: 11J x 20, RO 50	No
Winter	FA: 235/35 R20 92V XL M+S RA: 275/30 R20 97V XL M+S	FA: 8J x 20, RO 57 RA: 10J x 20, RO 45	RA only
	FA: 245/35 R20 91V M+S RA: 295/30 R20 101V XL M+S	FA: 8,5 J x 20, RO 61 RA: 11J x 20, RO 50	No
	FA: 245/35 R20 91V M+S RA: 295/30 R20 97V M+S	FA: 8,5 J x 20, RO 61 RA: 11J x 20, RO 50	No

Wheels: **Overview of Porsche wheels for summer and winter tires**

Identification on the inside of the wheel:

Wheel size, rim offset (RO) in mm, part number (without colour code marking FFF) and Porsche logo

20-inch wheel "Spyder / GT4 / GT4 Sports Cup"

FA: 8,5 J x 20, RO 61
or Part No. 982.601.025.AB_FFF or
Part No. 982.601.029.AB_FFF

RA: 11J x 20, RO 50
or Part No. 982.601.025.AC_FFF or
Part No. 982.601.029.AC_FFF



20-inch wheel Spyder / GT4 / GT4 Sport Cup

20-inch wheel "Carrera S 4"

FA: 8J x 20, RO 57
Part No. 982.601.025.AJ_FFF /
982.601.029.AD_FFF

RA: 10J x 20, RO 45
Part No. 982.601.025.AK_FFF /
982.601.029.AE_FFF

only as a winter wheel



20-inch Carrera S wheel, black silky gloss

20-inch wheel for "GT4 RS" / "Spyder RS"

Summer:

FA: 8,5 J x 20, RO 61
Part No. 9GT.601.025.D__FFF

RA: 11J x 20, RO 50
Part No. 9GT.601.025.E__FFF

Winter:

FA: 8J x 20, RO 57
Part No. 9GT.601.025.H__FFF

RA: 10J x 20, RO 45
Part No. 9GT.601.025.J__FFF



20-inch wheel for GT4 RS / Spyder RS

20-inch wheel for "GT4 RS" / "Spyder RS"**Mg wheel**

FA: 8,5 J x 20, RO 61

Part No. 9GT.601.025.F__FFF

RA: 11J x 20, RO 50

Part No. 9GT.601.025.G__FFF

*20-inch wheel for GT4 RS / Spyder RS***20-inch "GT4" / "Spyder" wheel**

FA: 8,5 J x 20, RO 61

Part No. 982.044.610__FFF

RA: 11J x 20, RO 50

Part No. 982.044.611__FFF

*20-inch TEQ - GT4 lightweight wheel***Information**

Improper handling can damage the wheel surface.

Carry out tire removal and mounting using a bead holding-down device only.

Use a leather pad on the rim flange to support the valve insertion tool.

Only use the Porsche centring clamping set for balancing.

Do not use hard brushes to clean the wheels as these can cause deep scratches that cannot be removed by polishing.

Never use solvents or other chemical substances not approved by Porsche on tires.

**Information**

Only install wheels with identical part numbers on each axle.

Wheel **Tightening torque 160 Nm (118 ftlb.)**
 Mounting: Using central wheel lock:
Tightening torque 600 Nm (443 ftlb)



Driving with different tires (mixed tires)

- **Uncontrollable vehicle handling**
- ⇒ **Only use tires of the same make and type, with the same speed index and the same specification code (N0, N1, N2, ...) on a vehicle.**

Summer Tires:

Model	Tire size	Tire make and type / Label value (Link to EU database)
718 Cayman GT4, 718 Cayman GT4 RS, 718 Spyder, 718 Spyder RS	FA: 245/35 ZR20 (95Y) XL RA: 295/30 ZR20 (101Y) XL	Michelin Pilot Sport Cup 2 N1 (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/411697 RA: https://eprel.ec.europa.eu/qr/408334
		Dunlop Sport Maxx Race 2 N2 (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/529669 RA: https://eprel.ec.europa.eu/qr/530930
		Michelin Pilot Sport 4S N0 (Inside/Outside) Not for: GT4 RS, Spyder RS FA: https://eprel.ec.europa.eu/qr/411317 RA: https://eprel.ec.europa.eu/qr/411676
		Michelin Pilot Sport Cup 2 R N0 (Inside/Outside) Not for: Spyder, Spyder RS FA: https://eprel.ec.europa.eu/qr/462045 RA: https://eprel.ec.europa.eu/qr/462047
		Goodyear Eagle F1 Super Sport RS N0 (Inside/Outside) Not for: Spyder, Spyder RS FA: https://eprel.ec.europa.eu/qr/1564903 RA: https://eprel.ec.europa.eu/qr/1564905

Winter Tires:

Model	Tire size	Tire make and type / Label value (Link to EU database)
718 Cayman GT4, 718 Cayman GT4 RS, 718 Spyder, 718 Spyder RS	FA: 235/35 R20 92V XL M+S RA: 275/30 R20 97V XL M+S	Michelin Pilot Alpin 4 NO (Rotation) FA: https://eprel.ec.europa.eu/qr/410187 RA: https://eprel.ec.europa.eu/qr/412446
	FA: 245/35 R20 91V M+S RA: 295/30 R20 101V XL M+S	Michelin Pilot Alpin 4 N1 (Rotation) FA: https://eprel.ec.europa.eu/qr/412844 RA: https://eprel.ec.europa.eu/qr/411498
	FA: 245/35 R20 91V M+S RA: 295/30 R20 97V M+S	Pirelli Winter 240 Sottozero Series II NO (Inside/Outside) FA: https://eprel.ec.europa.eu/qr/594297 RA: https://eprel.ec.europa.eu/qr/594293

Arrow with inscription "Rotation"

= Directional mounting

inscription "Inside/Outside" or "Left" or "Right"

= Mounting on specified side only

Arrow with inscriptions "Rotation" and
"Inside/Outside"

= directional mounting on specified side only.

Arrow with inscriptions "Rotation" and "Left" or
"Right"

= directional mounting on specified side only.

**Information**

In principle, only tires that at least correspond to the maximum vehicle speed may be installed on the vehicle.

There may be national exemptions for winter tires marked for M+S and 3PMSF (3 peak mountain snow flake), which also permit tires that do not correspond to the maximum vehicle speed.

**Information**

"N..." = Specification code of the tire, e.g. "N0", "N1", "N2" ... The complete "N ..." code of the tires in question must be shown on the tire sidewall near the tire type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.



Information

As a general rule, Porsche does not recommend having tires repaired. Local legislation must always be observed.

It is advisable to install winter tires for temperatures below 7 °C (44 °F), because the driving characteristics of summer tires and UHP tires are reduced at low temperatures. Subfreezing temperatures can cause permanent damage to summer tires and UHP tires.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire by more than 30%. If this value is exceeded, we recommend that you replace both tires.



WARNING

Incorrect tire pressure

- **Uncontrollable vehicle handling**
- ⇒ **Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.**
- ⇒ **Check age of tires. Recommendation: Replace tires that are more than 6 years old.**
- ⇒ **Perform visual inspections.**
- ⇒ **Use only tires approved by Porsche.**



Information

The tire pressure applies only to the tire makes and types approved by Porsche and is specified for cold tires (approx. 20 °C/ 68 °F). The tire pressure must not be lower than the specified values.

Standard pressure for summer tires

Wheel size	718 Cayman GT4, 718 Cayman GT4 RS, 718 Spyder, 718 Spyder RS	
	FA (partial load, full load)	RA (partial load, full load)
20-inch wheels	2.0 bar (29 psi)	2.3 bar (33 psi)

Standard tire pressure for winter tires

Wheel size	718 Cayman GT4, 718 Cayman GT4 RS, 718 Spyder, 718 Spyder RS	
	FA (partial load, full load)	RA (partial load, full load)
20-inch wheels	2.5 bar (36 psi)	

**WARNING****Incorrectly installed snow chains**

- **Uncontrollable vehicle handling**
- ⇒ **Do not exceed top speed of 50 km/h (30 mph).**
- ⇒ **Read assembly instructions (see also TEQUIPMENT accessory finder on the Internet).**
- ⇒ **Observe country-specific regulations.**

Porsche offers the following snow chains as accessories:

Tire size	Porsche Part No.	Type of snow chain
275/30 R 20 M+S	981.044.600.00	Link-type chain, quick fit

- Wheel Storage:
- Tires must be stored in a cool, dry and dark room with adequate ventilation.
 - Tires must never come into contact with fuel, oil, grease or chemicals.
 - Do not store summer tires in storage areas with ambient temperatures of less than 5° F (-15° C).
 - Complete wheel & tire assemblies can be stacked for storage; we recommend that you increase the tire pressure by approximately 6 psi (0.4 bar).
 - Optimum conditions for storage of the complete wheels are provided by the Original Porsche storage trolley, Part No. 000.044.000.38.
 - If the tires are not mounted on wheels, it is best to store them in a vertical position.
 - We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots.
 - Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.

- General Information:
- Always use new valves when changing tires.
 - Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on.
 - Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily.
 - In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.
 - In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

Matching (uncontrolled and controlled) is explained below: Uncontrolled matching:

- Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

Controlled matching:

- With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching.
- Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm - ideally approx. 0.5 mm - are desirable.
- The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

New Tires (Replacements):

- If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, type and with the same specification code must always be used on each of the two axles.
- If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling.
- This is especially the case if new tires are mounted on the rear axle.
- This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire on the same axle by more than 30 %.

Refer to WM 449503 for specific details of the vehicle you are working on.

- >The 2mm specification will be given here.
- > If there is none listed then the default is 30%.

Repairs to Tires:

- If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.
- Repairs to "V", "W", "Y" and "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires.

Tire Aging:

- Tires age due to chemical and physical processes, which can impair their function.
- Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use.
- Hairline aging cracks can occur on older tires.
- On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.
- Therefore, attention should be paid not only to the tread depth but also to the age of the tire.
- Tires should not be older than 6 years.
- The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201= 22nd week of 2001.

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2025 Porsche Cars North America, Inc.