



# Technical Service Bulletin

SUBJECT:				No: <b>TSB-25-00-013</b>
<b>TECHNICAL SPECIFICATIONS - 2026 ECLIPSE CROSS</b>				DATE: <b>August 2025</b>
				MODEL: <b>2026 Eclipse Cross</b>
<b>CIRCULATE TO:</b>	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN	
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input checked="" type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER	

2026 ECLIPSE CROSS					
Feature Description	ES 1.5T S-AWC	LE 1.5T S-AWC	BLACK EDITION 1.5T S-AWC	SE 1.5T S-AWC	SEL 1.5T S-AWC
<b>Engine</b>					
Type	1.5L MIVEC DOHC 4-cylinder Direct-Injection Turbocharged 4B40 TC	1.5L MIVEC DOHC 4-cylinder Direct-Injection Turbocharged 4B40 TC	1.5L MIVEC DOHC 4-cylinder Direct-Injection Turbocharged 4B40 TC	1.5L MIVEC DOHC 4-cylinder Direct-Injection Turbocharged 4B40 TC	1.5L MIVEC DOHC 4-cylinder Direct-Injection Turbocharged 4B40 TC
Engine Code					
Materials	Aluminum block/ aluminum cylinder head	Aluminum block/ aluminum cylinder head	Aluminum block/ aluminum cylinder head	Aluminum block/ aluminum cylinder head	Aluminum block/ aluminum cylinder head
Bore x Stroke	75.0 mm x 84.8 mm	75.0 mm x 84.8 mm	75.0 mm x 84.8 mm	75.0 mm x 84.8 mm	75.0 mm x 84.8 mm
Compression Ratio	10.0:1	10.0:1	10.0:1	10.0:1	10.0:1
Displacement	1.5L / 1,499 cc	1.5L / 1,499 cc	1.5L / 1,499 cc	1.5L / 1,499 cc	1.5L / 1,499 cc
Horsepower	152 hp @ 5,500 rpm	152 hp @ 5,500 rpm	152 hp @ 5,500 rpm	152 hp @ 5,500 rpm	152 hp @ 5,500 rpm
Torque	184 lb.-ft. @ 2,000-3,500 rpm	184 lb.-ft. @ 2,000-3,500 rpm	184 lb.-ft. @ 2,000-3,500 rpm	184 lb.-ft. @ 2,000-3,500 rpm	184 lb.-ft. @ 2,000-3,500 rpm
Redline RPM	6000	6000	6000	6000	6000
Emissions	TIER3-BIN 125LEVV-LULEV125	TIER3-BIN 125LEVV-LULEV125	TIER3-BIN 125LEVV-LULEV125	TIER3-BIN 125LEVV-LULEV125	TIER3-BIN 125LEVV-LULEV125
Engine Oil Type	0W-20	0W-20	0W-20	0W-20	0W-20
Recommended Fuel Type	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded
Radiator Core size	687.3x400x27	687.3x400x27	687.3x400x27	687.3x400x27	687.3x400x27
<b>Transmission</b>					
8-speed CVT with Sport Mode	STD	STD	STD	STD	STD
CVT Automatic Ratios	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378
1st	2.631	2.631	2.631	2.631	2.631
2nd	1.765	1.765	1.765	1.765	1.765
3rd	1.313	1.313	1.313	1.313	1.313
4th	1.046	1.046	1.046	1.046	1.046
5th	0.843	0.843	0.843	0.843	0.843
6th	0.664	0.664	0.664	0.664	0.664
7th	0.518	0.518	0.518	0.518	0.518
8th	0.404	0.404	0.404	0.404	0.404
Reverse	1.960	1.960	1.960	1.960	1.960
Final Drive	6.386	6.386	6.386	6.386	6.386
<b>Suspension</b>					
Front	Macpherson strut with stabilizer bar	Macpherson strut with stabilizer bar	Macpherson strut with stabilizer bar	Macpherson strut with stabilizer bar	Macpherson strut with stabilizer bar
Rear	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar	Multi-link with stabilizer bar
<b>Steering</b>					
Type	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering
Overall Ratio	14.6	14.6	14.6	14.6	14.6
Turns, lock to lock	2.9	2.9	2.9	2.9	2.9
Turning circle	34.8ft	34.8 ft	34.8 ft	34.8 ft	34.8 ft
<b>Brakes/ Tires/ Wheels</b>					
Front	Ventilated disc, 11.6 in	Ventilated disc, 11.6 in	Ventilated disc, 11.6 in	Ventilated disc, 11.6 in	Ventilated disc, 11.6 in
Rear	Solid disc, 11.9 in	Solid disc, 11.9 in	Solid disc, 11.9 in	Solid disc, 11.9 in	Solid disc, 11.9 in
ABS	4-wheel, 4-channel, 4- sensors with Electronic Brake-force Distribution (EBD)	4-wheel, 4-channel, 4- sensors with Electronic Brake-force Distribution (EBD)	4-wheel, 4-channel, 4- sensors with Electronic Brake-force Distribution (EBD)	4-wheel, 4-channel, 4- sensors with Electronic Brake-force Distribution (EBD)	4-wheel, 4-channel, 4- sensors with Electronic Brake-force Distribution (EBD)
Wheels	16 x 6 1/2 J Aluminum alloy	18 x 7 J Black Painted Aluminum alloy	18 x 7 J Black Painted Aluminum alloy	18 x 7 J Aluminum alloy	18 x 7 J Aluminum alloy
Tires	P215/70 R16	P225/55 R18	P225/55 R18	P225/55 R18	P225/55 R18
Tire Brand	Falken	Bridgestone	Bridgestone	Bridgestone	Bridgestone
Temporary Spare Tire	T155/90D16 110M	T155/90D16 110M	T155/80D17 100M	T155/80D17 100M	T155/80D17 100M
<b>Exterior Dimensions</b>					
Wheelbase (inches)	105.1	105.1	105.1	105.1	105.1
Overall length (inches)	179.0	179.0	179.0	179.0	179.0
Overall width (inches)	71.1	71.1	71.1	71.1	71.1
Overall height (inches)	66.5	66.5	66.5	66.5	66.5
Track, front (inches)	60.6	60.6	60.6	60.6	60.6
Track, rear (inches)	60.6	60.6	60.6	60.6	60.6
Ground clearance (inches)	8.5	8.5	8.5	8.5	8.5
<b>Interior Dimensions</b>					
<b>Head Room (with Panoramic roof)</b>					
Front (inches)	39.5	39.5	39.5	39.5 (39.5)	39.5 (39.5)
Rear (inches)	37.3	37.3	37.3	37.3 (36.7)	37.3 (36.7)
<b>Leg room</b>					
Front (inches)	40.9	40.9	40.9	40.9	40.9
Rear (inches)	37.1	37.1	37.1	37.1	37.1
<b>Shoulder room</b>					
Front (inches)	56.2	56.2	56.2	56.2	56.2
Rear (inches)	55.1	55.1	55.1	55.1	55.1
<b>Hip room</b>					
Front (inches)	53.0	53.0	53.0	53.0	53.0
Rear (inches)	52.0	52.0	52.0	52.0	52.0

Copyright 2025, Mitsubishi Motors North America

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website ([www.mitsubishitechinfo.com](http://www.mitsubishitechinfo.com)).

**2026 ECLIPSE CROSS**

Feature Description	ES 1.5T S-AWC	LE 1.5T S-AWC	BLACK EDITION 1.5T S-AWC	SE 1.5T S-AWC	SEL 1.5T S-AWC
<b>SAE volume</b>					
SAE passenger volume (with Panoramic roof) (cu ft.)	96.7	96.7	96.7	96.7 (96.0)	96.7 (96.0)
SAE cargo volume - Behind front seats (with Panoramic roof) (cu ft.)	50.1	50.1	50.1	50.1 (49.7)	50.1 (49.7)
SAE cargo volume - Behind 2nd row seats (with Panoramic roof) (cu ft.)	23.4	23.4	23.4	23.4 (23.2)	23.4 (23.2)
<b>Capacities</b>					
Passenger Seating	5	5	5	5	5
Fuel	15.8 gallons	15.8 gallons	15.8 gallons	15.8 gallons	15.8 gallons
Oil	4.5 qt	4.5 qt	4.5 qt	4.5 qt	4.5 qt
Towing Capacity (lbs.)	1,500	1,500	1,500	1,500	1,500
Trailer Tongue Weight (lbs.)	150	150	150	150	150
<b>Weights</b>					
Curb Weight (lbs.)	3,406	3,450	3,483	3,483	3,483
GVWR (lbs.)	4,630	4,630	4,630	4,630	4,630
Weight distribution	5842	5842	5842	5842	5842
<b>Fuel Economy</b>					
City	25	25	25	25	25
Highway	28	26	26	26	26
Combined	26	25	25	25	25
<b>Warranties</b>					
Basic	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles	5-year / 60,000 miles
Limited Powertrain	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles	10-year / 100,000 miles
Anti-corrosion	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles	7-year / 100,000 miles
Roadside Assistance	5 year / Unlimited miles	5 year / Unlimited miles	5 year / Unlimited miles	5 year / Unlimited miles	5 year / Unlimited miles