
Subject:

RE: [External] US Electric tandem axles with a moffet

Good afternoon Bill,

Yes 4 total brackets due to the tank length, the 2 front will be for the steps and the 2 rear will be without. Below is pic of the unit.

This will be covered under warranty. I will policy if it is not.

Step height is not in any spec review to my knowledge other than build compat sets. Step height cannot exceed 24 inches from the ground, for the first step – DOT compliance rules.

When the concern was brought to my attention there were different measurements for the step and different options to remedy.

The first option was to remove the risers on the lower step – this increases the height to the second step though. The other option is to replace the tank hanger brackets dropping the tank and step assemblies.

Original brackets are a minus 419 mm
The new brackets are a minus 519 mm

100mm is approx. 3.94 inches.

Thank and step combos will come down approximately 4 inches and likely in alignment with the DEF tank.



-

Subject: Re: [External] US Electric tandem axles with a moffet

John, If I am reading this right, we need to order two each of the brackets. Two with step and two no step and just the 2 mudflaps that go under the half fender.

How far is it going to drop the steps? Is this covered under warranty? I don't recall ever seeing step height in any spec review I have been a part of.

Subject: RE: [External] US Electric tandem axles with a moffet

CAUTION: This email originated from outside of the organization. Do not click links or open attachments unless you recognize the sender and know the content is safe.

Good morning all,

Attached you will find the part numbers for brackets to lower the steps for this unit and install drawings. They can also be pulled from EZ wiring if needed.

This modification will ensure the step is within compliance. If the work is performed in house at Miller, I will update the annotations in Excellerator.

Please let me know if you have any questions.

