


Notes:

1. Axle Rating: (2) 4,400#
2. Safety Chains: 11,700#
3. Level Installation. Mount Both Roadside and Curbside 1/4" Down From The I-Beam Flange. Slide Arm Head: 173594 / 159624 / 105966.
4. Tapered Installation Mount Curbside 1/4" Down From The I-Beam Flange Tapering To 1/8" At The Roadside. Slide Arm Head: 173594 / 159624 / 105966.
5. Tapered Installation Mount Roadside 1/4" Down From The I-Beam Flange Tapering To 1/8" At The Curbside. Slide Arm Head: 173594 / 159624 / 105966.

LCI FRAME # 2021026745

Rev	Description	Date	ECN#	Title:	Date:
A	Released For Production / Redrawn In 3D	02/11/25	--	<b>Frame, Assembly</b> <b>Lippert Frame 8" I-Beam</b>	02/11/25
					Drawn By: <b>BCW</b>
TOLERANCES: UNLESS OTHERWISE STATED DIMS ARE IN INCHES .X = ± .1      FRACTIONS = ± 1/16 .XX = ± .01    ANGLES = ± .1°				Model Usage: <b>ALT-2600KRB</b>	Sheet: <b>1 of 4</b>
					Drawing No. <b>02-00165</b>