

**Approved: Wheels and Tires (14/26)**

Revision: This bulletin replaces bulletin Group 4 14/25, Dated September 16, 2025.

Model Year: **As of 2024**

Vehicle Type: **Panamera/Panamera 4/Panamera 4 E-Hybrid/Panamera 4S E-Hybrid/Panamera GTS/Panamera Turbo E-Hybrid/Panamera Turbo S E-Hybrid**

General Information: This Manufacturer's Certificate contains information about

- technically permissible wheel/tire combinations,
- measures that may be required when changing the wheel/tire combination mounted at the factory,
- approved original Porsche alloy wheels and
- approved summer, all-season and winter tires and their tire pressures.



**Information**

Self-sealing tires differ from conventional tires in that they have a self-adhesive, viscous layer that covers the inside of the tire from shoulder to shoulder. If a foreign body with a diameter of up to 5 mm penetrates the tread of a self-sealing tire, this layer closes in around the foreign body and prevents any air loss by immediately sealing the area. If the foreign body becomes dislodged from the tire, the self-adhesive viscous layer is designed to seal most puncture channels caused by foreign bodies with a diameter of up to 5 mm.

It is not intended as a permanent tire repair solution following a puncture and is not designed to allow tires to be driven under-inflated or flat.

- Regularly check self-sealing tires – just like any other tires – for signs of cuts, punctures and loss of tire pressure.
- Carefully remove foreign bodies from the tread.
- Replace damaged tires.



**Information**

In some countries, only tires with a speed index that safeguard the vehicle to at least the maximum vehicle speed are generally allowed to be mounted on the vehicle. Please check and observe the national regulations.

There may be national exemptions for winter tires with the marking 3PMSF (3 peak mountain snow flake), which also permit tires that do **not** safeguard to the maximum vehicle speed.

Porsche winter tires always have a 3PMSF marking and the speed index "V" (up to 240 km/h).



3PMSF

**Information**

"N..." = Specification code of the tire, e.g. "ND0", "ND1", "ND2" ... The complete "N ..." code of the relevant tire makes must be shown on the tire sidewall near the type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.

Arrow with inscription "Rotation"	= directional mounting
"Inside/Outside" inscription or "Left" or "Right"	= mounting on specified side only
Arrow with both inscriptions "Rotation" and "Inside/Outside"	= directional mounting on specified side only.
Arrow with inscriptions "Rotation" and "Left" or "Right"	= directional mounting on specified side only.

**Information**

As a general rule, Porsche does not recommend having tires repaired. Local legislation must always be observed.

It is advisable to install winter tires for temperatures below 7 °C (44 °F), because the driving characteristics of summer tires and UHP tires are reduced at low temperatures. Subfreezing temperatures can cause permanent damage to summer tires and UHP tires.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire by more than 30%. If this value is exceeded, we recommend that you replace both tires.

Cause: Approval status: April 2026

# Manufacturer's Certificate

Panamera (976)

14/26 ENU 4400

4

Sizes:

**Permissible tire and wheel sizes**

(RO = rim offset in mm, FA = front axle, RA = rear axle)

Tires	Tire sizes	Wheel sizes	Snow chains
<b>Panamera, Panamera 4, Panamera 4 E-Hybrid, Panamera 4S E-Hybrid</b>			
Summer	FA: 265/45 ZR 19 (105Y) XL RA: 295/40 ZR 19 (108Y) XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB).</b> <b>Not for vehicles with 410/420 GG brake.</b>  <b>Not for 4S E-Hybrid.</b>	FA: 9.0 J x 19, RO 64 RA: 10.5 J x 19, RO 62	No
	FA: 275/40 ZR 20(106Y) XL RA: 315/35 ZR 20 (110Y) XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	FA: 9.5 J x 20, RO 71 RA: 11.5 J x 20, RO 68	No
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL	FA: 9.5 J x 21, RO 71 RA: 11.5 J x 21, RO 69	No
Winter	FA: 265/45 R 19 105V XL RA: 295/40 R 19 108V XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB).</b> <b>Not for vehicles with 410/420 GG brake.</b>  <b>Not for 4S E-Hybrid.</b>	FA: 9.0 J x 19, RO 64 RA: 10.5 J x 19, RO 62	Yes
	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	FA: 9.5 J x 20, RO 71 RA: 10.5 J x 20, RO 71	Yes
	FA: 275/35 R 21 105V XL RA: 315/30 R 21 109V XL	FA: 9.5 J x 21, RO 71 RA: 10.5 J x 21, RO 71	Yes
All Season	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	FA: 9.5 J x 20, RO 71 RA: 11.5 J x 20, RO 68	No
	FA: 275/35 R 21 103V XL RA: 325/30 R 21 108V XL	FA: 9.5 J x 21, RO 71 RA: 11.5 J x 21, RO 69	No

Tires	Tire sizes	Wheel sizes	Snow chains
<b>Panamera GTS</b>			
Summer	FA: 275/40 ZR 20(106Y) XL RA: 315/35 ZR 20 (110Y) XL <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	FA: 9.5 J x 20, RO 71 RA: 11.5 J x 20, RO 68	No
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL	FA: 9.5 J x 21, RO 71 RA: 11.5 J x 21, RO 69	No
Winter	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	FA: 9.5 J x 20, RO 71 RA: 10.5 J x 20, RO 71	Yes
	FA: 275/35 R 21 105V XL RA: 315/30 R 21 109V XL	FA: 9.5 J x 21, RO 71 RA: 10.5 J x 21, RO 71	Yes
All Season	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	FA: 9.5 J x 20, RO 71 RA: 11.5 J x 20, RO 68	No
	FA: 275/35 R 21 103V XL RA: 325/30 R 21 108V XL	FA: 9.5 J x 21, RO 71 RA: 11.5 J x 21, RO 69	No
<b>Panamera Turbo E-Hybrid, Panamera Turbo S E-Hybrid</b>			
Summer	FA: 275/40 ZR 20(106Y) XL RA: 315/35 ZR 20 (110Y) XL <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b> <b>Not for Turbo S E-Hybrid</b>	FA: 9.5 J x 20, RO 71 RA: 11.5 J x 20, RO 68	No
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL	FA: 9.5 J x 21, RO 71 RA: 11.5 J x 21, RO 69	No
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL <b>Track tire</b>	FA: 9.5 J x 21, RO 71 RA: 11.5 J x 21, RO 69	No

# Manufacturer's Certificate

Panamera (976)

14/26 ENU 4400

4

Tires	Tire sizes	Wheel sizes	Snow chains
Winter	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>  <b>Not for Turbo S E-Hybrid</b>	FA: 9.5 J x 20, R0 71 RA: 10.5 J x 20, R0 71	Yes
	FA: 275/35 R 21 103V XL RA: 315/30 R 21 105V XL	FA: 9.5 J x 21, R0 71 RA: 10.5 J x 21, R0 71	Yes
All Season	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>  <b>Not for Turbo S E-Hybrid</b>	FA: 9.5 J x 20, R0 71 RA: 11.5 J x 20, R0 68	No
	FA: 275/35 R 21 103V XL RA: 325/30 R 21 108V XL	FA: 9.5 J x 21, R0 71 RA: 11.5 J x 21, R0 69	No

## Wheels:

**Overview of Porsche wheels for summer, winter and all-season tires**

Identification on the inside of the wheel:

Wheel size, rim offset (RO) in mm, part number (without color code marking FFF) and Porsche logo

**19-inch "Standard" wheel**

FA: 9.0 J x 19, RO 64

Part no. 976.601.025.\_\_\_FFF

RA: 10.5 J x 19, RO 62

Part no. 976.601.025.A\_\_FFF

*19-inch standard wheel***19-inch "S" wheel**

FA: 9.0 J x 19, RO 64

Part no. 976.601.025.K\_\_FFF

RA: 10.5 J x 19, RO 62

Part no. 976.601.025.L\_\_FFF

*19-inch S*

**20-inch "Turbo" wheel**

FA: 9.5 J x 20, RO 71

Part no. 976.601.025.F\_\_FFF

RA Summer: 11.5 J x 20, RO 68

Part no. 976.601.025.G\_\_FFF

RA Winter: 10.5 J x 20, RO 71

Part no. 976.698.025.C\_\_FFF



*20-inch Turbo*

**20-inch "Design" wheel**

FA: 9.5 J x 20, RO 71

Part no. 976.601.025.AM\_FFF or  
976.601.025.R\_FFF

RA: 11.5 J x 20, RO 68

Part no 976.601.025.AL\_FFF or  
976.601.025.S\_FFF



*20-inch Design*

**20-inch "S-PHEV" wheel**

FA: 9.5 J x 20, RO 71  
Part no. 976.601.025.AP\_FFF or  
976.601.025.D\_FFF

RA: 11.5 J x 20, RO 68  
Part no. 976.601.025.AN\_FFF or  
976.601.025.E\_FFF

*20-inch S-PHEV***21-inch "Sport Design" wheel**

FA: 9.5 J x 21, RO 71  
Part no.:  
976.601.025.M\_\_FFF or  
976.601.029.B\_\_FFF

RA Summer: 11.5 J x 21, RO 69  
Part no.:  
976.601.025.N\_\_FFF or  
976.601.029.C\_\_FFF

RA Winter: 10.5 J x 21, RO 71  
Part no. 976.698.025.A\_\_FFF

*21-inch Sport Design*

**21-inch "Exclusive Design" wheel**

FA: 9.5 J x 21, RO 71

Part no.:

976.601.025.AR\_FFF or

976.601.029\_\_FFF or

976.601.025.AA\_FFF

RA Summer: 11.5 J x 21, RO 69

Part no.:

976.601.025.AQ\_FFF or

976.601.029.A\_\_FFF or

976.601.025.AB\_FFF

RA Winter: 10.5 J x 21, RO 71

Part no.:

976.698.025.H\_\_FFF



*21-inch Exclusive Design*

**21-inch "Turbo 5" wheel**

FA Summer: 9.5 J x 21, RO 71  
Part no. 971.601.025.BR\_FFF

RA Summer: 11.5 J x 21, RO 69  
Part no.: 971.601.025.BS\_FFF



*21-inch Turbo 5*

**21-inch "ZV wheel"**

FA Summer: 9.5 J x 21, RO 71  
Part no.:  
976.601.025.T\_\_FFF

RA Summer: 11.5 J x 21, RO 69  
Part no.:  
976.601.025.Q\_\_FFF

RA Winter: 10.5 J x 21, RO 71  
Part no.:  
976.698.025.B\_\_FFF



*21-inch ZV wheel*

**Information**

Improper handling can damage the wheel surface.

Carry out tire removal and mounting using a bead holding-down device only.

Use a leather pad on the rim flange to support the valve insertion tool.

Only use the Porsche centring clamping set for balancing.

Do not use hard brushes to clean the wheels as these can cause deep scratches that cannot be removed by polishing.

Never use solvents or other chemical substances not approved by Porsche on tires.

**Information**

Only install wheels with identical part numbers on each axle.

Wheel mounting: **Tightening torque 160 Nm (118 ftlb.)**



**WARNING**

**Driving with different tires (mixed tires)**

- **Uncontrollable vehicle handling**

⇒ **Only use tires of the same make, type, speed index and the same specification code (ND0, ND1, ND2, etc.) on a vehicle.**

Summer Tires:

Model	Tire sizes	Tire make and type / Label value (Link to EU database)	
Spare wheel	155/70 R 20	Pirelli Spare Tire	
<b>Panamera, Panamera 4, Panamera 4 E-Hybrid, Panamera 4S E-Hybrid</b>	FA: 265/45 ZR 19 (105Y) XL RA: 295/40 ZR 19 (108Y) XL	Michelin Pilot Sport 4 ND0 (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/413186">https://eprel.ec.europa.eu/qr/413186</a> RA: <a href="https://eprel.ec.europa.eu/qr/409153">https://eprel.ec.europa.eu/qr/409153</a>	
	<b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB).  Not for vehicles with 410/420 GG brake.  Not for 4S E-Hybrid.</b>	Nexen N'Fera Sport ND0 FA: <a href="https://eprel.ec.europa.eu/qr/600649">HTTPS://EPREL.EC.EUROPA.EU/QR/600649</a> RA: <a href="https://eprel.ec.europa.eu/qr/600650">HTTPS://EPREL.EC.EUROPA.EU/QR/600650</a>	
		Hankook Ventus S1 EvoZ ND0 (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/476387">https://eprel.ec.europa.eu/qr/476387</a> RA: <a href="https://eprel.ec.europa.eu/qr/476409">https://eprel.ec.europa.eu/qr/476409</a>	
		Michelin Pilot Sport 4 S ND0 (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/410944">https://eprel.ec.europa.eu/qr/410944</a> RA: <a href="https://eprel.ec.europa.eu/qr/409314">https://eprel.ec.europa.eu/qr/409314</a>	
	<b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	FA: 275/40 ZR 20 (106Y) XL RA: 315/35 ZR 20 (110Y) XL	Hankook Ventus S1 EvoZ ND0 (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/476435">https://eprel.ec.europa.eu/qr/476435</a> RA: <a href="https://eprel.ec.europa.eu/qr/476433">https://eprel.ec.europa.eu/qr/476433</a>
			Pirelli Pzero ND0 (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/596642">https://eprel.ec.europa.eu/qr/596642</a> RA: <a href="https://eprel.ec.europa.eu/qr/596643">https://eprel.ec.europa.eu/qr/596643</a>
		FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL	Michelin Pilot Sport S5 ND0 FA: <a href="https://eprel.ec.europa.eu/qr/1341243">https://eprel.ec.europa.eu/qr/1341243</a> RA: <a href="https://eprel.ec.europa.eu/qr/1341242">https://eprel.ec.europa.eu/qr/1341242</a>

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
		Michelin Pilot Sport S5 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/2263654">HTTPS://EPREL.EC.EUROPA.EU/QR/2263654</a> RA: <a href="https://eprel.ec.europa.eu/qr/2263648">HTTPS://EPREL.EC.EUROPA.EU/QR/2263648</a>
		Bridgestone Potenza Sport NDO FA: <a href="https://eprel.ec.europa.eu/qr/502679">https://eprel.ec.europa.eu/qr/502679</a> RA: <a href="https://eprel.ec.europa.eu/qr/502875">https://eprel.ec.europa.eu/qr/502875</a>
		Continental Sport Contact 7 NDO FA: <a href="https://eprel.ec.europa.eu/qr/643904">https://eprel.ec.europa.eu/qr/643904</a> RA: <a href="https://eprel.ec.europa.eu/qr/643884">https://eprel.ec.europa.eu/qr/643884</a>
		Continental Sport Contact 7 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/1578143">HTTPS://EPREL.EC.EUROPA.EU/QR/1578143</a> RA: <a href="https://eprel.ec.europa.eu/qr/1578093">HTTPS://EPREL.EC.EUROPA.EU/QR/1578093</a>
		Hankook Ventus S1 EvoZ ND1 FA: RA:
<b>Panamera GTS</b>	FA: 275/40 ZR 20 (106Y) XL RA: 315/35 ZR 20 (110Y) XL  <b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	Michelin Pilot Sport 4 S NDO (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/410944">https://eprel.ec.europa.eu/qr/410944</a> RA: <a href="https://eprel.ec.europa.eu/qr/409314">https://eprel.ec.europa.eu/qr/409314</a>
		Hankook Ventus S1 EvoZ NDO (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/476435">https://eprel.ec.europa.eu/qr/476435</a> RA: <a href="https://eprel.ec.europa.eu/qr/476433">https://eprel.ec.europa.eu/qr/476433</a>
		Pirelli Pzero NDO (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/596642">https://eprel.ec.europa.eu/qr/596642</a> RA: <a href="https://eprel.ec.europa.eu/qr/596643">https://eprel.ec.europa.eu/qr/596643</a>
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL	Michelin Pilot Sport S5 NDO FA: <a href="https://eprel.ec.europa.eu/qr/1341243">https://eprel.ec.europa.eu/qr/1341243</a> RA: <a href="https://eprel.ec.europa.eu/qr/1341242">https://eprel.ec.europa.eu/qr/1341242</a>
		Michelin Pilot Sport S5 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/2263654">HTTPS://EPREL.EC.EUROPA.EU/QR/2263654</a>

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
		RA: <a href="https://eprel.ec.europa.eu/qr/2263648">HTTPS://EPREL.EC.EUROPA.EU/QR/2263648</a>
		Bridgestone Potenza Sport NDO FA: <a href="https://eprel.ec.europa.eu/qr/502679">https://eprel.ec.europa.eu/qr/502679</a> RA: <a href="https://eprel.ec.europa.eu/qr/502875">https://eprel.ec.europa.eu/qr/502875</a>
		Continental Sport Contact 7 NDO FA: <a href="https://eprel.ec.europa.eu/qr/643904">https://eprel.ec.europa.eu/qr/643904</a> RA: <a href="https://eprel.ec.europa.eu/qr/643884">https://eprel.ec.europa.eu/qr/643884</a>
		Continental Sport Contact 7 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/1578143">HTTPS://EPREL.EC.EUROPA.EU/QR/1578143</a> RA: <a href="https://eprel.ec.europa.eu/qr/1578093">HTTPS://EPREL.EC.EUROPA.EU/QR/1578093</a>
		Hankook Ventus S1 EvoZ ND1 FA: RA:
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL <b>UHP</b>	Pirelli Pzero R NDO FA: <a href="https://eprel.ec.europa.eu/qr/1955870">https://eprel.ec.europa.eu/qr/1955870</a> RA: <a href="https://eprel.ec.europa.eu/qr/1993330">https://eprel.ec.europa.eu/qr/1993330</a>
FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL <b>Track tire</b>	Michelin Pilot Sport Cup 2 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/1539365">https://eprel.ec.europa.eu/qr/1539365</a> RA: <a href="https://eprel.ec.europa.eu/qr/1539366">https://eprel.ec.europa.eu/qr/1539366</a>	
<b>Panamera Turbo E-Hybrid, Panamera Turbo S E-Hybrid</b>	FA: 275/40 ZR 20 (106Y) XL RA: 315/35 ZR 20 (110Y) XL	Michelin Pilot Sport 4 S NDO (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/410944">https://eprel.ec.europa.eu/qr/410944</a> RA: <a href="https://eprel.ec.europa.eu/qr/409314">https://eprel.ec.europa.eu/qr/409314</a>
	<b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	Hankook Ventus S1 EvoZ NDO (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/476435">https://eprel.ec.europa.eu/qr/476435</a> RA: <a href="https://eprel.ec.europa.eu/qr/476433">https://eprel.ec.europa.eu/qr/476433</a>
	<b>Not for Turbo S E-Hybrid</b>	Pirelli Pzero NDO (Inside/Outside) FA: <a href="https://eprel.ec.europa.eu/qr/596642">https://eprel.ec.europa.eu/qr/596642</a>

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
		RA: <a href="https://eprel.ec.europa.eu/qr/596643">https://eprel.ec.europa.eu/qr/596643</a>
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL	Michelin Pilot Sport S5 NDO FA: <a href="https://eprel.ec.europa.eu/qr/1341243">https://eprel.ec.europa.eu/qr/1341243</a> RA: <a href="https://eprel.ec.europa.eu/qr/1341242">https://eprel.ec.europa.eu/qr/1341242</a>
		Michelin Pilot Sport S5 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/2263654">HTTPS://EPREL.EC.EUROPA.EU/QR/2263654</a> RA: <a href="https://eprel.ec.europa.eu/qr/2263648">HTTPS://EPREL.EC.EUROPA.EU/QR/2263648</a>
		Bridgestone Potenza Sport NDO <b>Not for E-Hybrid derivatives *)</b> FA: <a href="https://eprel.ec.europa.eu/qr/502679">https://eprel.ec.europa.eu/qr/502679</a> RA: <a href="https://eprel.ec.europa.eu/qr/502875">https://eprel.ec.europa.eu/qr/502875</a>
		Continental Sport Contact 7 NDO FA: <a href="https://eprel.ec.europa.eu/qr/643904">https://eprel.ec.europa.eu/qr/643904</a> RA: <a href="https://eprel.ec.europa.eu/qr/643884">https://eprel.ec.europa.eu/qr/643884</a>
		Continental Sport Contact 7 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/1578143">HTTPS://EPREL.EC.EUROPA.EU/QR/1578143</a> RA: <a href="https://eprel.ec.europa.eu/qr/1578093">HTTPS://EPREL.EC.EUROPA.EU/QR/1578093</a>
		Hankook Ventus S1 EvoZ ND1 FA: RA:
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL <b>UHP</b>	Pirelli Pzero R NDO FA: <a href="https://eprel.ec.europa.eu/qr/1955870">https://eprel.ec.europa.eu/qr/1955870</a> RA: <a href="https://eprel.ec.europa.eu/qr/1993330">https://eprel.ec.europa.eu/qr/1993330</a>
	FA: 275/35 ZR 21 (103Y) XL RA: 325/30 ZR 21 (108Y) XL <b>Track tire</b>	Michelin Pilot Sport Cup 2 ND1 FA: <a href="https://eprel.ec.europa.eu/qr/1539365">https://eprel.ec.europa.eu/qr/1539365</a> RA: <a href="https://eprel.ec.europa.eu/qr/1539366">https://eprel.ec.europa.eu/qr/1539366</a>

\*) in conjunction with Porsche Active Suspension Management (PASM)

Winter Tires:

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
Panamera, Panamera 4, Panamera 4 E-Hybrid	FA: 265/45 R 19 105V XL RA: 295/40 R 19 108V XL	Continental Winter Contact TS860 S NDO FA: <a href="https://eprel.ec.europa.eu/qr/658969">https://eprel.ec.europa.eu/qr/658969</a> RA: <a href="https://eprel.ec.europa.eu/qr/658995">https://eprel.ec.europa.eu/qr/658995</a>
	<b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB).</b>  <b>Not for vehicles with 410/420 GG brake.</b>	Nexen Wingard Sport 2 NDO FA: <a href="https://eprel.ec.europa.eu/qr/1436042">https://eprel.ec.europa.eu/qr/1436042</a> RA: <a href="https://eprel.ec.europa.eu/qr/1436045">https://eprel.ec.europa.eu/qr/1436045</a>

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
Panamera, Panamera 4, Panamera 4 E-Hybrid, Panamera 4S E-Hybrid, Panamera GTS, Panamera Turbo E-Hybrid, Panamera Turbo S E-Hybrid	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL	Michelin Pilot Alpin 5 NDO FA: <a href="https://eprel.ec.europa.eu/qr/1446518">https://eprel.ec.europa.eu/qr/1446518</a> RA: <a href="https://eprel.ec.europa.eu/qr/1446523">https://eprel.ec.europa.eu/qr/1446523</a>
		Bridgestone Blizzak LM005 NDO FA: <a href="https://eprel.ec.europa.eu/qr/501803">https://eprel.ec.europa.eu/qr/501803</a> RA: <a href="https://eprel.ec.europa.eu/qr/501980">https://eprel.ec.europa.eu/qr/501980</a>
	FA: 275/35 R 21 105V XL RA: 315/30 R 21 109V XL	Pirelli Winter PZero NDO FA: <a href="https://eprel.ec.europa.eu/qr/2026498">https://eprel.ec.europa.eu/qr/2026498</a> RA: <a href="https://eprel.ec.europa.eu/qr/2026499">https://eprel.ec.europa.eu/qr/2026499</a>
		Continental Winter Contact TS860 S NDO FA: <a href="https://eprel.ec.europa.eu/qr/710387">https://eprel.ec.europa.eu/qr/710387</a> RA: <a href="https://eprel.ec.europa.eu/qr/710282">https://eprel.ec.europa.eu/qr/710282</a>
		Michelin Pilot Alpin 5 NDO FA: <a href="https://eprel.ec.europa.eu/qr/653763">https://eprel.ec.europa.eu/qr/653763</a> RA: <a href="https://eprel.ec.europa.eu/qr/653795">https://eprel.ec.europa.eu/qr/653795</a>

All-season Tires:

Model	Tire sizes	Tire make and type / Label value (Link to EU database)
Panamera, Panamera 4, Panamera 4 E-Hybrid, Panamera 4S E-Hybrid, Panamera GTS, Panamera Turbo E-Hybrid Panamera Turbo S E-Hybrid	FA: 275/40 R 20 106V XL RA: 315/35 R 20 110V XL	Michelin Pilot AS 4 NDO FA: <a href="https://eprel.ec.europa.eu/qr/1140637">https://eprel.ec.europa.eu/qr/1140637</a> RA: <a href="https://eprel.ec.europa.eu/qr/1210082">https://eprel.ec.europa.eu/qr/1210082</a>
	<b>Not for vehicles with Porsche Ceramic Composite Brake (PCCB)</b>	Hankook Ventus S1 EvoZ AS NDO FA: <a href="https://eprel.ec.europa.eu/qr/1017282">https://eprel.ec.europa.eu/qr/1017282</a> RA: <a href="https://eprel.ec.europa.eu/qr/1017307">https://eprel.ec.europa.eu/qr/1017307</a>
	<b>Not for Turbo S E-Hybrid</b>	Michelin Pilot AS 4 NDO EPREL Link is currently unavailable
	FA: 275/35 R 21 103V XL RA: 325/30 R 21 108V XL	Continental ProContact RX NDO FA: <a href="https://eprel.ec.europa.eu/qr/658792">https://eprel.ec.europa.eu/qr/658792</a> RA: <a href="https://eprel.ec.europa.eu/qr/658838">https://eprel.ec.europa.eu/qr/658838</a>

**WARNING****Incorrect tire pressure**

- **Uncontrollable vehicle handling**
- ⇒ **Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.**
- ⇒ **Check age of tires. Recommendation: Replace tires that are more than 6 years old.**
- ⇒ **Perform visual inspections.**
- ⇒ **Use only tires approved by Porsche.**

Tire Pressure:

**Information**

The tire pressure applies only to the tire makes and types approved by Porsche and is specified for cold tires (approx. 20 °C/ 68 °F). The tire pressure must not be lower than the specified values.

Standard tire pressure

Panamera	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
19-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.5 bar (36 psi)
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
21-inch summer tires	2.3 bar (33 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.4 bar (35 psi)
21-inch all-season tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)
19-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.5 bar (36 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.4 bar (35 psi)
21-inch winter tires	2.4 bar (35 psi)	2.3 bar (33 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)

Panamera 4	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
19-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.5 bar (36 psi)
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
21-inch summer tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.6 bar (38 psi)	2.5 bar (36 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)
21-inch all-season tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.6 bar (38 psi)	2.5 bar (36 psi)
19-inch winter tires	2.3 bar (33 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)
21-inch winter tires	2.5 bar (36 psi)	2.3 bar (33 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)

Panamera 4 E-Hybrid	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
19-inch summer tires	2.4 bar (35 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)	3.0 bar (44 psi)
20-inch summer tires	2.3 bar (33 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch summer tires	2.5 bar (36 psi)	2.7 bar (39 psi)	2.8 bar (41 psi)	3.0 bar (44 psi)
20-inch all-season tires	2.3 bar (33 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch all-season tires	2.5 bar (36 psi)	2.6 bar (38 psi)	2.7 bar (39 psi)	3.0 bar (44 psi)
19-inch winter tires	2.4 bar (35 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)	3.0 bar (44 psi)
20-inch winter tires	2.3 bar (33 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch winter tires	2.6 bar (38 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	3.0 bar (44 psi)

Panamera 4S E-Hybrid	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
20-inch summer tires	2.5 bar (36 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	3.1 bar (45 psi)
21-inch summer tires	2.7 bar (39 psi)	2.9 bar (42 psi)	2.9 bar (42 psi)	3.3 bar (48 psi)
20-inch all-season tires	2.3 bar (33 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch all-season tires	2.5 bar (36 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	3.0 bar (44 psi)
20-inch winter tires	2.3 bar (33 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch winter tires	2.6 bar (38 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	3.1 bar (45 psi)

Panamera GTS	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
20-inch summer tires	2.7 bar (39 psi)	2.5 bar (36 psi)	2.9 bar (42 psi)	2.9 bar (42 psi)
21-inch summer tires	3.0 bar (44 psi)	2.7 bar (39 psi)	3.2 bar (46 psi)	3.1 bar (45 psi)
20-inch all-season tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.6 bar (38 psi)	2.5 bar (36 psi)
21-inch all-season tires	2.6 bar (38 psi)	2.3 bar (33 psi)	2.8 bar (41 psi)	2.7 bar (39 psi)
20-inch winter tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.6 bar (38 psi)	2.5 bar (36 psi)
21-inch winter tires	2.6 bar (38 psi)	2.4 bar (35 psi)	2.8 bar (41 psi)	2.8 bar (41 psi)
21-inch Corsa	3.0 bar (44 psi)	2.7 bar (39 psi)	3.2 bar (46 psi)	3.1 bar (45 psi)

Panamera Turbo E-Hybrid 5 seat	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
20-inch summer tires	2.8 bar (41 psi)	2.9 bar (42 psi)	3.0 bar (44 psi)	3.2 bar (46 psi)
21-inch summer tires	3.1 bar (45 psi)	3.1 bar (45 psi)	3.3 bar (48 psi)	3.4 bar (49 psi)
20-inch all-season tires	2.5 bar (36 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)	2.9 bar (42 psi)
21-inch all-season tires	2.7 bar (39 psi)	2.8 bar (41 psi)	2.9 bar (42 psi)	3.1 bar (45 psi)
20-inch winter tires	2.5 bar (36 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)	2.9 bar (42 psi)
21-inch winter tires	2.7 bar (39 psi)	2.8 bar (41 psi)	2.8 bar (41 psi)	3.1 bar (45 psi)

Panamera Turbo E-Hybrid 4 seat	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
20-inch summer tires	2.8 bar (41 psi)	2.8 bar (41 psi)	3.0 bar (44 psi)	3.2 bar (46 psi)
21-inch summer tires	3.1 bar (45 psi)	3.0 bar (44 psi)	3.3 bar (48 psi)	3.4 bar (49 psi)

Panamera Turbo E-Hybrid 4 seat	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
20-inch all-season tires	2.5 bar (36 psi)	2.4 bar (35 psi)	2.6 bar (38 psi)	2.7 bar (39 psi)
21-inch all-season tires	2.7 bar (39 psi)	2.6 bar (38 psi)	2.9 bar (42 psi)	2.9 bar (42 psi)
20-inch winter tires	2.5 bar (36 psi)	2.4 bar (35 psi)	2.6 bar (38 psi)	2.7 bar (39 psi)
21-inch winter tires	2.7 bar (39 psi)	2.7 bar (39 psi)	2.8 bar (41 psi)	3.0 bar (44 psi)

Panamera Turbo S E-Hybrid 5-seater	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
21-inch summer tires	3.1 bar (45 psi)	3.0 bar (44 psi)	3.2 bar (46 psi)	3.4 bar (49 psi)
21-inch all-season tires	2.7 bar (39 psi)	2.7 bar (39 psi)	2.8 bar (41 psi)	3.0 bar (44 psi)
21-inch winter tires	2.7 bar (39 psi)	2.8 bar (41 psi)	2.8 bar (41 psi)	3.0 bar (44 psi)
21-inch Corsa	3.1 bar (45 psi)	3.0 bar (44 psi)	3.2 bar (46 psi)	3.4 bar (49 psi)

Panamera Turbo S E-Hybrid 4-seater	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
21-inch summer tires	3.0 bar (44 psi)	3.0 bar (44 psi)	3.2 bar (46 psi)	3.4 bar (49 psi)
21-inch all-season tires	2.7 bar (39 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)	2.9 bar (42 psi)
21-inch winter tires	2.7 bar (39 psi)	2.6 bar (38 psi)	2.8 bar (41 psi)	2.9 bar (42 psi)
21-inch Corsa	3.0 bar (44 psi)	3.0 bar (44 psi)	3.2 bar (46 psi)	3.4 bar (49 psi)

Panamera Executive	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
19-inch summer tires	2.3 bar (33 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.5 bar (36 psi)
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
21-inch summer tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
21-inch all-season tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)
19-inch winter tires	2.3 bar (33 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.5 bar (36 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.3 bar (33 psi)
21-inch winter tires	2.5 bar (36 psi)	2.3 bar (33 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)

Panamera 4 Executive	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
19-inch summer tires	2.3 bar (33 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.4 bar (35 psi)
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)	2.3 bar (33 psi)	2.2 bar (32 psi)
21-inch summer tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.6 bar (38 psi)	2.4 bar (35 psi)
20-inch all-season tires	2.3 bar (33 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.3 bar (33 psi)
21-inch all-season tires	2.5 bar (36 psi)	2.2 bar (32 psi)	2.6 bar (38 psi)	2.4 bar (35 psi)
19-inch winter tires	2.4 bar (35 psi)	2.2 bar (32 psi)	2.5 bar (36 psi)	2.4 bar (35 psi)
20-inch winter tires	2.3 bar (33 psi)	2.2 bar (32 psi)	2.4 bar (35 psi)	2.3 bar (33 psi)
21-inch winter tires	2.5 bar (36 psi)	2.3 bar (33 psi)	2.6 bar (38 psi)	2.5 bar (36 psi)

Panamera 4 E-Hybrid Executive	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
19-inch summer tires	2.5 bar (36 psi)	2.7 bar (39 psi)	2.6 bar (38 psi)	3.0 bar (44 psi)
20-inch summer tires	2.4 bar (35 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch summer tires	2.6 bar (38 psi)	2.7 bar (39 psi)	2.8 bar (41 psi)	3.0 bar (44 psi)
20-inch all-season tires	2.4 bar (35 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch all-season tires	2.6 bar (38 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	2.9 bar (42 psi)
19-inch winter tires	2.4 bar (35 psi)	2.7 bar (39 psi)	2.6 bar (38 psi)	2.9 bar (42 psi)
20-inch winter tires	2.4 bar (35 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch winter tires	2.6 bar (38 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	3.0 bar (44 psi)

Panamera 4 S E-Hybrid Executive	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
20-inch summer tires	2.6 bar (38 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	3.0 bar (44 psi)
21-inch summer tires	2.8 bar (41 psi)	2.9 bar (42 psi)	2.9 bar (42 psi)	3.2 bar (46 psi)
20-inch all-season tires	2.4 bar (35 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch all-season tires	2.6 bar (38 psi)	2.7 bar (39 psi)	2.7 bar (39 psi)	3.0 bar (44 psi)
20-inch winter tires	2.4 bar (35 psi)	2.5 bar (36 psi)	2.5 bar (36 psi)	2.8 bar (41 psi)
21-inch winter tires	2.6 bar (38 psi)	2.8 bar (41 psi)	2.7 bar (39 psi)	3.0 bar (44 psi)

Panamera Turbo E-Hybrid Executive	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
20-inch summer tires	2.9 bar (42 psi)	2.9 bar (42 psi)	3.0 bar (44 psi)	3.2 bar (46 psi)
21-inch summer tires	3.2 bar (46 psi)	3.1 bar (45 psi)	3.3 bar (48 psi)	3.4 bar (49 psi)
20-inch all-season tires	2.6 bar (38 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)	2.9 bar (42 psi)
21-inch all-season tires	2.8 bar (41 psi)	2.8 bar (41 psi)	2.9 bar (42 psi)	3.1 bar (45 psi)
20-inch winter tires	2.6 bar (38 psi)	2.6 bar (38 psi)	2.6 bar (38 psi)	2.9 bar (42 psi)
21-inch winter tires	2.8 bar (41 psi)	2.9 bar (42 psi)	2.9 bar (42 psi)	3.1 bar (45 psi)
21-inch Corsa	3.2 bar (46 psi)	3.1 bar (45 psi)	3.3 bar (48 psi)	3.4 bar (49 psi)

Panamera Turbo S E-Hybrid Executive	Part load		Full load	
	Front axle	Rear axle	Front axle	Rear axle
21-inch summer tires	3.2 bar (46 psi)	3.1 bar (45 psi)	3.3 bar (48 psi)	3.4 bar (49 psi)
21-inch all-season tires	2.8 bar (41 psi)	2.8 bar (41 psi)	2.9 bar (42 psi)	3.0 bar (44 psi)
21-inch winter tires	2.7 bar (39 psi)	2.8 bar (41 psi)	2.8 bar (41 psi)	3.0 bar (44 psi)
21-inch Corsa	3.2 bar (46 psi)	3.1 bar (45 psi)	3.3 bar (48 psi)	3.4 bar (49 psi)



**WARNING**

Driving at high speed with low tire pressure

- Irreparable damage to tires
- ⇒ Set comfort and performance air pressure for tires only on vehicles with "Comfort pressure" and "Performance pressure" selected in the instrument cluster.

**Information**

The permitted speed threshold for Comfort tire pressure depends on the vehicle's country equipment (c-option) and cannot be selected.

Comfort Tire  
Pressure up to  
160 km/h (100  
mph):

**Comfort tire pressure up to 160 km/h (100 mph)**

For vehicles with item "Comfort pressure" in the Tire Pressure Monitoring (TPM) system and speed threshold "160 km/h" ("100 mph").

<b>Panamera, Panamera 4</b>	<b>Front axle</b>	<b>Rear axle</b>
<b>19-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch all-season tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch all-season tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>19-inch winter tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch winter tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch winter tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)

<b>Panamera 4 E-Hybrid</b>	<b>Front axle</b>	<b>Rear axle</b>
<b>19-inch summer tires</b>	2.2 bar (32 psi)	2.3 bar (33 psi)
<b>20-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch summer tires</b>	2.2 bar (32 psi)	2.3 bar (33 psi)
<b>20-inch all-season tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)

Panamera 4 E-Hybrid	Front axle	Rear axle
21-inch all-season tires	2.2 bar (32 psi)	2.3 bar (33 psi)
19-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)

Panamera 4S E-Hybrid	Front axle	Rear axle
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch summer tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch winter tires	2.2 bar (32 psi)	2.4 bar (35 psi)

Panamera GTS	Front axle	Rear axle
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)

Panamera GTS	Front axle	Rear axle
21-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch Corsa	2.2 bar (32 psi)	2.2 bar (32 psi)

Panamera Turbo E-Hybrid 5 seat	Front axle	Rear axle
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch summer tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch Corsa	2.2 bar (32 psi)	2.3 bar (33 psi)

Panamera Turbo E-Hybrid 4 seat	Front axle	Rear axle
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)

Panamera Turbo E-Hybrid 4 seat	Front axle	Rear axle
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch Corsa	2.2 bar (32 psi)	2.2 bar (32 psi)

Panamera Turbo S E-Hybrid 5-seater	Front axle	Rear axle
21-inch summer tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch Corsa	2.2 bar (32 psi)	2.3 bar (33 psi)

Panamera Turbo S E-Hybrid 4-seater	Front axle	Rear axle
21-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch Corsa	2.2 bar (32 psi)	2.2 bar (32 psi)

Panamera Executive	Front axle	Rear axle
19-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)

<b>Panamera Executive</b>	<b>Front axle</b>	<b>Rear axle</b>
<b>21-inch all-season tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch winter tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)

<b>Panamera 4 Executive</b>	<b>Front axle</b>	<b>Rear axle</b>
<b>19-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch all-season tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch all-season tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>19-inch winter tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch winter tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch winter tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)

<b>Panamera 4 E-Hybrid Executive</b>	<b>Front axle</b>	<b>Rear axle</b>
<b>19-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>21-inch summer tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)
<b>20-inch all-season tires</b>	2.2 bar (32 psi)	2.2 bar (32 psi)

Panamera 4 E-Hybrid Executive	Front axle	Rear axle
21-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
19-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)

Panamera 4 S E-Hybrid Executive	Front axle	Rear axle
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch summer tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)

Panamera Turbo E-Hybrid Executive	Front axle	Rear axle
20-inch summer tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch summer tires	2.2 bar (32 psi)	2.3 bar (33 psi)
20-inch all-season tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.3 bar (33 psi)

Panamera Turbo E-Hybrid Executive	Front axle	Rear axle
20-inch winter tires	2.2 bar (32 psi)	2.2 bar (32 psi)
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch Corsa	2.2 bar (32 psi)	2.3 bar (33 psi)

Panamera Turbo S E-Hybrid Executive	Front axle	Rear axle
21-inch summer tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch all-season tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch winter tires	2.2 bar (32 psi)	2.3 bar (33 psi)
21-inch Corsa	2.2 bar (32 psi)	2.3 bar (33 psi)

**WARNING****Incorrectly installed snow chains**

- **Uncontrollable vehicle handling**
- ⇒ **Do not exceed top speed of 50 km/h (30 mph).**
- ⇒ **Read assembly instructions (see also EQUIPMENT accessory finder on the Internet).**
- ⇒ **Observe country-specific regulations.**

Snow Chains: Porsche offers the following snow chains as accessories:

Tire size	Porsche Part no.
295/40 R 19	971.044.690.A
315/35 R 20	971.044.690.B
315/30 R 21	971.044.690.B

Ease of operation of snow chains is only guaranteed for the tires specified above. Can only be mounted on the rear wheels.

- Wheel Storage:
- Tires must be stored in a cool, dry and dark room with adequate ventilation.
  - Tires must never come into contact with fuel, oil, grease or chemicals.
  - Do not store summer tires in storage areas with ambient temperatures of less than 5° F (-15° C).
  - Complete wheel & tire assemblies can be stacked for storage; we recommend that you increase the tire pressure by approximately 6 psi (0.4 bar).
  - Optimum conditions for storage of the complete wheels are provided by the Original Porsche storage trolley, Part No. 000.044.000.38.
  - If the tires are not mounted on wheels, it is best to store them in a vertical position.
  - We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots.
  - Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.

- General Information:
- Always use new valves when changing tires.
  - Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on.
  - Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily.
  - In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.
  - In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

**Matching (uncontrolled and controlled) is explained below: Uncontrolled matching:**

- Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

**Controlled matching:**

- With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching.
- Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm -ideally approx. 0.5 mm - are desirable.
- The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

**New Tires (Replacements):**

- If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, type and with the same specification code must always be used on each of the two axles.
- If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling.
- This is especially the case if new tires are mounted on the rear axle.
- This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire on the same axle by more than 30 %.

Refer to WM 449503 for specific details of the vehicle you are working on.

- >The 2mm specification will be given here.
- > If there is none listed then the default is 30%.

#### Repairs to Tires:

- If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.
- Repairs to "V", "W", "Y", and "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires.

#### Tire Aging:

- Tires age due to chemical and physical processes, which can impair their function.
- Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use.
- Hairline aging cracks can occur on older tires.
- On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.
- Therefore, attention should be paid not only to the tread depth but also to the age of the tire.
- Tires should not be older than 6 years.
- The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201= 22nd week of 2001.

**Important Notice:** Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2026 Porsche Cars North America, Inc.