

Charging fault - P292900 or P0AE173

Topic number	LI54.10-P-080684
Version	2
Function group	54.10 - Battery, power supply, voltage converter
Date	8/6/26
Validity	Model 465.600
Reason for change	New findings and expansion for P0AE173

Complaint

When disconnecting or connecting the charging connector, the charging socket flashes red and red warning messages are displayed in the instrument cluster. Immediately after that, neither driving nor charging is possible.

Cause

P292900:

If the charging cable connector is removed approximately 5 to 7 seconds after the charging process has ended, a fault is triggered.

Remedy

If this fault occurs, please follow these steps:

- 1) Wait for bus idle -> driving should be possible again. Note: Charging is still not possible. The fault will keep recurring as long as the fault is stored in the fault memory.
- 2) Plug in charging cable and check if fault (P292900 or P0AE173) is active. Clear active fault. Charging should be possible after the fault has been cleared.

To prevent the fault from recurring, after the charging process has ended, wait at least 15 seconds before disconnecting the AC charging cable connector.

Please create a TIPS case including quick test and HV control module log.

Disclaimer

NOTE: The information contained in this document is intended for use by trained, professional technicians with the knowledge to properly and safely perform diagnosis and repairs on Mercedes-Benz vehicles, using Mercedes-Benz approved tools and equipment. It informs service technicians about conditions that could occur in certain vehicles and provides information that could assist in proper vehicle diagnosis, service, or repair. It does not indicate that a defect is present in any vehicle referenced in this document nor does it imply warranty coverage. DO NOT assume that a

symptom or condition, or a described cause of a symptom or condition, affects any particular vehicle or groups of vehicles, or that a described repair applies to any particular vehicle or groups of vehicles. There can be multiple causes resulting in the same or similar symptoms or conditions described in this document, and trained professional service technicians must use their diagnostic skills to make evaluations on a case-by-case basis. The information contained in this document does not guarantee warranty coverage nor does it extend the vehicle's warranty in any way.

Symptoms
Overall vehicle > Power supply > Battery/On-board electrical system > Battery/on-board electrical system indicator lamp > Battery charge indicator/consumer shutoff > Illuminates red
Overall vehicle > Power supply > High-voltage on-board electrical system > High-voltage battery > Display message
Overall vehicle > Power supply > High-voltage on-board electrical system > Charging > Charging socket > Red LED lights up
Power generation > Engine management > Function > Electric drive does not start

Control unit/fault code	
Control unit	Fault text
N82/9 - Battery management system (BMS) (BMS465)	P0AE173 - The switch 'Precharging' in the hybrid/high-voltage battery module has an electrical fault. The actuator does not open. P292900 - Contact 'Negative terminal' of contactor B in the high-voltage battery is jammed closed. _
N127 - Control unit "Drivetrain" (PTCU) (CPC3)	P154B00 - There is a warning due to a stuck contactor. _

Operation numbers/damage codes				
Op. no.	Operation text	Time	Damage code	Note